

# RedBoot™ User's Guide

## RedBoot™ User's Guide

Copyright © 2001, 2002, 2003 Red Hat, Inc.

### Documentation licensing terms

This material may be distributed only subject to the terms and conditions set forth in the Open Publication License, v1.0 or later (the latest version is presently available at <http://www.opencontent.org/openpub/>).

Distribution of substantively modified versions of this document is prohibited without the explicit permission of the copyright holder. Distribution of the work or derivative of the work in any standard (paper) book form is prohibited unless prior permission is obtained from the copyright holder.

### Trademarks

Red Hat, the Red Hat Shadow Man logo®, eCos™, RedBoot™, GNUPro®, and Insight™ are trademarks of Red Hat, Inc.

Sun Microsystems® and Solaris® are registered trademarks of Sun Microsystems, Inc.

SPARC® is a registered trademark of SPARC International, Inc., and is used under license by Sun Microsystems, Inc.

Intel® is a registered trademark of Intel Corporation.

Motorola™ is a trademark of Motorola, Inc.

ARM® is a registered trademark of Advanced RISC Machines, Ltd.

MIPS™ is a trademark of MIPS Technologies, Inc.

Toshiba® is a registered trademark of the Toshiba Corporation.

NEC® is a registered trademark of the NEC Corporation.

Cirrus Logic® is a registered trademark of Cirrus Logic, Inc.

Compaq® is a registered trademark of the Compaq Computer Corporation.

Matsushita™ is a trademark of the Matsushita Electric Corporation.

Samsung® and CalmRISC™ are trademarks or registered trademarks of Samsung, Inc.

Linux® is a registered trademark of Linus Torvalds.

UNIX® is a registered trademark of The Open Group.

Microsoft®, Windows®, and Windows NT® are registered trademarks of Microsoft Corporation, Inc.

All other brand and product names, trademarks, and copyrights are the property of their respective owners.

### Warranty

eCos and RedBoot are open source software, covered by a modified version of the GNU General Public License

(<http://www.gnu.org/copyleft/gpl.html>), and you are welcome to change it and/or distribute copies of it under certain conditions. See <http://sources.redhat.com/ecos/license-overview.html> for more information about the license.

eCos and RedBoot software have NO WARRANTY.

Because this software is licensed free of charge, there are no warranties for it, to the extent permitted by applicable law. Except when otherwise stated in writing, the copyright holders and/or other parties provide the software “as is” without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. The

entire risk as to the quality and performance of the software is with you. Should the software prove defective, you assume the cost of all necessary servicing, repair or correction.

In no event, unless required by applicable law or agreed to in writing, will any copyright holder, or any other party who may modify and/or redistribute the program as permitted above, be liable to you for damages, including any general, special, incidental or consequential damages arising out of the use or inability to use the program (including but not limited to loss of data or data being rendered inaccurate or losses sustained by you or third parties or a failure of the program to operate with any other programs), even if such holder or other party has been advised of the possibility of such damages.



# Table of Contents

<b>I. RedBoot™ User's Guide.....</b>	<b>xvii</b>
1. Getting Started with RedBoot .....	1
More information about RedBoot on the web .....	1
Installing RedBoot.....	2
User Interface .....	2
RedBoot Editing Commands .....	2
RedBoot Startup Mode .....	3
RedBoot Resource Usage .....	4
Flash Resources .....	5
RAM Resources .....	5
Configuring the RedBoot Environment .....	6
Target Network Configuration .....	7
Host Network Configuration.....	8
Enable TFTP on Red Hat Linux 6.2.....	8
Enable TFTP on Red Hat Linux 7 (or newer) .....	8
Enable BOOTP/DHCP server on Red Hat Linux.....	9
Enable DNS server on Red Hat Linux .....	10
RedBoot network gateway .....	11
Verification .....	12
2. RedBoot Commands and Examples.....	13
Introduction .....	13
Common Commands .....	15
alias .....	16
baudrate.....	19
cache .....	21
channel .....	23
cksum .....	25
disks .....	27
dump .....	29
help.....	33
ip_address .....	37
load.....	39
mcmp.....	43
mfill .....	45
ping .....	47
reset.....	49
version.....	51
Flash Image System (FIS) .....	53
fis init .....	53
fis list.....	55
fis free.....	57

fis create .....	59
fis load .....	63
fis delete .....	65
fis lock .....	67
fis unlock .....	69
fis erase .....	71
fis write .....	73
Persistent State Flash-based Configuration and Control .....	75
Executing Programs from RedBoot .....	79
go .....	80
exec .....	83
3. Rebuilding RedBoot .....	85
Introduction .....	85
Rebuilding RedBoot using ecosconfig .....	85
Rebuilding RedBoot from the Configuration Tool .....	86
4. Updating RedBoot .....	89
Introduction .....	89
Load and start a RedBoot RAM instance .....	89
Update the primary RedBoot flash image .....	90
Reboot; run the new RedBoot image .....	92
5. Installation and Testing .....	93
AM3x/MN103E010 Matsushita MN103E010 (AM33/2.0) ASB2305 Board .....	93
Overview .....	93
Initial Installation .....	93
Preparing to program the board .....	93
Preparing to use the JTAG debugger .....	94
Loading the RAM-based RedBoot via JTAG .....	94
Loading the boot PROM-based RedBoot via the RAM mode RedBoot	
96	
Additional Commands .....	97
Memory Maps .....	98
Rebuilding RedBoot .....	98
ARM/ARM7 ARM Evaluator7T .....	99
Overview .....	99
Initial Installation .....	99
Quick download instructions .....	99
Special RedBoot Commands .....	100
Memory Maps .....	100
Rebuilding RedBoot .....	101
ARM/ARM7+ARM9 ARM Integrator .....	101
Overview .....	101
Initial Installation .....	101
Quick download instructions .....	102

Special RedBoot Commands .....	103
Memory Maps .....	103
Rebuilding RedBoot.....	104
ARM/ARM7+ARM9 ARM PID Board and EPI Dev7+Dev9 .....	104
Overview .....	104
Initial Installation Method.....	105
Special RedBoot Commands .....	105
Memory Maps .....	105
Rebuilding RedBoot.....	105
ARM/ARM7 Atmel AT91 Evaluation Board (EB40) .....	106
Overview .....	106
Initial Installation Method.....	106
Special RedBoot Commands .....	108
Memory Maps .....	108
Rebuilding RedBoot.....	108
ARM/ARM7 Cirrus Logic EP7xxx (EDB7211, EDB7212, EDB7312) .....	108
Overview .....	109
Initial Installation Method.....	109
Special RedBoot Commands .....	109
Memory Maps .....	109
Platform Resource Usage.....	110
Rebuilding RedBoot.....	110
ARM/ARM9 Agilent AAED2000.....	111
Overview .....	111
Initial Installation Method.....	111
RedBoot as Primary Bootmonitor .....	112
Special RedBoot Commands .....	113
Memory Maps .....	114
Rebuilding RedBoot.....	115
ARM/ARM9 Cirrus Logic SEB9312 (EP93xx) (aka SEB9213) .....	115
Overview .....	115
Initial Installation Method.....	116
Special RedBoot Commands .....	116
Memory Maps .....	116
Rebuilding RedBoot.....	117
ARM/StrongARM(SA110) Intel EBSA 285 .....	117
Overview .....	118
Initial Installation Method.....	118
Communication Channels .....	118
Special RedBoot Commands .....	118
Memory Maps .....	118
Platform Resource Usage.....	119
Rebuilding RedBoot.....	119

ARM/StrongARM(SA1100) Intel Brutus .....	119
Overview .....	120
Initial Installation Method.....	120
Special RedBoot Commands .....	120
Memory Maps.....	120
Platform Resource Usage.....	121
Rebuilding RedBoot.....	121
ARM/StrongARM(SA1100) Intel SA1100 Multimedia Board .....	121
Overview .....	122
Initial Installation Method.....	122
Special RedBoot Commands .....	122
Memory Maps.....	122
Platform Resource Usage.....	123
Rebuilding RedBoot.....	123
ARM/StrongARM(SA1110) ASCOM/ACN PLC2 Board.....	124
Overview .....	124
Initial Installation Method.....	124
Special RedBoot Commands .....	125
Memory Maps.....	125
Rebuilding RedBoot.....	126
ARM/StrongARM(SA1110) Intel SA1110 (Assabet).....	126
Overview .....	126
Initial Installation Method.....	127
Special RedBoot Commands .....	127
Memory Maps.....	127
Platform Resource Usage.....	128
Rebuilding RedBoot.....	128
ARM/StrongARM(SA11X0) Bright Star Engineering commEngine and nanoEngine .....	128
Overview .....	128
Initial Installation.....	129
Download Instructions .....	129
Cohabiting with POST in Flash.....	130
Special RedBoot Commands .....	131
Memory Maps.....	131
Nano Platform Port .....	133
Ethernet Driver.....	133
Rebuilding RedBoot.....	133
ARM/StrongARM(SA11X0) Compaq iPAQ PocketPC.....	134
Overview .....	134
Initial Installation .....	134
Installing RedBoot on the iPAQ using Windows/CE .....	134
Installing RedBoot on the iPAQ - using the Compaq boot loader.....	135

Setting up and testing RedBoot.....	135
Installing RedBoot permanently.....	136
Restoring Windows/CE.....	137
Additional commands.....	137
Memory Maps.....	138
Rebuilding RedBoot.....	138
ARM/StrongARM(SA11X0) Intrinsyc CerfCube.....	139
Overview.....	139
Initial Installation.....	139
Additional commands.....	140
Memory Maps.....	140
Rebuilding RedBoot.....	141
ARM/StrongARM(SA11X0) Symbol PPT2800 Series Portable Pen Terminal....	141
Overview.....	142
Initial Installation.....	142
Installing RedBoot on the PPT2800 using the IPL.....	142
Restoring the IPL.....	143
Additional commands.....	143
Memory Maps.....	144
Rebuilding RedBoot.....	145
ARM/Xscale Cyclone IQ80310.....	145
Overview.....	145
Initial Installation Method.....	146
Error codes.....	147
Using RedBoot with ARM Bootloader.....	147
Special RedBoot Commands.....	147
IQ80310 Hardware Tests.....	148
Rebuilding RedBoot.....	149
Interrupts.....	149
Memory Maps.....	151
Platform Resource Usage.....	152
ARM/Xscale Intel IQ80321.....	152
Overview.....	152
Initial Installation Method.....	153
Switch Settings.....	153
LED Codes.....	154
Special RedBoot Commands.....	156
Memory Tests.....	157
Repeating Memory Tests.....	157
Repeat-On-Fail Memory Tests.....	157
Rotary Switch S1 Test.....	158
7 Segment LED Tests.....	158
i82544 Ethernet Configuration.....	158

Battery Status Test.....	158
Battery Backup SDRAM Memory Test .....	159
Timer Test.....	159
PCI Bus Test.....	159
CPU Cache Loop.....	159
Rebuilding RedBoot.....	159
Interrupts .....	159
Memory Maps.....	161
Platform Resource Usage.....	162
ARM/Xscale Intel DBPXA27XC0.....	162
Overview .....	162
Initial Installation Method.....	163
Switch Settings .....	163
LED Codes.....	164
Rebuilding RedBoot.....	165
Interrupts .....	165
Memory Maps.....	167
Platform Resource Usage.....	168
CalmRISC/CalmRISC16 Samsung CalmRISC16 Core Evaluation Board.....	168
Overview .....	168
Initial Installation Method.....	169
Special RedBoot Commands .....	169
Special Note on Serial Channel .....	169
Rebuilding RedBoot.....	169
CalmRISC/CalmRISC32 Samsung CalmRISC32 Core Evaluation Board.....	170
Overview .....	170
Initial Installation Method.....	170
Special RedBoot Commands .....	171
Special Note on Serial Channel .....	171
Rebuilding RedBoot.....	171
FRV/FRV400 Fujitsu FR-V 400 (MB-93091).....	172
Overview .....	172
Initial Installation Method.....	172
Special RedBoot Commands .....	172
Memory Maps.....	173
Rebuilding RedBoot.....	173
IA32/x86 x86-Based PC.....	173
Overview .....	174
Initial Installation.....	174
Flash management .....	175
Special RedBoot Commands .....	175
Memory Maps.....	175
Rebuilding RedBoot.....	175

MIPS/MIPS32(CoreLV 4Kc)+MIPS64(CoreLV 5Kc) Atlas Board .....	175
Overview .....	176
Initial Installation .....	176
Quick download instructions .....	176
Atlas download format .....	177
Flash management .....	177
Additional config options .....	177
Additional commands .....	178
Interrupts .....	178
Memory Maps .....	179
Rebuilding RedBoot.....	179
MIPS/MIPS32(CoreLV 4Kc)+MIPS64(CoreLV 5Kc) Malta Board.....	180
Overview .....	180
Initial Installation .....	180
Quick download instructions .....	181
Malta download format .....	181
Additional commands .....	181
Interrupts .....	182
Memory Maps .....	183
Rebuilding RedBoot.....	184
MIPS/RM7000 PMC-Sierra Ocelot .....	184
Overview .....	184
Additional commands .....	184
Memory Maps .....	185
Rebuilding RedBoot.....	186
MIPS/UPD985XX ASCOM LAKI Board .....	186
Overview .....	186
Initial Installation Method.....	186
Run the RAM mode RedBoot .....	187
Initialize the Flash .....	188
Install POST RedBoot in flash .....	188
Install RedBoot in the boot block.....	189
Flash management .....	189
Updating the POST RedBoot image .....	190
Starting RedBoot from ASCOM Boot image .....	190
Communication Channels .....	190
Special RedBoot Commands .....	190
Memory Maps .....	191
Rebuilding RedBoot.....	191
MIPS/VR4375 NEC DDB-VRC4375 .....	191
Overview .....	192
Initial Installation Method.....	192
Special RedBoot Commands .....	192

Memory Maps .....	192
Ethernet Driver .....	193
Rebuilding RedBoot .....	193
PowerPC/MPC860T Analogue & Micro PowerPC 860T .....	194
Overview .....	194
Initial Installation Method .....	194
Special RedBoot Commands .....	194
Memory Maps .....	194
Rebuilding RedBoot .....	195
PowerPC/MPC8XX Motorola MBX .....	195
Overview .....	195
Initial Installation Method .....	196
Special RedBoot Commands .....	196
Memory Maps .....	197
Rebuilding RedBoot .....	197
SuperH/SH2(SH7615) Control SerHub1 .....	197
Overview .....	197
Initial Installation Method .....	198
Special RedBoot Commands .....	199
Memory Maps .....	200
Ethernet Driver .....	200
Rebuilding RedBoot .....	200
SuperH/SH2(SH7044) Alpha Project AP-SH2F-2A .....	201
Overview .....	201
Initial Installation Method .....	201
Memory Maps .....	201
Rebuilding RedBoot .....	201
SuperH/SH3(SH7708) Hitachi EDK7708 .....	201
Overview .....	202
Initial Installation Method .....	202
Memory Maps .....	202
Rebuilding RedBoot .....	202
SuperH/SH3(SH7709) Hitachi Solution Engine 7709 .....	203
Overview .....	203
Initial Installation Method .....	203
Special RedBoot Commands .....	204
Memory Maps .....	205
Ethernet Driver .....	205
Rebuilding RedBoot .....	205
SuperH/SH3(SH7729) Hitachi HS7729PCI .....	206
Overview .....	206
Initial Installation Method .....	206
Special RedBoot Commands .....	207

Memory Maps .....	208
Rebuilding RedBoot.....	208
SuperH/SH3(SH77X9) Hitachi Solution Engine 77X9 .....	209
Overview .....	209
Initial Installation Method.....	209
Special RedBoot Commands .....	210
Memory Maps .....	211
Ethernet Driver.....	211
Rebuilding RedBoot.....	211
SuperH/SH4(SH7751) Hitachi Solution Engine 7751 .....	211
Overview .....	212
Initial Installation Method.....	212
Special RedBoot Commands .....	213
Memory Maps .....	213
Ethernet Driver.....	214
Rebuilding RedBoot.....	214



# List of Examples

1-1. Sample DHCP configuration file.....	9
1-2. Sample <code>/etc/named.conf</code> for Red Hat Linux 7.x.....	10



# I. RedBoot™ User's Guide



# Chapter 1. Getting Started with RedBoot

RedBoot™ is an acronym for "Red Hat Embedded Debug and Bootstrap", and is the standard embedded system debug/bootstrap environment from Red Hat, replacing the previous generation of debug firmware: CygMon and GDB stubs. It provides a complete bootstrap environment for a range of embedded operating systems, such as embedded Linux™ and eCos™, and includes facilities such as network downloading and debugging. It also provides a simple flash file system for boot images.

RedBoot provides a wide set of tools for downloading and executing programs on embedded target systems, as well as tools for manipulating the target system's environment. It can be used for both product development (debug support) and for end product deployment (flash and network booting).

Here are some highlights of RedBoot's capabilities:

- Boot scripting support
- Simple command line interface for RedBoot configuration and management, accessible via serial (terminal) or Ethernet (telnet)
- Integrated GDB stubs for connection to a host-based debugger via serial or ethernet. (Ethernet connectivity is limited to local network only)
- Attribute Configuration - user control of aspects such as system time and date (if applicable), default Flash image to boot from, default failsafe image, static IP address, etc.
- Configurable and extensible, specifically adapted to the target environment
- Network bootstrap support including setup and download, via BOOTP, DHCP and TFTP
- X/YModem support for image download via serial
- Power On Self Test

Although RedBoot is derived from eCos, it may be used as a generalized system debug and bootstrap control software for any embedded system and any operating system. For example, with appropriate additions, RedBoot could replace the commonly used BIOS of PC (and certain other) architectures. Red Hat is currently installing RedBoot on all embedded platforms as a standard practice, and RedBoot is now generally included as part of all Red Hat Embedded Linux and eCos ports. Users who specifically wish to use RedBoot with the eCos operating system should refer to the *Getting Started with eCos* document, which provides information about the portability and extendability of RedBoot in an eCos environment.

## More information about RedBoot on the web

Information about the RedBoot product, including information about details of porting, cus-

tomization, training and technical support services from Red Hat, is available from the RedBoot Product web site (<http://www.redhat.com/embedded/technologies/redboot/>).

The RedBoot Net Distribution web site (<http://sources.redhat.com/redboot/>) contains downloadable sources and documentation for all publically released targets, including the latest features and updates.

## Installing RedBoot

To install the RedBoot package, follow the procedures detailed in the accompanying README.

Although there are other possible configurations, RedBoot is usually run from the target platform's flash boot sector or boot ROM, and is designed to run when your system is initially powered on. The method used to install the RedBoot image into non-volatile storage varies from platform to platform. In general, it requires that the image be programmed into flash in situ or programmed into the flash or ROM using a device programmer. In some cases this will be done at manufacturing time; the platform being delivered with RedBoot already in place. In other cases, you will have to program RedBoot into the appropriate device(s) yourself. Installing to flash in situ may require special cabling or interface devices and software provided by the board manufacturer. The details of this installation process for a given platform will be found in Installation and Testing. Once installed, user-specific configuration options may be applied, using the **fconfig** command, providing that persistent data storage in flash is present in the relevant RedBoot version. See the Section called *Configuring the RedBoot Environment* for details.

## User Interface

RedBoot provides a command line user interface (CLI). At the minimum, this interface is normally available on a serial port on the platform. If more than one serial interface is available, RedBoot is normally configured to try to use any one of the ports for the CLI. Once command input has been received on one port, that port is used exclusively until the board is reset or the channel is manually changed by the user. If the platform has networking capabilities, the RedBoot CLI is also accessible using the `telnet` access protocol. By default, RedBoot runs `telnet` on port TCP/9000, but this is configurable and/or settable by the user.

RedBoot also contains a set of GDB "stubs", consisting of code which supports the GDB remote protocol. GDB stub mode is automatically invoked when the '\$' character appears anywhere on a command line unless escaped using the '\\$' character. The platform will remain in GDB stub mode until explicitly disconnected (via the GDB protocol). The GDB stub mode is available regardless of the connection method; either serial or network. Note that if a GDB connection is made via the network, then special care must be taken to preserve that connection when running user code. eCos contains special network sharing code to allow for this situation, and can be used as a model if this methodology is required in other OS environments.

# RedBoot Editing Commands

RedBoot uses the following line editing commands.

**NOTE:** In this description, ^A means the character formed by typing the letter "A" while holding down the control key.

- Delete (0x7F) or Backspace (0x08) erases the character to the left of the cursor.
- ^A moves the cursor (insertion point) to the beginning of the line.
- ^K erases all characters on the line from the cursor to the end.
- ^E positions the cursor to the end of the line.
- ^D erases the character under the cursor.
- ^F moves the cursor one character to the right.
- ^B moves the cursor one character to the left.
- ^P replaces the current line by a previous line from the history buffer. A small number of lines can be kept as history. Using ^P (and ^N), the current line can be replaced by any one of the previously typed lines.
- ^N replaces the current line by the next line from the history buffer.

In the case of the **fconfig** command, additional editing commands are possible. As data are entered for this command, the current/previous value will be displayed and the cursor placed at the end of that data. The user may use the editing keys (above) to move around in the data to modify it as appropriate. Additionally, when certain characters are entered at the end of the current value, i.e. entered separately, certain behavior is elicited.

- ^ (caret) switch to editing the previous item in the **fconfig** list. If fconfig edits item A, followed by item B, pressing ^ when changing item B, allows you to change item A. This is similar to the up arrow. Note: ^P and ^N do not have the same meaning while editing **fconfig** data and should not be used.
- . (period) stop editing any further items. This does not change the current item.
- Return leaves the value for this item unchanged. Currently it is not possible to step through the value for the start-up script; it must always be retyped.

## RedBoot Startup Mode

RedBoot can normally be configured to run in a number of startup modes (or just "modes" for short), determining its location of residence and execution:

### ROM mode

In this mode, RedBoot both resides and executes from ROM memory (flash or EPROM). This mode is used when there are limited RAM resources. The flash commands cannot update the region of flash where the RedBoot image resides. In order to update the RedBoot image in flash, it is necessary to run a RAM mode instance of RedBoot.

### ROMRAM mode

In this mode, RedBoot resides in ROM memory (flash or EPROM), but is copied to RAM memory before it starts executing. The RAM footprint is larger than for ROM mode, but there are two advantages to make up for this: it normally runs faster (relevant only on slower boards) and it is able to update the flash region where the image resides.

### RAM mode

In this mode, RedBoot both resides and executes from RAM memory. This is used for updating a primary ROM mode image in situ and sometimes as part of the RedBoot installation on the board when there's already an existing (non-RedBoot) boot monitor available.

You can only use ROM and ROMRAM mode images for booting a board - a RAM mode image cannot run unless loaded by another ROM monitor. There is no need for this startup mode if a RedBoot ROMRAM mode image is the primary boot monitor. When this startup mode is programmed into flash (as a convenience as it's fast to load from flash) it will generally be named as "RedBoot[RAM]" in the FIS directory.

The chosen mode has influence on flash and RAM resource usage (see the Section called *RedBoot Resource Usage*) and the procedure of an in situ update of RedBoot in flash (see Chapter 4).

The startup mode is controlled by the option `CYG_HAL_STARTUP` which resides in the platform HAL. Some platforms provide only some of the RAM, ROM, and ROMRAM modes, others provide additional modes.

To see mode of a currently executing RedBoot, issue the **version** command, which prints the RedBoot banner, including the startup mode (here ROM):

```
RedBoot>version
```

```
RedBoot(tm) bootstrap and debug environment [ROM]
Non-certified release, version UNKNOWN - built 13:31:57, May 17 2002
```

# RedBoot Resource Usage

RedBoot takes up both flash and RAM resources depending on its startup mode and number of enabled features. There are also other resources used by RedBoot, such as timers. Platform-specific resources used by RedBoot are listed in the platform specific parts of this manual.

Both flash and RAM resources used by RedBoot depend to some degree on the features enabled in the RedBoot configuration. It is possible to reduce in particular the RAM resources used by RedBoot by removing features that are not needed. Flash resources can also be reduced, but due to the granularity of the flash (the block sizes), reductions in feature size do not always result in flash resource savings.

## Flash Resources

On many platforms, a ROM mode RedBoot image resides in the first flash sectors, working as the board's primary boot monitor. On these platforms, it is also normal to reserve a similar amount of flash for a secondary RAM mode image, which is used when updating the primary ROM mode image.

On other platforms, a ROMRAM mode RedBoot image is used as the primary boot monitor. On these platforms there is not normally reserved space for a RAM mode RedBoot image, since the ROMRAM mode RedBoot is capable of updating the primary boot monitor image.

Most platforms also contain a FIS directory (keeping track of available flash space) and a RedBoot config block (containing RedBoot board configuration data).

To see the amount of reserved flash memory, run the **fis list** command:

```
RedBoot> fis list
Name                FLASH addr  Mem addr    Length      Entry point
RedBoot              0x00000000  0x00000000  0x00020000  0x00000000
RedBoot[RAM]         0x00020000  0x06020000  0x00020000  0x060213C0
RedBoot config       0x0007F000  0x0007F000  0x00001000  0x00000000
FIS directory        0x00070000  0x00070000  0x0000F000  0x00000000
```

To save flash resources, use a ROMRAM mode RedBoot, or if using a ROM mode RedBoot, avoid reserving space for the RedBoot[RAM] image (this is done by changing the RedBoot configuration) and download the RAM mode RedBoot whenever it is needed. If the RedBoot image takes up a fraction of an extra flash block, it may be possible to reduce the image size enough to free this block by removing some features.

## RAM Resources

RedBoot reserves RAM space for its run-time data, and such things as CPU exception/interrupt tables. It normally does so at the bottom of the memory map. It may also reserve space at the top of the memory map for configurable RedBoot features such as the net stack and zlib decompression support.

To see the actual amount of reserved space, issue the **version** command, which prints the RedBoot banner, including the RAM usage:

```
RedBoot> version

RedBoot(tm) bootstrap and debug environment [ROM]
Non-certified release, version UNKNOWN - built 13:31:57, May 17 2002

Platform: FooBar (SH 7615)
Copyright (C) 2000, 2001, 2002, Red Hat, Inc.

RAM: 0x06000000-0x06080000, 0x06012498-0x06061000 available
FLASH: 0x00000000 - 0x00080000, 8 blocks of 0x00010000 bytes each.
```

To simplify operations that temporarily need data in free memory, the limits of free RAM are also available as aliases (aligned to the nearest kilo-byte limit). These are named FREEMEMLO and FREEMEMHI, and can be used in commands like any user defined alias:

```
RedBoot> load -r -b %{FREEMEMLO} file
Raw file loaded 0x06012800-0x06013e53, assumed entry at 0x06012800

RedBoot> x -b %{FREEMEMHI}
06061000: 86 F5 EB D8 3D 11 51 F2 96 F4 B2 DC 76 76 8F 77 |...=.Q.....vv.w|
06061010: E6 55 DD DB F3 75 5D 15 E0 F3 FC D9 C8 73 1D DA |.U...u].....s..|
```

To reduce RedBoot's RAM resource usage, use a ROM mode RedBoot. The RedBoot features that use most RAM are the net stack, the flash support and the gunzip support. These, and other features, can be disabled to reduce the RAM footprint, but obviously at the cost of lost functionality.

## Configuring the RedBoot Environment

Once installed, RedBoot will operate fairly generically. However, there are some features that can be configured for a particular installation. These depend primarily on whether flash and/or

networking support are available. The remainder of this discussion assumes that support for both of these options is included in RedBoot.

## Target Network Configuration

Each node in a networked system needs to have a unique address. Since the network support in RedBoot is based on TCP/IP, this address is an IP (Internet Protocol) address. There are two ways for a system to “know” its IP address. First, it can be stored locally on the platform. This is known as having a static IP address. Second, the system can use the network itself to discover its IP address. This is known as a dynamic IP address. RedBoot supports this dynamic IP address mode by use of the BOOTP (a subset of DHCP) protocol. In this case, RedBoot will ask the network (actually some generic server on the network) for the IP address to use.

**NOTE:** Currently, RedBoot only supports BOOTP. In future releases, DHCP may also be supported, but such support will be limited to additional data items, not lease-based address allocation.

The choice of IP address type is made via the **fconfig** command. Once a selection is made, it will be stored in flash memory. RedBoot only queries the flash configuration information at reset, so any changes will require restarting the platform.

Here is an example of the RedBoot **fconfig** command, showing network addressing:

```
RedBoot> fconfig -l
Run script at boot: false
Use BOOTP for network configuration: false
Local IP address: 192.168.1.29
Default server IP address: 192.168.1.101
DNS server IP address: 192.168.1.1
GDB connection port: 9000
Network debug at boot time: false
```

In this case, the board has been configured with a static IP address listed as the Local IP address. The default server IP address specifies which network node to communicate with for TFTP service. This address can be overridden directly in the TFTP commands.

The DNS server IP address option controls where RedBoot should make DNS lookups. A setting of 0.0.0.0 will disable DNS lookups. The DNS server IP address can also be set at runtime.

If the selection for Use BOOTP for network configuration had been true, these IP addresses would be determined at boot time, via the BOOTP protocol. The final number which needs to be configured, regardless of IP address selection mode, is the GDB connection port. RedBoot allows for incoming commands on either the available serial ports or via the network. This port number is the TCP port that RedBoot will use to accept incoming connections.

These connections can be used for GDB sessions, but they can also be used for generic RedBoot commands. In particular, it is possible to communicate with RedBoot via the telnet protocol. For example, on Linux@:

```
% telnet redboot_board 9000
Connected to redboot_board
Escape character is '^]'.
RedBoot>
```

## Host Network Configuration

RedBoot may require three different classes of service from a network host:

- dynamic IP address allocation, using BOOTP
- TFTP service for file downloading
- DNS server for hostname lookups

Depending on the host system, these services may or may not be available or enabled by default. See your system documentation for more details.

In particular, on Red Hat Linux, neither of these services will be configured out of the box. The following will provide a limited explanation of how to set them up. These configuration setups must be done as `root` on the host or server machine.

### Enable TFTP on Red Hat Linux 6.2

1. Ensure that you have the `tftp-server` RPM package installed. By default, this installs the TFTP server in a disabled state. These steps will enable it:

2. Make sure that the following line is uncommented in the control file `/etc/inetd.conf`

```
tftp dgram  udp      wait    root    /usr/sbin/tcpd    /usr/sbin/in.tftpd
```

3. If it was necessary to change the line in Step 2, then the `inetd` server must be restarted, which can be done via the command:

```
# service inet reload
```

## Enable TFTP on Red Hat Linux 7 (or newer)

1. Ensure that the xinetd RPM is installed.
2. Ensure that the tftp-server RPM is installed.
3. Enable TFTP by means of the following:

```
/sbin/chkconfig tftp on
```

Reload the xinetd configuration using the command:

```
/sbin/service xinetd reload
```

Create the directory /tftpboot using the command

```
mkdir /tftpboot
```

**NOTE:** Under Red Hat 7 you must address files by absolute pathnames, for example: /tftpboot/boot.img not /boot.img, as you may have done with other implementations. On systems newer than Red Hat 7 (7.1 and beyond), filenames are once again relative to the /tftpboot directory.

## Enable BOOTP/DHCP server on Red Hat Linux

First, ensure that you have the proper package, dhcp (not dhcpd) installed. The DHCP server provides Dynamic Host Configuration, that is, IP address and other data to hosts on a network. It does this in different ways. Next, there can be a fixed relationship between a certain node and the data, based on that node's unique Ethernet Station Address (ESA, sometimes called a MAC address). The other possibility is simply to assign addresses that are free. The sample DHCP configuration file shown does both. Refer to the DHCP documentation for more details.

### Example 1-1. Sample DHCP configuration file

```
----- /etc/dhcpd.conf -----
default-lease-time 600;
max-lease-time 7200;
option subnet-mask 255.255.255.0;
option broadcast-address 192.168.1.255;
option domain-name-servers 198.41.0.4, 128.9.0.107;
option domain-name "bogus.com";
allow bootp;
shared-network BOGUS {
subnet 192.168.1.0 netmask 255.255.255.0 {
    option routers 192.168.1.101;
```

```
        range 192.168.1.1 192.168.1.254;
    }
}
host mbx {
    hardware ethernet 08:00:3E:28:79:B8;
    fixed-address 192.168.1.20;
    filename "/tftpboot/192.168.1.21/zImage";
    default-lease-time -1;
    server-name "srvr.bugus.com";
    server-identifier 192.168.1.101;
    option host-name "mbx";
}
```

Once the DHCP package has been installed and the configuration file set up, type:

```
# service dhcpd start
```

## Enable DNS server on Red Hat Linux

First, ensure that you have the proper RPM package, `caching-nameserver` installed. Then change the configuration (in `/etc/named.conf`) so that the `forwarders` point to the primary nameservers for your machine, normally using the nameservers listed in `/etc/resolv.conf`.

### Example 1-2. Sample `/etc/named.conf` for Red Hat Linux 7.x

```
----- /etc/named.conf -----
// generated by named-bootconf.pl

options {
    directory "/var/named";
    /*
     * If there is a firewall between you and nameservers you want
     * to talk to, you might need to uncomment the query-source
     * directive below. Previous versions of BIND always asked
     * questions using port 53, but BIND 8.1 uses an unprivileged
     * port by default.
     */
    // query-source address * port 53;

    forward first;
    forwarders {
        212.242.40.3;
        212.242.40.51;
    };
};
```

```
};

//
// a caching only nameserver config
//
// Uncomment the following for Red Hat Linux 7.2 or above:
// controls {
//     inet 127.0.0.1 allow { localhost; } keys { rndckey; };
// };
// include "/etc/rndc.key";
zone "." IN {
    type hint;
    file "named.ca";
};

zone "localhost" IN {
    type master;
    file "localhost.zone";
    allow-update { none; };
};

zone "0.0.127.in-addr.arpa" IN {
    type master;
    file "named.local";
    allow-update { none; };
};
```

Make sure the server is started with the command:

```
# service named start
```

and is started on next reboot with the command

```
# chkconfig named on
```

Finally, you may wish to change `/etc/resolv.conf` to use `127.0.0.1` as the nameserver for your local machine.

## RedBoot network gateway

RedBoot cannot communicate with machines on different subnets because it does not support routing. It always assumes that it can get to an address directly, therefore it always tries to ARP and then send packets directly to that unit. This means that whatever it talks to must be on the same subnet. If you need to talk to a host on a different subnet (even if it's on the same 'wire'), you need to go through an ARP proxy, providing that there is a Linux box connected to the network which is able to route to the TFTP server. For example:

`/proc/sys/net/ipv4/conf/<interface>/proxy_arp` where `<interface>` should be replaced with whichever network interface is directly connected to the board.

## **Verification**

Once your network setup has been configured, perform simple verification tests as follows:

- Reboot your system, to enable the setup, and then try to 'ping' the target board from a host.
- Once communication has been established, try to ping a host using the RedBoot ping command - both by IP address and hostname.
- Try using the RedBoot load command to download a file from a host.

# Chapter 2. RedBoot Commands and Examples

## Introduction

RedBoot provides three basic classes of commands:

- Program loading and execution
- Flash image and configuration management
- Miscellaneous commands

Given the extensible and configurable nature of eCos and RedBoot, there may be extended or enhanced sets of commands available.

The basic format for commands is:

```
RedBoot> COMMAND [-S]... [-s val]... operand
```

Commands may require additional information beyond the basic command name. In most cases this additional information is optional, with suitable default values provided if they are not present.

Format	Description	Example
-S	A boolean switch; the behavior of the command will differ, depending on the presence of the switch. In this example, the <b>-f</b> switch indicates that a complete initialization of the FIS data should be performed. There may be many such switches available for any given command and any or all of them may be present, in any order.	RedBoot> <b>fis init -f</b>

Format	Description	Example
<code>-s val</code>	A qualified value; the letter "s" introduces the value, qualifying it's meaning. In the example, <b>-b 0x100000</b> specifies where the memory dump should begin. There may be many such switches available for any given command and any or all of them may be present, in any order.	RedBoot> <b>dump -b 0x100000 -l 0x20</b>
<code>operand</code>	A simple value; some commands require a single parameter for which an additional <b>-X</b> switch would be redundant. In the example, <b>JFFS2</b> is the name of a flash image. The image name is always required, thus is no need to qualify it with a switch. Note that any un-qualified operand must always appear at the end of the command.	RedBoot> <b>fis delete JFFS2</b>

The list of available commands, and their syntax, can be obtained by typing **help** at the command line:

```
RedBoot> help
Manage aliases kept in FLASH memory
    alias name [value]
Set/Query the system console baud rate
    baudrate [-b <rate>]
Manage machine caches
    cache [ON | OFF]
Display/switch console channel
    channel [-l|<channel number>]
Display disk partitions
    disks
Display (hex dump) a range of memory
    dump -b <location> [-l <length>] [-s]
Manage flash images
```

```

    fis {cmds}
Manage configuration kept in FLASH memory
    fconfig [-i] [-l] [-n] [-f] [-d] | [-d] nickname [value]
Execute code at a location
    go [-w <timeout>] [entry]
Help about help?
    help [<topic>]
Set/change IP addresses
    ip_address [-l <local_ip_address>] [-h <server_address>]
Load a file
    load [-r] [-v] [-d] [-c <channel>] [-h <host>] [-m {TFTP | HTTP | {x|y}MODEM}
    [-b <base_address>] <file_name>
Network connectivity test
    ping [-v] [-n <count>] [-t <timeout>] [-i <IP_addr>]
    -h <host>
Reset the system
    reset
Display RedBoot version information
    version
Display (hex dump) a range of memory
    x -b <location> [-l <length>] [-s]

```

Commands can be abbreviated to their shortest unique string. Thus in the list above, **d,du,dum** and **dump** are all valid for the **dump** command. The **fconfig** command can be abbreviated **fc**, but **f** would be ambiguous with **fis**.

There is one additional, special command. When RedBoot detects '\$' or '+' (unless escaped via '\') in a command, it switches to GDB protocol mode. At this point, the eCos GDB stubs take over, allowing connections from a GDB host. The only way to get back to RedBoot from GDB mode is to restart the platform.

**NOTE:** Multiple commands may be entered on a single line, separated by the semi-colon ";" character.

The standard RedBoot command set is structured around the bootstrap environment. These commands are designed to be simple to use and remember, while still providing sufficient power and flexibility to be useful. No attempt has been made to render RedBoot as the end-all product. As such, things such as the debug environment are left to other modules, such as GDB stubs, which are typically included in RedBoot.

The command set may be also be extended on a platform basis.

# Common Commands

## alias

### Name

`alias` — Manipulate command line aliases

### Synopsis

```
alias { name } [ value ]
```

### Arguments

Name	Type	Description	Default
<i>name</i>	Name	The name for this alias.	<i>none</i>
<i>value</i>	String	Replacement value for the alias.	<i>none</i>

### Description

The **alias** command is used to maintain simple command line aliases. These aliases are shorthand for longer expressions. When the pattern `%{name}` appears in a command line, including in a script, the corresponding value will be substituted. Aliases may be nested.

If no value is provided, then the current value of the alias is displayed.

If the system supports non-volatile configuration data via the **fconfig** command (see the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2), then the value will be saved and used when the system is reset.

## Examples

Set an alias.

```
RedBoot> alias joe "This is Joe"  
Update RedBoot non-volatile configuration - continue (y/n)? n
```

Display an alias.

```
RedBoot> alias joe  
'joe' = 'This is Joe'
```

Use an alias. Note: the "=" command simply echoes the command to console.

```
RedBoot> = %{joe}  
This is Joe
```

Aliases can be nested.

```
RedBoot> alias frank "Who are you? %{joe}"  
Update RedBoot non-volatile configuration - continue (y/n)? n  
RedBoot> = %{frank}  
Who are you? This is Joe
```

Notice how the value of %{frank} changes when %{joe} is changed since the value of %{joe} is not evaluated until %{frank} is evaluated.

```
RedBoot> alias joe "This is now Josephine"  
Update RedBoot non-volatile configuration - continue (y/n)? n  
RedBoot> = %{frank}  
Who are you? This is now Josephine
```

*alias*

# baudrate

## Name

`baudrate` — Set the baud rate for the system serial console

## Synopsis

`baudrate` [-b *rate*]

## Arguments

Name	Type	Description	Default
-b <i>rate</i>	Number	The baud rate to use for the serial console.	<i>none</i>

## Description

The `baudrate` command sets the baud rate for the system serial console.

If no value is provided, then the current value of the console baud rate is displayed.

If the system supports non-volatile configuration data via the `fconfig` command (see the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2), then the value will be saved and used when the system is reset.

## Examples

Show the current baud rate.

```
RedBoot> baudrate  
Baud rate = 38400
```

Change the console baud rate. In order to make this operation safer, there will be a slight pause after the first message to give you time to change to the new baud rate. If it doesn't work, or a less than affirmative answer is given to the "continue" prompt, then the baud rate will revert to

## *baudrate*

the current value. Only after the baud rate has been firmly established will *RedBoot* give you an opportunity to save the value in persistent storage.

```
RedBoot> baudrate -b 57600  
Baud rate will be changed to 57600 - update your settings  
Device baud rate changed at this point  
Baud rate changed to 57600 - continue (y/n)? y  
Update RedBoot non-volatile configuration - continue (y/n)? n
```

# cache

## Name

cache — Control hardware caches

## Synopsis

**cache** [on | off]

## Arguments

Name	Type	Description	Default
on		Turn the caches on	<i>none</i>
off		Turn the caches off	<i>none</i>

## Description

The **cache** command is used to manipulate the caches on the processor.

With no options, this command specifies the state of the system caches.

When an option is given, the caches are turned off or on appropriately.

## Examples

Show the current cache state.

```
RedBoot> cache  
Data cache: On, Instruction cache: On
```

Disable the caches.

```
RedBoot> cache off  
RedBoot> cache
```

## *cache*

Data cache: Off, Instruction cache: Off

Enable the caches.

```
RedBoot> cache on
```

```
RedBoot> cache
```

```
Data cache: On, Instruction cache: On
```

# channel

## Name

`channel` — Select the system console channel

## Synopsis

`channel` [-1 | *channel\_number*]

## Arguments

Name	Type	Description	Default
-1		Reset the console channel	<i>none</i>
<code>channel_number</code>	Number	Select a channel	<i>none</i>

## Description

With no arguments, the **channel** command displays the current console channel number.

When passed an argument of 0 upward, this command switches the console channel to that channel number. The mapping between channel numbers and physical channels is platform specific but will typically be something like channel 0 is the first serial port, channel 1 is the second, etc.

When passed an argument of -1, this command reverts RedBoot to responding to whatever channel receives input first, as happens when RedBoot initially starts execution.

## Examples

Show the current channel.

```
RedBoot> channel  
Current console channel id: 0
```

Change to an invalid channel.

## *channel*

```
RedBoot> channel 99  
**Error: bad channel number '99'
```

Revert to the default channel setting (any console mode).

```
RedBoot> channel -1
```

# cksum

## Name

cksum — Compute POSIX checksums

## Synopsis

```
cksum {-b location} {-l length}
```

## Arguments

Name	Type	Description	Default
-b <i>location</i>	Memory address	Location in memory for stat of data.	<i>none</i>
-l <i>length</i>	Number	Length of data	<i>none</i>

## Description

Computes the POSIX checksum on a range of memory (either RAM or FLASH). The values printed (decimal cksum, decimal length, hexadecimal cksum, hexadecimal length) can be compared with the output from the Linux program 'cksum'.

## Examples

Checksum a buffer.

```
RedBoot> cksum -b 0x100000 -l 0x100
POSIX cksum = 3286483632 256 (0xc3e3c2b0 0x00000100)
```

Checksum an area of memory after loading a file. Note that the base address and length parameters are provided by the preceding load command.

```
RedBoot> load -r -b %{FREEMEMLO} redboot.bin
```

## *cksum*

```
Raw file loaded 0x06012800-0x0602f0a8
RedBoot> cksum
Computing cksum for area 0x06012800-0x0602f0a8
POSIX cksum = 2092197813 116904 (0x7cb467b5 0x0001c8a8)
```

# disks

## Name

`disks` — List available disk partitions.

## Synopsis

`disks`

## Arguments

None.

## Description

The `disks` command is used to list disk partitions recognized by RedBoot.

## Examples

Show what disk partitions are available.

```
RedBoot> disks
hda1      Linux Swap
hda2      Linux
00100000: 00 3E 00 06 00 06 00 06 00 00 00 00 00 00 00 00 |.>.....|
00100010: 00 00 00 78 00 70 00 60 00 60 00 60 00 60 00 60 |...x.p.'.'.'.'|
```

*disks*

# dump

## Name

`dump` — Display memory.

## Synopsis

`dump` *{-b location}* *[-l length]* *[-s]* *[-1 | -2 | -4]*

## Arguments

Name	Type	Description	Default
<i>-b location</i>	Memory address	Location in memory for start of data.	<i>none</i>
<i>-l length</i>	Number	Length of data	32
<i>-s</i>	Boolean	Format data using Motorola S-records.	
<i>-1</i>		Access one byte (8 bits) at a time. Only the least significant 8 bits of the pattern will be used.	-1
<i>-2</i>		Access two bytes (16 bits) at a time. Only the least significant 16 bits of the pattern will be used.	-1
<i>-4</i>		Access one word (32 bits) at a time.	-1

## Description

Display a range of memory on the system console.

The **x** is a synonym for **dump**.

Note that this command could be detrimental if used on memory mapped hardware registers.

## *dump*

The memory is displayed at most sixteen bytes per line, first as the raw hex value, followed by an ASCII interpretation of the data.

## Examples

Display a buffer, one byte at a time.

```
RedBoot> mfill -b 0x100000 -l 0x20 -p 0xDEADFACE
RedBoot> x -b 0x100000
00100000: CE FA AD DE CE FA AD DE CE FA AD DE CE FA AD DE | ..... |
00100010: CE FA AD DE CE FA AD DE CE FA AD DE CE FA AD DE | ..... |
```

Display a buffer, one short (16 bit) word at a time. Note in this case that the ASCII interpretation is suppressed.

```
RedBoot> dump -b 0x100000 -2
00100000: FACE DEAD FACE DEAD FACE DEAD FACE DEAD
00100010: FACE DEAD FACE DEAD FACE DEAD FACE DEAD
```

Display a buffer, one word (32 bit) word at a time. Note in this case that the ASCII interpretation is suppressed.

```
RedBoot> dump -b 0x100000 -4
00100000: DEADFACE DEADFACE DEADFACE DEADFACE
00100010: DEADFACE DEADFACE DEADFACE DEADFACE
```

Display the same buffer, using Motorola S-record format.

```
RedBoot> dump -b 0x100000 -s
S31500100000CEFAADDECEFAADDECEFAADDECEFAADDE8E
S31500100010CEFAADDECEFAADDECEFAADDECEFAADDE7E
```

Display a buffer, with visible ASCII strings.

```
RedBoot> d -b 0xfe00b000 -l 0x80
0xFE00B000: 20 25 70 0A 00 00 00 00 41 74 74 65 6D 70 74 20 | %p.....Attempt |
```

*dump*

```
0xFE00B010: 74 6F 20 6C 6F 61 64 20 53 2D 72 65 63 6F 72 64 |to load S-record|
0xFE00B020: 20 64 61 74 61 20 74 6F 20 61 64 64 72 65 73 73 | data to address|
0xFE00B030: 3A 20 25 70 20 5B 6E 6F 74 20 69 6E 20 52 41 4D |: %p [not in RAM|
0xFE00B040: 5D 0A 00 00 2A 2A 2A 20 57 61 72 6E 69 6E 67 21 |]...*** Warning!|
0xFE00B050: 20 43 68 65 63 6B 73 75 6D 20 66 61 69 6C 75 72 | Checksum failur|
0xFE00B060: 65 20 2D 20 41 64 64 72 3A 20 25 6C 78 2C 20 25 |e - Addr: %lx, %|
0xFE00B070: 30 32 6C 58 20 3C 3E 20 25 30 32 6C 58 0A 00 00 |021X <> %021X...|
0xFE00B080: 45 6E 74 72 79 20 70 6F 69 6E 74 3A 20 25 70 2C |Entry point: %p,|
```

*dump*

# help

## Name

`help` — Display help on available commands

## Synopsis

`help` [ *topic* ]

## Arguments

Name	Type	Description	Default
<i>topic</i>	String	Which command to provide help for.	All commands

## Description

The `help` command displays information about the available RedBoot commands. If a *topic* is given, then the display is restricted to information about that specific command.

If the command has sub-commands, e.g. `fis`, then the topic specific display will print additional information about the available sub-commands. special (ICMP) packets to a specific host. These packets should be automatically returned by that host. The command will indicate how many of these round-trips were successfully completed.

## Examples

Show generic help. Note that the contents of this display will depend on the various configuration options for RedBoot when it was built.

```
RedBoot> help
Manage aliases kept in FLASH memory
  alias name [value]
Manage machine caches
  cache [ON | OFF]
Display/switch console channel
  channel [-1|<channel number>]
```

## help

```
Compute a 32bit checksum [POSIX algorithm] for a range of memory
  cksum -b <location> -l <length>
Display (hex dump) a range of memory
  dump -b <location> [-l <length>] [-s] [-1|2|4]
Manage FLASH images
  fis {cmds}
Manage configuration kept in FLASH memory
  fconfig [-i] [-l] [-n] [-f] [-d] | [-d] nickname [value]
Execute code at a location
  go [-w <timeout>] [entry]
Help about help?
  help [<topic>]
Set/change IP addresses
  ip_address [-l <local_ip_address>] [-h <server_address>]
Load a file
  load [-r] [-v] [-d] [-h <host>] [-m {TFTP | HTTP | {x|y}MODEM -c <channel_num>
    [-b <base_address>] <file_name>
Compare two blocks of memory
  mcmp -s <location> -d <location> -l <length> [-1|-2|-4]
Fill a block of memory with a pattern
  mfill -b <location> -l <length> -p <pattern> [-1|-2|-4]
Network connectivity test
  ping [-v] [-n <count>] [-l <length>] [-t <timeout>] [-r <rate>]
    [-i <IP_addr>] -h <IP_addr>
Reset the system
  reset
Display RedBoot version information
  version
Display (hex dump) a range of memory
  x -b <location> [-l <length>] [-s] [-1|2|4]
```

Help about a command with sub-commands.

```
RedBoot> help fis
Manage FLASH images
  fis {cmds}
Create an image
  fis create -b <mem_base> -l <image_length> [-s <data_length>]
    [-f <flash_addr>] [-e <entry_point>] [-r <ram_addr>] [-n] <name>
Display an image from FLASH Image System [FIS]
  fis delete name
Erase FLASH contents
  fis erase -f <flash_addr> -l <length>
Display free [available] locations within FLASH Image System [FIS]
  fis free
Initialize FLASH Image System [FIS]
  fis init [-f]
```

Display contents of FLASH Image System [FIS]

`fis list [-c] [-d]`

Load image from FLASH Image System [FIS] into RAM

`fis load [-d] [-b <memory_load_address>] [-c] name`

Write raw data directly to FLASH

`fis write -f <flash_addr> -b <mem_base> -l <image_length>`

*help*

# ip\_address

## Name

`ip_address` — Set IP addresses

## Synopsis

```
ip_address [-l local_IP_address] [-h server_IP_address] [-d  
DNS_server_IP_address]
```

## Arguments

Name	Type	Description	Default
<code>-l</code> <i>local_IP_address</i>	Numeric IP or DNS name	The IP address RedBoot should use.	<i>none</i>
<code>-h</code> <i>server_IP_address</i>	Numeric IP or DNS name	The IP address of the default server. Use of this address is implied by other commands, such as <b>load</b> .	<i>none</i>
<code>-d</code> <i>DNS_server_IP_address</i>	Numeric IP or DNS names	The IP address of the DNS server.	<i>none</i>

## Description

The **ip\_address** command is used to show and/or change the basic IP addresses used by RedBoot. IP addresses may be given as numeric values, e.g. 192.168.1.67, or as symbolic names such as www.redhat.com if DNS support is enabled.

The `-l` option is used to set the IP address used by the target device.

The `-h` option is used to set the default server address, such as is used by the **load** command.

The `-d` option is used to set the default DNS server address which is used for resolving symbolic network addresses. Note that an address of 0.0.0.0 will disable DNS lookups.

*ip\_address*

## Examples

Display the current network settings.

```
RedBoot> ip_address  
IP: 192.168.1.31, Default server: 192.168.1.101, DNS server IP: 0.0.0.0
```

Change the DNS server address.

```
RedBoot> ip_address -d 192.168.1.101  
IP: 192.168.1.31, Default server: 192.168.1.101, DNS server IP: 192.168.1.101
```

Change the default server address.

```
RedBoot> ip_address -h 192.168.1.104  
IP: 192.168.1.31, Default server: 192.168.1.104, DNS server IP: 192.168.1.101
```

# load

## Name

load — Download programs or data to the RedBoot platform

## Synopsis

```
load [-v ] [-d ] [-r ] [-m [[xmodem | ymodem] | tftp | disk] ] [-h server_IP_address] [-b  
  location] [-c channel] [file_name]
```

## Arguments

Name	Type	Description	Default
-v	Boolean	Display a small spinner (indicator) while the download is in progress. This is just for feedback, especially during long loads. Note that the option has no effect when using a serial download method since it would interfere with the protocol.	<i>quiet</i>
-d	Boolean	Decompress data stream (gzip data)	<i>non-compressed data</i>
-r	Boolean	Raw (or binary) data	<i>formatted (S-records, ELF image, etc)</i>
-m tftp		Transfer data via the network using TFTP protocol.	TFTP
-m http		Transfer data via the network using HTTP protocol.	TFTP

Name	Type	Description	Default
-m xmodem		Transfer data using <i>X-modem</i> protocol.	TFTP
-m ymodem		Transfer data using <i>Y-modem</i> protocol.	TFTP
-m disk		Transfer data from a local disk.	TFTP
-h <i>server_IP_address</i>	Numeric IP or DNS name	The IP address of the TFTP or HTTP server.	Value set by <b>ip_address</b>
-b <i>location</i>	Number	Address in memory to load the data. Formatted data streams will have an implied load address which this option may override.	<i>Depends on data format</i>
-c <i>channel</i>	Number	Specify which I/O channel to use for download. This option is only supported when using either xmodem or ymodem protocol.	<i>Depends on data format</i>
<i>file_name</i>	String	The name of the file on the TFTP or HTTP server or the local disk. Details of how this is specified for TFTP are host-specific. For local disk files, the name must be in <i>disk:filename</i> format. The disk portion must match one of the disk names listed by the <b>disks</b> command.	<i>None</i>

## Description

The **load** command is used to download data into the target system. Data can be loaded via a network connection, using either the TFTP or HTTP protocols, or the console serial connection using the X/Y modem protocol. Files may also be loaded directly from local filesystems on disk. Files to be downloaded may either be executable images in ELF executable program format, Motorola S-record (SREC) format or raw data.

## Examples

Download a Motorola S-record (or ELF) image, using TFTP, specifying the base memory address.

```
RedBoot> load redboot.ROM -b 0x8c400000
Address offset = 0x0c400000
Entry point: 0x80000000, address range: 0x80000000-0x8000fe80
```

Download a Motorola S-record (or ELF) image, using HTTP, specifying the host [server] address.

```
RedBoot> load /redboot.ROM -m HTTP -h 192.168.1.104
Address offset = 0x0c400000
Entry point: 0x80000000, address range: 0x80000000-0x8000fe80
```

Load an ELF file from /dev/hda1 which should be an EXT2 partition:

```
RedBoot> load -mode disk hda1:hello.elf
Entry point: 0x00020000, address range: 0x00020000-0x0002fd70
```

*load*

# mcmp

## Name

mcmp — Compare two segments of memory

## Synopsis

```
mcmp {-s location1} {-d location1} {-l length} [-1 | -2 | -4]
```

## Arguments

Name	Type	Description	Default
-s <i>location1</i>	Memory address	Location for start of data.	<i>none</i>
-d <i>location2</i>	Memory address	Location for start of data.	<i>none</i>
-l <i>length</i>	Number	Length of data	<i>none</i>
-1		Access one byte (8 bits) at a time. Only the least significant 8 bits of the pattern will be used.	-4
-2		Access two bytes (16 bits) at a time. Only the least significant 16 bits of the pattern will be used.	-4
-4		Access one word (32 bits) at a time.	-4

## Description

Compares the contents of two ranges of memory (RAM, ROM, FLASH, etc).

*ncmp*

## Examples

Compare two buffers which match (result is *quiet*).

```
RedBoot> mfill -b 0x100000 -l 0x20 -p 0xDEADFACE
RedBoot> mfill -b 0x200000 -l 0x20 -p 0xDEADFACE
RedBoot> ncmp -s 0x100000 -d 0x200000 -l 0x20
```

Compare two buffers which don't match. Only the first non-matching element is displayed.

```
RedBoot> ncmp -s 0x100000 -d 0x200000 -l 0x30 -2
Buffers don't match - 0x00100020=0x6000, 0x00200020=0x0000
```

# mfill

## Name

mfill — Fill RAM with a specified pattern

## Synopsis

mfill {-b *location*} {-l *length*} {-p *value*} [-1 | -2 | -4]

## Arguments

Name	Type	Description	Default
-b <i>location</i>	Memory address	Location in memory for start of data.	<i>none</i>
-l <i>length</i>	Number	Length of data	<i>none</i>
-p <i>pattern</i>	Number	Data value to fill with	0
-1		Access one byte (8 bits) at a time. Only the least significant 8 bits of the pattern will be used.	-4
-2		Access two bytes (16 bits) at a time. Only the least significant 16 bits of the pattern will be used.	-4
-4		Access one word (32 bits) at a time.	-4

## Description

Fills a range of memory with the given pattern.

## Examples

Fill a buffer with zeros.

```
RedBoot> x -b 0x100000 -l 0x20
00100000: 00 3E 00 06 00 06 00 06 00 00 00 00 00 00 00 00 |.>.....|
00100010: 00 00 00 78 00 70 00 60 00 60 00 60 00 60 00 60 |...x.p.'.'.'.'.'|
RedBoot> mfill -b 0x100000 -l 0x20
RedBoot> x -b 0x100000 -l 0x20
00100000: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
00100010: 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 |.....|
```

Fill a buffer with a pattern.

```
RedBoot> mfill -b 0x100000 -l 0x20 -p 0xDEADFACE
RedBoot> x -b 0x100000 -l 0x20
00100000: CE FA AD DE CE FA AD DE CE FA AD DE CE FA AD DE |.....|
00100010: CE FA AD DE CE FA AD DE CE FA AD DE CE FA AD DE |.....|
```

# ping

## Name

ping — Verify network connectivity

## Synopsis

```
ping [-v ] [-i local_IP_address] [-l length] [-n count] [-t timeout] [-r rate] {-h server_IP_address}
```

## Arguments

Name	Type	Description	Default
-v	Boolean	Be verbose, displaying information about each packet sent.	<i>quiet</i>
-n <i>local_IP_address</i>	Number	Controls the number of packets to be sent.	10
-i <i>local_IP_address</i>	Numeric IP or DNS name	The IP address RedBoot should use.	Value set by <b>ip_address</b>
-h <i>server_IP_address</i>	Numeric IP or DNS name	The IP address of the host to contact.	<i>none</i>
-l <i>length</i>	Number	The length of the ICMP data payload.	64
-r <i>length</i>	Number	How fast to deliver packets, i.e. time between successive sends. A value of 0 sends packets as quickly as possible.	1000ms (1 second)

Name	Type	Description	Default
<code>-t length</code>	Number	How long to wait for the round-trip to complete, specified in milliseconds.	1000ms (1 second)

## Description

The **ping** command checks the connectivity of the local network by sending special (ICMP) packets to a specific host. These packets should be automatically returned by that host. The command will indicate how many of these round-trips were successfully completed.

## Examples

Test connectivity to host 192.168.1.101.

```
RedBoot> ping -h 192.168.1.101
Network PING - from 192.168.1.31 to 192.168.1.101
PING - received 10 of 10 expected
```

Test connectivity to host 192.168.1.101, with verbose reporting.

```
RedBoot> ping -h 192.168.1.101 -v -n 4
Network PING - from 192.168.1.31 to 192.168.1.101
  seq: 1, time: 1 (ticks)
  seq: 2, time: 1 (ticks)
  seq: 3, time: 1 (ticks)
  seq: 4, time: 1 (ticks)
PING - received 10 of 10 expected
```

Test connectivity to a non-existent host (192.168.1.109).

```
RedBoot> ping -h 192.168.1.109 -v -n 4
PING: Cannot reach server '192.168.1.109' (192.168.1.109)
```

# reset

## Name

reset — Reset the device

## Synopsis

reset

## Arguments

*None*

## Description

The **reset** command causes the target platform to be reset. Where possible (hardware support permitting), this will be equivalent to a power-on reset condition.

## Examples

Reset the platform.

```
RedBoot> reset
... Resetting.+... Waiting for network card: .
Socket Communications, Inc: Low Power Ethernet CF Revision C 5V/3.3V 08/27/98
Ethernet eth0: MAC address 00:c0:1b:00:ba:28
IP: 192.168.1.29, Default server: 192.168.1.101

RedBoot(tm) bootstrap and debug environment [ROM]
Non-certified release, version UNKNOWN - built 10:41:41, May 14 2002

Platform: Compaq iPAQ Pocket PC (StrongARM 1110)
Copyright (C) 2000, 2001, 2002, Red Hat, Inc.

RAM: 0x00000000-0x01fc0000, 0x00014748-0x01f71000 available
FLASH: 0x50000000 - 0x51000000, 64 blocks of 0x00040000 bytes each.
RedBoot>
```

*reset*

# version

## Name

`version` — Display RedBoot version information

## Synopsis

`version`

## Arguments

*None*

## Description

The **version** command simply displays version information about RedBoot.

## Examples

Display RedBoot's version.

```
RedBoot> version  
RedBoot(tm) debug environment - built 09:12:03, Feb 12 2001  
Platform: XYZ (PowerPC 860)  
Copyright (C) 2000, 2001, Red Hat, Inc.  
RAM: 0x00000000-0x00400000
```

*version*

# Flash Image System (FIS)

If the platform has flash memory, RedBoot can use this for image storage. Executable images, as well as data, can be stored in flash in a simple file store. The **fis** command (fis is short for Flash Image System) is used to manipulate and maintain flash images.

## fis init

### Name

`fis init` — Initialize Flash Image System (FIS)

### Synopsis

`fis init [-f]`

### Arguments

Name	Type	Description	Default
-f		All blocks of flash memory (except for the boot blocks) will be erased as part of the initialization procedure.	

### Description

This command is used to initialize the Flash Image System (FIS). It should normally only be executed once, when RedBoot is first installed on the hardware. If the reserved images or their sizes in the FIS change, due to a different configuration of RedBoot being used, it may be necessary to issue the command again though.

**Note:** Subsequent executions will cause loss of previously stored information in the FIS.

## Examples

Initialize the FIS directory.

```
RedBoot> fis init
About to initialize [format] flash image system - continue (y/n)? y
*** Initialize FLASH Image System
    Warning: device contents not erased, some blocks may not be usable
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
```

Initialize the FIS directory and all of flash memory, except for first blocks of the flash where the boot monitor resides.

```
RedBoot> fis init -f
About to initialize [format] flash image system - continue (y/n)? y
*** Initialize FLASH Image System
... Erase from 0x00020000-0x00070000: .....
... Erase from 0x00080000-0x00080000:
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
```

# fis list

## Name

`fis list` — List Flash Image System directory

## Synopsis

`fis list [-f]`

## Arguments

Name	Type	Description	Default
-c		Show image checksum instead of memory address (column Mem addr is replaced by Checksum).	
-d		Show image data length instead of amount of flash occupied by image (column Length is replaced by Datalen).	

## Description

This command lists the images currently available in the FIS. Certain images used by RedBoot have fixed names and have reserved slots in the FIS (these can be seen after using the `fis init` command). Other images can be manipulated by the user.

**Note:** The images are listed in the order they appear in the FIS directory, not by name or creation time.

## Examples

List the FIS directory.

```
RedBoot> fis list
Name          FLASH addr  Mem addr    Length      Entry point
RedBoot       0x00000000  0x00000000  0x00020000  0x00000000
RedBoot config 0x0007F000  0x0007F000  0x00001000  0x00000000
FIS directory  0x00070000  0x00070000  0x0000F000  0x00000000
```

List the FIS directory, with image checksums substituted for memory addresses.

```
RedBoot> fis list -c
Name          FLASH addr  Checksum    Length      Entry point
RedBoot       0x00000000  0x00000000  0x00020000  0x00000000
RedBoot config 0x0007F000  0x00000000  0x00001000  0x00000000
FIS directory  0x00070000  0x00000000  0x0000F000  0x00000000
```

List the FIS directory with image data lengths substituted for flash block reservation lengths.

```
RedBoot> fis list
Name          FLASH addr  Mem addr    Datalen     Entry point
RedBoot       0x00000000  0x00000000  0x00000000  0x00000000
RedBoot config 0x0007F000  0x0007F000  0x00000000  0x00000000
FIS directory  0x00070000  0x00070000  0x00000000  0x00000000
```

# fis free

## Name

fis free — Free flash image

## Synopsis

fis free

## Description

This command shows which areas of the flash memory are currently not in use. When a block contains non-erased contents it is considered in use. Since it is possible to force an image to be loaded at a particular flash location, this command can be used to check whether that location is in use by any other image.

**Note:** There is currently no cross-checking between actual flash contents and the FIS directory, which means that there could be a segment of flash which is not erased that does not correspond to a named image, or vice-versa.

## Examples

Show free flash areas.

```
RedBoot> fis free
0xA0040000 .. 0xA07C0000
0xA0840000 .. 0xA0FC0000
```

*fis free*

# fis create

## Name

`fis create` — Create flash image

## Synopsis

`fis create` *{-b data address} {-l length} [-f flash address] [-e entry] [-r relocation address] [-s data length] [-n ] [name]*

## Arguments

Name	Type	Description	Default
-b	Number	Address of data to be written to the flash.	Address of last loaded file. If not set in a load operation, it must be specified.
-l	Number	Length of flash area to occupy. If specified, and the named image already exists, the length must match the value in the FIS directory.	Length of area reserved in FIS directory if the image already exists, or the length of the last loaded file. If neither are set, it must be specified.
-f	Number	Address of flash area to occupy.	The address of an area reserved in the FIS directory for extant images. Otherwise the first free block which is large enough will be used.
-e	Number	Entry address for an executable image, used by the <b>fis load</b> command.	The entry address of last loaded file.

Name	Type	Description	Default
-r	Number	Address where the image should be relocated to by the <b>fis load</b> command. This is only relevant for images that will be loaded with the <b>fis load</b> command.	The load address of the last loaded file.
-s	Number	Actual length of data written to image. This is used to control the range over which the checksum is made.	It defaults to the length of the last loaded file.
-n		When set, no image data will be written to the flash. Only the FIS directory will be updated.	
<i>name</i>	String	Name of flash image.	

## Description

This command creates an image in the FIS directory. The data for the image must exist in RAM memory before the copy. Typically, you would use the RedBoot **load** command to load file into RAM and then the **fis create** command to write it to a flash image.

## Examples

Trying to create an extant image, will require the action to be verified.

```
RedBoot> fis create RedBoot -f 0xa0000000 -b 0x8c400000 -l 0x20000  
An image named 'RedBoot' exists - continue (y/n)? n
```

Create a new test image, let the command find a suitable place.

```
RedBoot> fis create junk -b 0x8c400000 -l 0x20000  
... Erase from 0xa0040000-0xa0060000: .  
... Program from 0x8c400000-0x8c420000 at 0xa0040000: .  
... Erase from 0xa0fe0000-0xa1000000: .
```

... Program from 0x8c7d0000-0x8c7f0000 at 0xa0fe0000: .

Update the RedBoot[RAM] image.

```
RedBoot> load redboot_RAM.img
Entry point: 0x060213c0, address range: 0x06020000-0x06036cc0
RedBoot> fis create RedBoot[RAM]
No memory address set.
An image named 'RedBoot[RAM]' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot[RAM]'
      at 0x00020000..0x00036cbf from 0x06020000 - continue (y/n)? y
... Erase from 0x00020000-0x00040000: ..
... Program from 0x06020000-0x06036cc0 at 0x00020000: ..
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
```

*fis create*

# fis load

## Name

`fis load` — Load flash image

## Synopsis

`fis load [-b load address] [-c ] [-d ] [name]`

## Arguments

Name	Type	Description	Default
-b	Number	Address the image should be loaded to. Executable images normally load at the location to which the file was linked. This option allows the image to be loaded to a specific memory location, possibly overriding any assumed location.	If not specified, the address associated with the image in the FIS directory will be used.
-c		Compute and print the checksum of the image data after it has been loaded into memory.	
-d		Decompress gzipped image while copying it from flash to RAM.	
<i>name</i>	String	The name of the file, as shown in the FIS directory.	

*fis load*

## Description

This command is used to transfer an image from flash memory to RAM.

Once the image has been loaded, it may be executed using the **go** command.

## Examples

Load and run RedBoot[RAM] image.

```
RedBoot> fis load RedBoot[RAM]
```

```
RedBoot> go
```

# fis delete

## Name

`fis delete` — Delete flash image

## Synopsis

`fis delete {name}`

## Arguments

Name	Type	Description	Default
<i>name</i>	Number	Name of image that should be deleted.	

## Description

This command removes an image from the FIS. The flash memory will be erased as part of the execution of this command, as well as removal of the name from the FIS directory.

**Note:** Certain images are reserved by RedBoot and cannot be deleted. RedBoot will issue a warning if this is attempted.

## Examples

```
RedBoot> fis list
Name           flash addr   Mem addr    Length    Entry point
RedBoot        0xA0000000  0xA0000000  0x020000  0x80000000
RedBoot config 0xA0FC0000  0xA0FC0000  0x020000  0x00000000
FIS directory  0xA0FE0000  0xA0FE0000  0x020000  0x00000000
junk           0xA0040000  0x8C400000  0x020000  0x80000000
RedBoot> fis delete junk
Delete image 'junk' - continue (y/n)? y
... Erase from 0xa0040000-0xa0060000: .
```

*fis delete*

```
... Erase from 0xa0fe0000-0xa1000000: .  
... Program from 0x8c7d0000-0x8c7f0000 at 0xa0fe0000: .
```

# fis lock

## Name

`fis lock` — Lock flash area

## Synopsis

```
fis lock {-f flash_address} {-l length}
```

## Arguments

Name	Type	Description	Default
<i>flash_address</i>	Number	Address of area to be locked.	
<i>length</i>	Number	Length of area to be locked.	

## Description

This command is used to write-protect (lock) a portion of flash memory, to prevent accidental overwriting of images. In order to make any modifications to the flash, a matching **fis unlock** command must be issued. This command is optional and will only be provided on hardware which can support write-protection of the flash space.

**Note:** Depending on the system, attempting to write to write-protected flash may generate errors or warnings, or be benignly quiet.

## Examples

Lock an area of the flash

```
RedBoot> fis lock -f 0xa0040000 -l 0x20000  
... Lock from 0xa0040000-0xa0060000: .
```

*fis lock*

# fis unlock

## Name

`fis unlock` — Unlock flash area

## Synopsis

`fis unlock` *{-f flash\_address} {-l length}*

## Arguments

Name	Type	Description	Default
<i>flash_address</i>	Number	Address of area to be unlocked.	
<i>length</i>	Number	Length of area to be unlocked.	

## Description

This command is used to unlock a portion of flash memory forcibly, allowing it to be updated. It must be issued for regions which have been locked before the FIS can reuse those portions of flash.

**Note:** Some flash devices power up in locked state and always need to be manually unlocked before they can be written to.

## Examples

Unlock an area of the flash

```
RedBoot> fis unlock -f 0xa0040000 -l 0x20000
... Unlock from 0xa0040000-0xa0060000: .
```

*fis unlock*

# fis erase

## Name

`fis erase` — Erase flash area

## Synopsis

`fis erase` *{-f flash\_address} {-l length}*

## Arguments

Name	Type	Description	Default
<i>flash_address</i>	Number	Address of area to be erased.	
<i>length</i>	Number	Length of area to be erased.	

## Description

This command is used to erase a portion of flash memory forcibly. There is no cross-checking to ensure that the area being erased does not correspond to an existing image.

## Examples

Erase an area of the flash

```
RedBoot> fis erase -f 0xa0040000 -l 0x20000  
... Erase from 0xa0040000-0xa0060000: .
```

*fis erase*

# fis write

## Name

`fis write` — Write flash area

## Synopsis

`fis write` *{-b mem\_address} {-l length} {-f flash\_address}*

## Arguments

Name	Type	Description	Default
<i>mem_address</i>	Number	Address of data to be written to flash.	
<i>length</i>	Number	Length of data to be written.	
<i>flash_address</i>	Number	Address of flash to write to.	

## Description

This command is used to write data from memory to flash. There is no cross-checking to ensure that the area being written to does not correspond to an existing image.

## Examples

Write an area of data to the flash

```
RedBoot> fis write -b 0x0606f000 -l 0x1000 -f 0x00020000
* CAUTION * about to program FLASH
          at 0x00020000..0x0002ffff from 0x0606f000 - continue (y/n)? y
... Erase from 0x00020000-0x00030000: .
... Program from 0x0606f000-0x0607f000 at 0x00020000: .
```

*fis write*

# Persistent State Flash-based Configuration and Control

RedBoot provides flash management support for storage in the flash memory of multiple executable images and of non-volatile information such as IP addresses and other network information.

RedBoot on platforms that support flash based configuration information will report the following message the first time that RedBoot is booted on the target:

```
flash configuration checksum error or invalid key
```

This error can be ignored if no flash based configuration is desired, or can be silenced by running the **fconfig** command as described below. At this point you may also wish to run the **fis init** command. See other **fis** commands in the Section called *Flash Image System (FIS)*.

Certain control and configuration information used by RedBoot can be stored in flash.

The details of what information is maintained in flash differ, based on the platform and the configuration. However, the basic operation used to maintain this information is the same. Using the **fconfig -l** command, the information may be displayed and/or changed.

If the optional flag **-i** is specified, then the configuration database will be reset to its default state. This is also needed the first time RedBoot is installed on the target, or when updating to a newer RedBoot with different configuration keys.

If the optional flag **-l** is specified, the configuration data is simply listed. Otherwise, each configuration parameter will be displayed and you are given a chance to change it. The entire value must be typed - typing just carriage return will leave a value unchanged. Boolean values may be entered using the first letter (**t** for true, **f** for false). At any time the editing process may be stopped simply by entering a period (**.**) on the line. Entering the caret (**^**) moves the editing back to the previous item. See “RedBoot Editing Commands”, the Section called *RedBoot Editing Commands* in Chapter 1.

If any changes are made in the configuration, then the updated data will be written back to flash after getting acknowledgment from the user.

If the optional flag **-n** is specified (with or without **-l**) then “nicknames” of the entries are used. These are shorter and less descriptive than “full” names. The full name may also be displayed by adding the **-f** flag.

The reason for telling you nicknames is that a quick way to set a single entry is provided, using the format

```
RedBoot> fconfig nickname value
```

If no value is supplied, the command will list and prompt for only that entry. If a value is supplied, then the entry will be set to that value. You will be prompted whether to write the new information

into flash if any change was made. For example

```
RedBoot> fconfig -l -n
boot_script: false
bootp: false
bootp_my_ip: 10.16.19.176
bootp_server_ip: 10.16.19.66
dns_ip: 10.16.19.1
gdb_port: 9000
net_debug: false
RedBoot> fconfig bootp_my_ip 10.16.19.177
bootp_my_ip: 10.16.19.176 Setting to 10.16.19.177
Update RedBoot non-volatile configuration - continue (y/n)? y
... Unlock from 0x507c0000-0x507e0000: .
... Erase from 0x507c0000-0x507e0000: .
... Program from 0x0000a8d0-0x0000acd0 at 0x507c0000: .
... Lock from 0x507c0000-0x507e0000: .
RedBoot>
```

Additionally, nicknames can be used like aliases via the format `%{nickname}`. This allows the values stored by **fconfig** to be used directly by scripts and commands.

Depending on how your terminal program is connected and its capabilities, you might find that you are unable to use line-editing to delete the ‘old’ value when using the default behaviour of **fconfig nickname** or just plain **fconfig**, as shown in this example:

```
RedBoot> fco bootp
bootp: false_
```

The user deletes the word “false;” and enters “true” so the display looks like this:

```
RedBoot> fco bootp
bootp: true
Update RedBoot non-volatile configuration - continue (y/n)? y
... Unlock from ...
RedBoot> _
```

To edit when you cannot backspace, use the optional flag `-d` (for “dumb terminal”) to provide a simpler interface thus:

```
RedBoot> fco -d bootp
bootp: false ? _
```

and you enter the value in the obvious manner thus:

```
RedBoot> fco -d bootp
```

```

bootp: false ? true
Update RedBoot non-volatile configuration - continue (y/n)? y
... Unlock from ...
RedBoot> _

```

One item which is always present in the configuration data is the ability to execute a script at boot time. A sequence of RedBoot commands can be entered which will be executed when the system starts up. Optionally, a time-out period can be provided which allows the user to abort the startup script and proceed with normal command processing from the console.

```

RedBoot> fconfig -l
Run script at boot: false
Use BOOTP for network configuration: false
Local IP address: 192.168.1.29
Default server IP address: 192.168.1.101
DNS server IP address: 192.168.1.1
GDB connection port: 9000
Network debug at boot time: false

```

The following example sets a boot script and then shows it running.

```

RedBoot> fconfig
Run script at boot: false t
    Boot script:
Enter script, terminate with empty line
>> fi li
    Boot script timeout: 0 10
Use BOOTP for network configuration: false .
Update RedBoot non-volatile configuration - continue (y/n)? y
... Erase from 0xa0fc0000-0xa0fe0000: .
... Program from 0x8c021f60-0x8c022360 at 0xa0fc0000: .
RedBoot>
RedBoot(tm) debug environment - built 08:22:24, Aug 23 2000
Copyright (C) 2000, Red Hat, Inc.

RAM: 0x8c000000-0x8c800000
flash: 0xa0000000 - 0xa1000000, 128 blocks of 0x00020000 bytes ea.
Socket Communications, Inc: Low Power Ethernet CF Revision C \
5V/3.3V 08/27/98 IP: 192.168.1.29, Default server: 192.168.1.101 \
== Executing boot script in 10 seconds - enter ^C to abort
RedBoot> fi li
Name                flash addr    Mem addr     Length      Entry point
RedBoot             0xA0000000    0xA0000000    0x020000    0x80000000

```

## Chapter 2. RedBoot Commands and Examples

```
RedBoot config 0xA0FC0000 0xA0FC0000 0x020000 0x00000000
FIS directory  0xA0FE0000 0xA0FE0000 0x020000 0x00000000
RedBoot>
```

**NOTE:** The bold characters above indicate where something was entered on the console. As you can see, the **fi li** command at the end came from the script, not the console. Once the script is executed, command processing reverts to the console.

**NOTE:** RedBoot supports the notion of a boot script timeout, i.e. a period of time that RedBoot waits before executing the boot time script. This period is primarily to allow the possibility of canceling the script. Since a timeout value of zero (0) seconds would never allow the script to be aborted or canceled, this value is not allowed. If the timeout value is zero, then RedBoot will abort the script execution immediately.

On many targets, RedBoot may be configured to run from ROM or it may be configured to run from RAM. Other configurations are also possible. All RedBoot configurations will execute the boot script, but in certain cases it may be desirable to limit the execution of certain script commands to one RedBoot configuration or the other. This can be accomplished by prepending {<startup type>} to the commands which should be executed only by the RedBoot configured for the specified startup type. The following boot script illustrates this concept by having the ROM based RedBoot load and run the RAM based RedBoot. The RAM based RedBoot will then list flash images.

```
RedBoot> fco
Run script at boot: false t
Boot script:
Enter script, terminate with empty line
>> {ROM}fis load RedBoot[RAM]
>> {ROM}go
>> {RAM}fis li
>>
Boot script timeout (1000ms resolution): 2
Use BOOTP for network configuration: false
...
Update RedBoot non-volatile configuration - continue (y/n)? y
... Unlock from 0x007c0000-0x007e0000: .
... Erase from 0x007c0000-0x007e0000: .
... Program from 0xa0015030-0xa0016030 at 0x007df000: .
... Lock from 0x007c0000-0x007e0000: .
RedBoot> reset
```

```
... Resetting.
+Ethernet eth0: MAC address 00:80:4d:46:01:05
IP: 192.168.1.153, Default server: 192.168.1.10

RedBoot(tm) bootstrap and debug environment [ROM]
Red Hat certified release, version R1.xx - built 17:37:36, Aug 14 2001

Platform: IQ80310 (XScale)
Copyright (C) 2000, 2001, Red Hat, Inc.

RAM: 0xa0000000-0xa2000000, 0xa001b088-0xa1fdf000 available
FLASH: 0x00000000 - 0x00800000, 64 blocks of 0x00020000 bytes each.
== Executing boot script in 2.000 seconds - enter ^C to abort
RedBoot> fis load RedBoot[RAM]
RedBoot> go
+Ethernet eth0: MAC address 00:80:4d:46:01:05
IP: 192.168.1.153, Default server: 192.168.1.10

RedBoot(tm) bootstrap and debug environment [RAM]
Red Hat certified release, version R1.xx - built 13:03:47, Aug 14 2001

Platform: IQ80310 (XScale)
Copyright (C) 2000, 2001, Red Hat, Inc.

RAM: 0xa0000000-0xa2000000, 0xa0057fe8-0xa1fdf000 available
FLASH: 0x00000000 - 0x00800000, 64 blocks of 0x00020000 bytes each.
== Executing boot script in 2.000 seconds - enter ^C to abort
RedBoot> fis li
```

Name	FLASH addr	Mem addr	Length	Entry point
RedBoot	0x00000000	0x00000000	0x00040000	0x00002000
RedBoot config	0x007DF000	0x007DF000	0x00001000	0x00000000
FIS directory	0x007E0000	0x007E0000	0x00020000	0x00000000

```
RedBoot>
```

## Executing Programs from RedBoot

Once an image has been loaded into memory, either via the **load** command or the **fis load** command, execution may be transferred to that image.

**NOTE:** The image is assumed to be a stand-alone entity, as RedBoot gives the entire platform over to it. Typical examples would be an eCos application or a Linux kernel.

# go

## Name

go — Execute a program

## Synopsis

```
go [-w timeout][ start_address]
```

## Arguments

Name	Type	Description	Default
<i>-w timeout</i>	Number	How long to wait before starting execution.	0
<i>start_address</i>	Number	Address in memory to begin execution.	Value set by last <b>load</b> or <b>fis load</b> command.

## Description

The **go** command causes RedBoot to give control of the target platform to another program. This program must execute stand alone, e.g. an eCos application or a Linux kernel.

If the **-w** option is used, RedBoot will print a message and then wait for a period of time before starting the execution. This is most useful in a script, giving the user a chance to abort executing a program and move on in the script.

## Examples

Execute a program - *no explicit output from RedBoot.*

```
RedBoot> go 0x40040
```

Execute a program with a timeout.

```
RedBoot> go -w 10
About to start execution at 0x00000000 - abort with ^C within 10 seconds
^C
RedBoot>
```

Note that the starting address was implied (0x00000000 in this example). The user is prompted that execution will commence in 10 seconds. At anytime within that 10 seconds the user may type **Ctrl+C** on the console and RedBoot will abort execution and return for the next command, either from a script or the console.



# exec

## Name

exec — Execute a Linux kernel

## Synopsis

```
exec [-w timeout] [-r ramdisk_address] [-s  
ramdisk_length] [-b load_address {-l load_length} ] [-c  
kernel_command_line] [ entry_point]
```

## Arguments

Name	Type	Description	Default
-w <i>timeout</i>	Number	Time to wait before starting execution.	0
-r <i>ramdisk_address</i>	Number	Address in memory of "initrd"-style ramdisk - passed to Linux kernel.	<i>None</i>
-s <i>ramdisk_length</i>	Number	Length of ramdisk image - passed to Linux kernel.	<i>None</i>
-b <i>load_address</i>	Number	Address in memory of the Linux kernel image.	Value set by <b>load</b> or <b>fis load</b>
-l <i>load_length</i>	Number	Length of Linux kernel image.	<i>none</i>
-c <i>kernel_command_line</i>	String	Command line to pass to the Linux kernel.	<i>None</i>
<i>entry_address</i>	Number	Starting address for Linux kernel execution	Implied by architecture

## Description

The **exec** command is used to execute a non-eCos application, typically a Linux kernel. Additional information may be passed to the kernel at startup time. This command is quite special (and unique from the **go** command) in that the program being executed may expect certain environmental setups, for example that the MMU is turned off, etc.

The Linux kernel expects to have been loaded to a particular memory location which is architecture dependent (0xC0008000 in the case of the SA1110). Since this memory is used by RedBoot internally, it is not possible to load the kernel to that location directly. Thus the requirement for the "-b" option which tells the command where the kernel has been loaded. When the **exec** command runs, the image will be relocated to the appropriate location before being started. The "-r" and "-s" options are used to pass information to the kernel about where a statically loaded ramdisk (initrd) is located.

The "-c" option can be used to pass textual "command line" information to the kernel. If the command line data contains any punctuation (spaces, etc), then it must be quoted using the double-quote character `"`. If the quote character is required, it should be written as ``\``.

## Examples

Execute a Linux kernel, passing a command line, which needs relocation. The result from RedBoot is normally quiet, with the target platform being passed over to Linux immediately.

```
RedBoot> exec -b 0x100000 -l 0x80000 -c "noinitrd root=/dev/mtdblock3 console=tt
```

Execute a Linux kernel, default entry address and no relocation required, with a timeout. The *emphasized lines* are output from the loaded kernel.

```
RedBoot> exec -c "console=ttyS0,38400 ip=dhcp nfsroot=/export/elfs-sh" -w 5
Now booting linux kernel:
Base address 0x8c001000 Entry 0x8c210000
Cmdline : console=ttyS0,38400 ip=dhcp nfsroot=/export/elfs-sh
About to start execution at 0x8x210000 - abort with ^C within 5 seconds
Linux version 2.4.10-pre6 (...) (gcc version 3.1-stdsh-010931) #3 Thu Sep 27 11:0
```

# Chapter 3. Rebuilding RedBoot

## Introduction

RedBoot is built as an application on top of eCos. The makefile rules for building RedBoot are part of the eCos CDL package, so it's possible to build eCos from the Configuration Tool, as well as from the command line using `ecosconfig`.

Building RedBoot requires only a few steps: selecting the platform and the RedBoot template, importing a platform specific configuration file, and finally starting the build.

The platform specific configuration file makes sure the settings are correct for building RedBoot on the given platform. Each platform should provide at least two of these configuration files: `redboot_RAM.ecm` for a RAM mode RedBoot configuration and `redboot_ROM.ecm` or `redboot_ROMRAM.ecm` for a ROM or ROMRAM mode RedBoot configuration. There may be additional configuration files according to the requirements of the particular platform.

The RedBoot build process results in a number of files in the `install bin` directory. The ELF file `redboot.elf` is the principal result. Depending on the platform CDL, there will also be generated versions of RedBoot in other file formats, such as `redboot.bin` (binary format, good when doing an update of a primary RedBoot image, see the Section called *Update the primary RedBoot flash image* in Chapter 4), `redboot.srec` (Motorola S-record format, good when downloading a RAM mode image for execution), and `redboot.img` (stripped ELF format, good when downloading a RAM mode image for execution, smaller than the `.srec` file). Some platforms may provide additional file formats and also relocate some of these files to a particular address making them more suitable for downloading using a different boot monitor or flash programming tools.

The platform specific information in Chapter 5 should be consulted, as there may be other special instructions required to build RedBoot for particular platforms.

## Rebuilding RedBoot using `ecosconfig`

To rebuild RedBoot using the `ecosconfig` tool, create a temporary directory for building RedBoot, name it according to the desired configuration of RedBoot, here RAM:

```
$ mkdir /tmp/redboot_RAM
$ cd /tmp/redboot_RAM
```

Create the build tree according to the chosen platform, here using the Hitachi Solution Engine 7751 board as an example:

**Note:** It is assumed that the environment variable `ECOS_REPOSITORY` points to the eCos/RedBoot source tree.

```
$ ecosconfig new se7751 redboot
U CYGPKG_HAL_SH_7750, new inferred value 0
U CYGPKG_HAL_SH_7751, new inferred value 1
U CYGHWR_HAL_SH_IRQ_USE_IRQ_LVL, new inferred value 1
U CYGSEM_HAL_USE_ROM_MONITOR, new inferred value 0
U CYGDBG_HAL_COMMON_CONTEXT_SAVE_MINIMUM, new inferred value 0
U CYGDBG_HAL_DEBUG_GDB_INCLUDE_STUBS, new inferred value 1
U CYGFUN_LIBC_STRING_BSD_FUNCS, new inferred value 0
U CYGPKG_NS_DNS_BUILD, new inferred value 0
```

Replace the platform name ("se7751") with the appropriate name for the chosen platform.

Then import the appropriate platform RedBoot configuration file, here for RAM configuration:

```
$ ecosconfig import ${ECOS_REPOSITORY}/hal/sh/se7751/VERSION/misc/redboot_RAM.ecm
$ ecosconfig tree
```

Replace architecture ("sh"), platform ("se7751") and version ("VERSION") with those appropriate for the chosen platform and the version number of its HAL package. Also replace the configuration name ("redboot\_RAM.ecm") with that of the appropriate configuration file.

RedBoot can now be built:

```
$ make
```

The resulting RedBoot files will be in the associated install directory, in this example, `./install/bin`.

In Chapter 5 each platform's details are described in the form of shell variables. Using those, the steps to build RedBoot are:

```
export REDBOOT_CFG=redboot_ROM
export VERSION=VERSION
mkdir /tmp/${REDBOOT_CFG}
cd /tmp/${REDBOOT_CFG}
ecosconfig new ${TARGET} redboot
ecosconfig import ${ECOS_REPOSITORY}/hal/${ARCH_DIR}/${PLATFORM_DIR}/${VERSION}/m
ecosconfig tree
make
```

To build for another configuration, simply change the `REDBOOT_CFG` definition accordingly. Also make sure the `VERSION` variable matches the version of the platform package.

## Rebuilding RedBoot from the Configuration Tool

To rebuild RedBoot from the Configuration Tool, open the template window (Build->Templates) and select the appropriate Hardware target and in Packages select "redboot". Then press OK. Depending on the platform, a number of conflicts may need to be resolved before the build can be started; select "Continue".

Import the desired RedBoot configuration file from the platform HAL (File->Import...). Depending on the platform, a number of conflicts may need to be resolved before the build can be started; select "Continue". For example, if the platform selected is Hitachi SE7751 board and the RAM configuration RedBoot should be built, import the file `hal/sh/se7751/VERSION/misc/redboot_RAM.ecm`.

Save the configuration somewhere suitable with enough disk space for building RedBoot (File->Save...). Choose the name according to the RedBoot configuration, for example `redboot_RAM.ecc`.

Then start the build (Build->Library) and wait for it to complete. The resulting RedBoot files will be in the associated install directory, for the example this would be `redboot_RAM_install/bin`.

As noted above, each platform's details are described in Chapter 5. Use the information provided in the shell variables to find the configuration file - the path to it is `${ECOS_REPOSITORY}/hal/${ARCH_DIR}/${PLATFORM_DIR}/${VERSION}/misc/${REDBOOT_CFG}` where `ECOS_REPOSITORY` points to the eCos/RedBoot sources, `VERSION` is the version of the package (usually "current") and `REDBOOT_CFG` is the desired configuration, e.g. `redboot_RAM`.



# Chapter 4. Updating RedBoot

## Introduction

RedBoot normally resides in an EPROM or, more common these days, a flash on the board. In the former case, updating RedBoot necessitates physically removing the part and reprogramming a new RedBoot image into it using prommer hardware. In the latter case, it is often possible to update RedBoot in situ using Redboot's flash management commands.

The process of updating RedBoot in situ is documented in this section. For this process, it is assumed that the target is connected to a host system and that there is a serial connection giving access to the RedBoot CLI. For platforms with a ROMRAM mode RedBoot, skip to the Section called *Update the primary RedBoot flash image*.

**Note:** The addresses and sizes included in the below are examples only, and will differ from those you will see. This is normal and should not cause concern.

## Load and start a RedBoot RAM instance

There are a number of choices here. The basic case is where a RAM mode image has been stored in the FIS (flash Image System). To load and execute this image, use the commands:

```
RedBoot> fis load RedBoot[RAM]  
RedBoot> go
```

If this image is not available, or does not work, then an alternate RAM mode image must be loaded:

```
RedBoot> load redboot_RAM.img  
Entry point: 0x060213c0, address range: 0x06020000-0x060369c8  
RedBoot> go
```

**Note:** This command loads the RedBoot image using the TFTP protocol via a network connection. Other methods of loading are available, refer to the **load** command for more details.

**Note:** If you expect to be doing this more than once, it is a good idea to program the RAM mode image into the flash. You do this using the **fis create** command after having downloaded the RAM mode image, but before you start it.

Some platforms support locking (write protecting) certain regions of the flash, while others do not. If your platform does not support locking, simply ignore the **fis unlock** and **fis lock** steps (the commands will not be recognized by RedBoot).

```
RedBoot> fis unlock RedBoot[RAM]
... Unlock from 0x00000000-0x00020000: ..
RedBoot> fis create RedBoot[RAM]
An image named 'RedBoot[RAM]' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot[RAM]'
          at 0x00020000..0x000369c7 from 0x06020000 - continue (y/n)?y
... Erase from 0x00020000-0x00040000: ..
... Program from 0x06020000-0x060369c8 at 0x00020000: ..
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
RedBoot> fis lock RedBoot[RAM]
... Lock from 0x00000000-0x00020000: ..
```

## Update the primary RedBoot flash image

An instance of RedBoot should now be running on the target from RAM. This can be verified by looking for the mode identifier in the banner. It should be either [RAM] or [ROMRAM].

If this is the first time RedBoot is running on the board or if the flash contents has been damaged, initialize the FIS directory:

```
RedBoot> fis init -f
About to initialize [format] FLASH image system - continue (y/n)? y
*** Initialize FLASH Image System
... Erase from 0x00020000-0x00070000: .....
... Erase from 0x00080000-0x00080000:
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
```

It is important to understand that the presence of a correctly initialized FIS directory allows RedBoot to automatically determine the flash parameters. Additionally, executing the steps below as stated without loading other data or using other flash commands (than possibly **fis list**) allows RedBoot to automatically determine the image location and size parameters. This greatly reduces the risk of potential critical mistakes due to typographical errors. It is still always possible to explicitly specify parameters, and indeed override these, but it is not advised.

**Note:** If the new RedBoot image has grown beyond the slot in flash reserved for it, it is necessary to change the RedBoot configuration option `CYGBLD_REDBOOT_MIN_IMAGE_SIZE` so the FIS is created with adequate space reserved for RedBoot images. In this case, it is necessary to re-initialize the FIS directory as described above, using a RAM mode RedBoot compiled with the updated configuration.

Using the **load** command, download the new flash based image from the host, relocating the image to RAM::

```
RedBoot> load -r -b %{FREEMEMLO} redboot_ROM.bin
Raw file loaded 0x06046800-0x06062fe8, assumed entry at 0x06046800
```

**Note:** This command loads the RedBoot image using the TFTP protocol via a network connection. Other methods of loading are available, refer to the load command for more details.

**Note:** Note that the binary version of the image is being downloaded. This is to ensure that the memory after the image is loaded should match the contents of the file on the host. Loading SREC or ELF versions of the image does not guarantee this since these formats may contain holes, leaving bytes in these holes in an unknown state after the load, and thus causing a likely cksum difference. It is possible to use these, but then the step verifying the cksum below may fail.

Once the image is loaded into RAM, it should be checksummed, thus verifying that the image on the target is indeed the image intended to be loaded, and that no corruption of the image has happened. This is done using the cksum command:

```
RedBoot> cksum
Computing cksum for area 0x06046800-0x06062fe8
POSIX cksum = 2535322412 116712 (0x971df32c 0x0001c7e8)
```

Compare the numbers with those for the binary version of the image on the host. If they do not match, try downloading the image again.

Assuming the cksum matches, the next step is programming the image into flash using the FIS commands.

Some platforms support locking (write protecting) certain regions of the flash, while others do not. If your platform does not support locking, simply ignore the **fis unlock** and **fis lock** steps (the commands will not be recognized by RedBoot).

```
RedBoot> fis unlock RedBoot
```

```
... Unlock from 0x00000000-0x00020000: ..
RedBoot> fis create RedBoot
An image named 'RedBoot' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot'
      at 0x00000000..0x0001c7e7 from 0x06046800 - continue (y/n)? y
... Erase from 0x00000000-0x00020000: ..
... Program from 0x06046800-0x06062fe8 at 0x00000000: ..
... Erase from 0x00070000-0x00080000: .
... Program from 0x0606f000-0x0607f000 at 0x00070000: .
RedBoot> fis lock RedBoot
... Lock from 0x00000000-0x00020000: ..
```

## Reboot; run the new RedBoot image

Once the image has been successfully written into the flash, simply reset the target and the new version of RedBoot should be running.

When installing RedBoot for the first time, or after updating to a newer RedBoot with different configuration keys, it is necessary to update the configuration directory in the flash using the **fconfig** command. See the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2.

# Chapter 5. Installation and Testing

## AM3x/MN103E010 Matsushita MN103E010 (AM33/2.0) ASB2305 Board

### Overview

RedBoot supports the debug serial port and the built in ethernet port for communication and downloads. The default serial port settings are 115200,8,N,1 with RTS/CTS flow control. RedBoot can run from either flash, and can support flash management for either the boot PROM or the system flash regions.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
PROM	[ROM]	RedBoot running from the boot PROM and able to access the system flash.	redboot_ROM.ecm
FLASH	[ROM]	RedBoot running from the system flash and able to access the boot PROM.	redboot_FLASH.ecm
RAM	[RAM]	RedBoot running from RAM and able to access the boot PROM.	redboot_RAM.ecm

### Initial Installation

Unless a pre-programmed system flash module is available to be plugged into a new board, RedBoot must be installed with the aid of a JTAG interface unit. To achieve this, the RAM mode RedBoot must be loaded directly into RAM by JTAG and started, and then *that* must be used to store the ROM mode RedBoot into the boot PROM.

These instructions assume that you have binary images of the RAM-based and boot PROM-based RedBoot images available.

## Preparing to program the board

If the board is to be programmed, whether via JTAG or RedBoot, some hardware settings need to be changed:

- Jumper across ST18 on the board to allow write access to the boot PROM.
- Set DIP switch S1-3 to OFF to allow RedBoot to write to the system flash.
- Set the switch S5 (on the front of the board) to boot from whichever flash is *not* being programmed. Note that the RedBoot image cannot access the flash from which it is currently executing (it can only access the other flash).

The RedBoot binary image files should also be copied to the TFTP pickup area on the host providing TFTP services if that is how RedBoot should pick up the images it is going to program into the flash. Alternatively, the images can be passed by YMODEM over the serial link.

## Preparing to use the JTAG debugger

The JTAG debugger will also need setting up:

1. Install the JTAG debugger software (WICE103E) on a PC running Windows (WinNT is probably the best choice for this) in “C:/PanaX”.
2. Install the Matsushita provided “project” into the “C:/PanaX/wice103e/prj” directory.
3. Install the RedBoot image files into the “C:/PanaX/wice103e/prj” directory under the names redboot.ram and redboot.prom.
4. Make sure the PC’s BIOS has the parallel port set to full bidirectional mode.
5. Connect the JTAG debugger to the PC’s parallel port.
6. Connect the JTAG debugger to the board.
7. Set the switch on the front of the board to boot from “boot PROM”.
8. Power up the JTAG debugger and then power up the board.
9. Connect the board’s Debug Serial port to a computer by a null modem cable.
10. Start minicom or some other serial communication software and set for 115200 baud, 1-N-8 with hardware (RTS/CTS) flow control.

## Loading the RAM-based RedBoot via JTAG

To perform the first half of the operation, the following steps should be followed:

1. Start the JTAG debugger software.

2. Run the following commands at the JTAG debugger's prompt to set up the MMU registers on the CPU.

```
ed 0xc0002000, 0x12000580

ed 0xd8c00100, 0x8000fe01
ed 0xd8c00200, 0x21111000
ed 0xd8c00204, 0x00100200
ed 0xd8c00208, 0x00000004

ed 0xd8c00110, 0x8400fe01
ed 0xd8c00210, 0x21111000
ed 0xd8c00214, 0x00100200
ed 0xd8c00218, 0x00000004

ed 0xd8c00120, 0x8600ff81
ed 0xd8c00220, 0x21111000
ed 0xd8c00224, 0x00100200
ed 0xd8c00228, 0x00000004

ed 0xd8c00130, 0x8680ff81
ed 0xd8c00230, 0x21111000
ed 0xd8c00234, 0x00100200
ed 0xd8c00238, 0x00000004

ed 0xd8c00140, 0x9800f801
ed 0xd8c00240, 0x00140000
ed 0xd8c00244, 0x11011100
ed 0xd8c00248, 0x01000001

ed 0xda000000, 0x55561645
ed 0xda000004, 0x000003c0
ed 0xda000008, 0x9000fe01
ed 0xda00000c, 0x9200fe01
ed 0xda000000, 0xa89b0654
```

3. Run the following commands at the JTAG debugger's prompt to tell it what regions of the CPU's address space it can access:

```
ex 0x80000000,0x81ffffff, /mexram
ex 0x84000000,0x85ffffff, /mexram
ex 0x86000000,0x867ffffff, /mexram
ex 0x86800000,0x87ffffff, /mexram
ex 0x8c000000,0x8cffffff, /mexram
ex 0x90000000,0x93ffffff, /mexram
```

4. Instruct the debugger to load the RAM RedBoot image into RAM:

```
_pc=90000000  
u_pc  
rd redboot.ram,90000000
```

5. Load the boot PROM RedBoot into RAM:

```
rd redboot.prom,91020000
```

6. Start RedBoot in RAM:

```
g
```

Note that RedBoot may take some time to start up, as it will attempt to query a BOOTP or DHCP server to try and automatically get an IP address for the board. Note, however, that it should send a plus over the serial port immediately, and the 7-segment LEDs should display “rh 8”.

## Loading the boot PROM-based RedBoot via the RAM mode RedBoot

Once the RAM mode RedBoot is up and running, it can be communicated with by way of the serial port. Commands can now be entered directly to RedBoot for flashing the boot PROM.

1. Instruct RedBoot to initialise the boot PROM:

```
RedBoot> fi init
```

2. Write the previously loaded redboot.prom image into the boot PROM:

```
RedBoot> fi write -f 0x80000000 -b 0x91020000 -l 0x00020000
```

3. Check that RedBoot has written the image:

```
RedBoot> dump -b 0x91020000
```

```
RedBoot> dump -b 0x80000000
```

Barring the difference in address, the two dumps should be the same.

4. Close the JTAG software and power-cycle the board. The RedBoot banners should be displayed again over the serial port, followed by the RedBoot prompt. The boot PROM-based RedBoot will now be running.

5. Power off the board and unjumper ST18 to write-protect the contents of the boot PROM. Then power the board back up.
6. Run the following command to initialise the system flash:

```
RedBoot> fi init
```

Then program the system flash based RedBoot into the system flash:

```
RedBoot> load -r -b %{FREEMEMLO} redboot_FLASH.bin
RedBoot> fi write -f 0x84000000 -b %{FREEMEMLO} -l 0x00020000
```

**NOTE:** RedBoot arranges the flashes on booting such that they always appear at the same addresses, no matter which one was booted from.

7. A similar sequence of commands can be used to program the boot PROM when RedBoot has been booted from an image stored in the system flash.

```
RedBoot> load -r -b %{FREEMEMLO} /tftpboot/redboot_ROM.bin
RedBoot> fi write -f 0x80000000 -b %{FREEMEMLO} -l 0x00020000
```

See the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2 for details on configuring the RedBoot in general, and also the Section called *Flash Image System (FIS)* in Chapter 2 for more details on programming the system flash.

## Additional Commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this architecture (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for ASB2305 board are:

**-w** *<time>*

Wait time in seconds before starting kernel

**-c** *"params"*

Parameters passed to kernel

*<addr>*

Kernel entry point, defaulting to the entry point of the last image loaded

The parameter string is stored in the on-chip memory at location 0x8C001000, and is prefixed by "cmdline:" if it was supplied.

## Memory Maps

RedBoot sets up the following memory map on the ASB2305 board.

**NOTE:** The regions mapped between 0x80000000-0x9FFFFFFF are cached by the CPU. However, all those regions can be accessed uncached by adding 0x20000000 to the address.

Physical Address Range	Description
-----	-----
0x80000000 - 0x9FFFFFFF	Cached Region
0x80000000 - 0x81FFFFFF	Boot PROM
0x84000000 - 0x85FFFFFF	System Flash
0x86000000 - 0x86007FFF	64Kbit Sys Config EEPROM
0x86F90000 - 0x86F90003	4x 7-segment LEDs
0x86FA0000 - 0x86FA0003	Software DIP Switches
0x86FB0000 - 0x86FB001F	PC16550 Debug Serial Port
0x8C000000 - 0x8FFFFFFF	On-Chip Memory (repeated 16Kb SRAM)
0x90000000 - 0x93FFFFFF	SDRAM
0x98000000 - 0x9BFFFFFF	Paged PCI Memory Space (64Mb)
0x9C000000 - 0x9DFFFFFF	PCI Local SRAM (32Mb)
0x9E000000 - 0x9E03FFFF	PCI I/O Space
0x9E040000 - 0x9E0400FF	AM33-PCI Bridge Registers
0x9FFFFFF4 - 0x9FFFFFF7	PCI Memory Page Register
0x9FFFFFF8 - 0x9FFFFFFF	PCI Config Registers
0xA0000000 - 0xBFFFFFFF	Uncached Mirror Region
0xC0000000 - 0xDFFFFFFF	CPU Control Registers

The ASB2305 HAL makes use of the on-chip memory in the following way:

0x8C000000 - 0x8C0000FF	hal_vsr_table
0x8C000100 - 0x8C0001FF	hal_virtual_vector_table
0x8C001000 -	Linux command line (RedBoot exec command)
- 0x8C003FFF	Emergency DoubleFault Exception Stack

Currently the CPU's interrupt table lies at the beginning of the RedBoot image, which must therefore be aligned to a 0xFF000000 mask.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=asb2305
export ARCH_DIR=mn10300
export PLATFORM_DIR=asb2305
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/ARM7 ARM Evaluator7T

### Overview

RedBoot supports both serial ports for communication and downloads. The default serial port settings are 38400,8,N,1.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from flash address 0x20000, with ARM Boot Monitor in flash boot sector.	redboot_ROMA.ecm

### Initial Installation

RedBoot is installed using the on-board boot environment. See the user manual for full details.

### Quick download instructions

Here are quick start instructions for downloading the prebuilt Redboot image:

- Boot the board and press ENTER:

```
ARM Evaluator7T Boot Monitor PreRelease 1.00
Press ENTER within 2 seconds to stop autoboot
Boot:
```

- Erase the part of the flash where RedBoot will get programmed:

```
Boot: flasherase 01820000 10000
```

- Prepare to download the UU-encoded version of the RedBoot image:

```
Boot: download 10000  
Ready to download. Use 'transmit' option on terminal emulator to download
```

- Either use ASCII transmit option in the terminal emulator, or on Linux, simply cat the file to the serial port:

```
$ cat redboot.UU > /dev/ttyS0
```

When complete, you should see:

```
Loaded file redboot.bin at address 000100000, size = 41960  
Boot:
```

- Program the flash:

```
Boot: flashwrite 01820000 10000 10000
```

- And verify that the module is available:

```
Boot: rommodules  
Header   Base      Limit  
018057c8 01800000 018059e7 BootStrapLoader v1.0 Apr 27 2000 10:33:58  
01828f24 01820000 0182a3e8 RedBoot Apr 5 2001
```

- Reboot the board and you should see the RedBoot banner.

## Special RedBoot Commands

None.

## Memory Maps

RedBoot sets up the following memory map on the E7T board.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address	Range	C	B	Description
0x00000000	- 0x0007ffff	Y	N	SDRAM
0x03ff0000	- 0x03ffffff	N	N	Microcontroller registers
0x01820000	- 0x0187ffff	N	N	System flash (mirrored)

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=e7t
export ARCH_DIR=arm
export PLATFORM_DIR=e7t
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/ARM7+ARM9 ARM Integrator

### Overview

RedBoot supports both serial ports for communication and downloads. The default serial port settings are 38400,8,N,1.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm

## Initial Installation

RedBoot is installed using the on-board bootPROM environment. See the user manual for full details.

## Quick download instructions

Here are quick start instructions for downloading the prebuilt Redboot image:

- Set DIP switch S1[1] to the ON position and reset or power the board up. You will see the bootPROM startup message on serial port A (J14):

```
Initialising...
```

```
ARM bootPROM [Version 1.3] Rebuilt on Jun 26 2001 at 22:04:10
Running on a Integrator Evaluation Board
Board Revision V1.0, ARM966E-S Processor
Memory Size is 16MBytes, Flash Size is 32MBytes
Copyright (c) ARM Limited 1999 - 2001. All rights reserved.
Board designed by ARM Limited
Hardware support provided at http://www.arm.com/
For help on the available commands type ? or h
boot Monitor >
```

- Issue the FLASH ROM load command:

```
boot Monitor > L
Load Motorola S-Records into flash
```

```
Deleting Image 0
```

```
The S-Record loader only accepts input on the serial port.
Type Ctrl/C to exit loader.
```

- Either use the ASCII transmit option in the terminal emulator, or on Linux, simply cat the file to the serial port:

```
$ cat redboot.srec > /dev/ttyS0
```

When complete, type Ctrl-C and you should see something similar to:

```
.....
.....
.....
Downloaded 5,394 records in 81 seconds.
```

```
Overwritten block/s
0
```

```
boot Monitor >
```

- Set DIP switch S1[1] to the OFF position and reboot the board and you should see the RedBoot banner.

## Special RedBoot Commands

None.

## Memory Maps

RedBoot sets up the following memory map on the Integrator board.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

```
ARM7TDMI
-----
```

Physical Address Range	C	B	Description
0x00000000 - 0x0007ffff	N	N	SSRAM
0x00080000 - 0x0fffffff	N	N	SDRAM (depends on part fitted)
0x10000000 - 0x1fffffff	N	N	System control and peripheral registers
0x20000000 - 0x23ffffff	N	N	Boot ROM (contains boot Monitor)
0x24000000 - 0x27ffffff	N	N	FLASH ROM (contains RedBoot)
0x28000000 - 0x2bffffff	N	N	SSRAM echo area
0x40000000 - 0x5fffffff	N	N	PCI Memory access windows
0x60000000 - 0x60ffffff	N	N	PCI IO access window
0x61000000 - 0x61ffffff	N	N	PCI config space window
0x62000000 - 0x6200ffff	N	N	PCI bridge register window
0x80000000 - 0x8fffffff	N	N	SDRAM echo area (used for PCI accesses)

```
ARM966E
-----
```

Physical Address Range	C	B	Description
-----	-	-	-----

```
0x00000000 - 0x000fffff N N  SSRAM
0x00100000 - 0x0fffffff N N  SDRAM (depends on part fitted)
0x10000000 - 0x1fffffff N N  System control and peripheral registers
0x20000000 - 0x23ffffff N N  Boot ROM (contains boot Monitor)
0x24000000 - 0x27ffffff N N  FLASH ROM (contains RedBoot)
0x28000000 - 0x2bffffff N N  SSRAM echo area
0x40000000 - 0x5fffffff N N  PCI Memory access windows
0x60000000 - 0x60ffffff N N  PCI IO access window
0x61000000 - 0x61ffffff N N  PCI config space window
0x62000000 - 0x6200ffff N N  PCI bridge register window
0x80000000 - 0x8fffffff N N  SDRAM echo area (used for PCI accesses)
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=integrator
export ARCH_DIR=arm
export PLATFORM_DIR=integrator
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/ARM7+ARM9 ARM PID Board and EPI Dev7+Dev9

## Overview

RedBoot uses either of the serial ports. The default serial port settings are 38400,8,N,1. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm

Configuration	Mode	Description	File
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

Device programmer is used to program socketed flash parts with ROM version of RedBoot.

Alternatively, to install RedBoot on a target that already has eCos GDB stubs, download the RAM mode image of RedBoot and run it. Initialize the flash image directory: **fis init** Then download the ROM version of RedBoot and program it into flash:

```
RedBoot> load -b %{FREEMEMLO} -m yodem
RedBoot> fi cr RedBoot
```

## Special RedBoot Commands

None.

## Memory Maps

RedBoot sets up the following memory map on the PID board.

```
Physical Address Range Description
-----
0x00000000 - 0x0007ffff DRAM
0x04000000 - 0x04080000 flash
0x08000000 - 0x09ffffff ASB Expansion
0x0a000000 - 0x0bffffff APB Reference Peripheral
0x0c000000 - 0x0fffffff NISA Serial, Parallel and PC Card ports
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=pid
export ARCH_DIR=arm
export PLATFORM_DIR=pid
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/ARM7 Atmel AT91 Evaluation Board (EB40)

### Overview

RedBoot supports both serial ports. The default serial port settings are 38400,8,N,1. RedBoot also supports minimal flash management on the EB40. However, since the flash device (AT29LV1024) is so small (only the upper 64K is available for general use), only 'fconfig' is supported, along with the simple flash write command, 'fis write'.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm

## Initial Installation Method

This development board comes with ARM's debug tool, Angel, installed in flash. At this time, Angel will not be replaced. Rather, RedBoot will be placed in the alternate half of flash. Switch SW1 is used which monitor to boot. Selecting SW1 to "lower mem" will choose Angel. Select SW1 to "Upper mem" for RedBoot once it has been installed.

Set SW1 to "lower mem" and connect serial port A to a host computer. Using GDB from the host and Angel on the board, download the RAM mode image of RedBoot to the board. Once this is started, the Angel session must be interrupted (on Linux this can be done using ^Z). Follow this by connecting to the board using minicom at 38400-8N1. At this point, RedBoot will be running on the board in RAM. Now, download the ROMRAM mode image and program it to flash. Be sure and first set SW1 to "upper mem".

```
arm-elf-gdb redboot_RAM.elf
```

```
(gdb) tar rdi s=/dev/ttyS0
```

```
Angel Debug Monitor (serial) 1.04 (Advanced RISC Machines SDT 2.5) for
AT91EB40 (2.00)
```

```
Angel Debug Monitor rebuilt on Apr 07 2000 at 12:40:31
```

```
Serial Rate: 9600
```

```
Connected to ARM RDI target.
```

```
(gdb) set $ps=0xd3
```

```
(gdb) load
```

```
Loading section .rom_vectors, size 0x40 lma 0x2020000
```

```
Loading section .text, size 0x7fd8 lma 0x2020040
```

```
Loading section .rodata, size 0x15a0 lma 0x2028018
```

```
Loading section .data, size 0x2e4 lma 0x20295b8
```

```
Start address 0x2020040 , load size 39068
```

```
Transfer rate: 6250 bits/sec, 500 bytes/write.
```

```
(gdb) cont
```

```
Continuing.
```

At this point, suspend the GDB session (use Ctrl-Z) and start a terminal emulator:

```
RedBoot> version
```

```
RedBoot(tm) bootstrap and debug environment [RAM]
```

```
Non-certified release, version UNKNOWN - built 14:09:27, Jul 20 2001
```

```
Platform: Atmel AT91/EB40 (ARM7TDMI)
```

```
Copyright (C) 2000, 2001, Red Hat, Inc.
```

```
RAM: 0x02000000-0x02080000, 0x020116d8-0x0207fd00 available
```

```
FLASH: 0x01010000 - 0x01020000, 256 blocks of 0x00000100 bytes each.
```

```
RedBoot> load -m ymodem -b %}{FREEMEMLO}
```

Use minicom to send the file redboot\_ROMRAM.srec via YModem.

```
RedBoot> fi wr -f 0x01010000 -b %{FREEMEMLO} -l 0xe000
```

Set switch SW1 to "upper mem", press the "reset" pushbutton and RedBoot should come up on the board.

## Special RedBoot Commands

None.

## Memory Maps

This processor has no MMU, so the only memory map is for physical addresses.

Physical Address Range	Description
0x00000000 - 0x00000fff	On-chip SRAM
0x01000000 - 0x0101ffff	Flash
0x02000000 - 0x0207ffff	RAM
0xffe00000 - 0xffffffff	I/O registers

The flash based RedBoot image occupies virtual addresses 0x01010000 - 0x0101dfff

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=eb40
export ARCH_DIR=arm
export PLATFORM_DIR=at91
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/ARM7 Cirrus Logic EP7xxx (EDB7211, EDB7212, EDB7312)

## Overview

RedBoot supports both serial ports on the board and the ethernet port. The default serial port settings are 38400,8,N,1. RedBoot also supports flash management on the EDB7xxx for the NOR flash only.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector (EDB7312 only).	redboot_ROMRAM.ecm

## Initial Installation Method

A Windows or Linux utility is used to program flash using serial port #1 via on-chip programming firmware. See board documentation for details on in situ flash programming.

## Special RedBoot Commands

None.

## Memory Maps

The MMU page tables and LCD display buffer, if enabled, are located at the end of DRAM.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range			Description
-----			-----
0x00000000 - 0x01ffffff			NOR Flash (EDB7211, EDB7212)
0x00000000 - 0x00ffffff			NOR Flash (EDB7312)
0x10000000 - 0x11ffffff			NAND Flash
0x20000000 - 0x2ffffff			Expansion 2
0x30000000 - 0x3ffffff			Expansion 3
0x40000000 - 0x4ffffff			PCMCIA 0
0x50000000 - 0x5ffffff			PCMCIA 1
0x60000000 - 0x600007ff			On-chip SRAM
0x80000000 - 0x8ffffff			I/O registers
0xc0000000 - 0xc1ffffff			DRAM (EDB7211, EDB7212)
0xc0000000 - 0xc0ffffff			DRAM (EDB7312)

  

Virtual Address Range	C	B	Description
-----			-----
0x00000000 - 0x01ffffff	Y	Y	DRAM
0x00000000 - 0x00fcffff	Y	Y	DRAM (EDB7312)
0x20000000 - 0x2ffffff	N	N	Expansion 2
0x30000000 - 0x3ffffff	N	N	Expansion 3
0x40000000 - 0x4ffffff	N	N	PCMCIA 0
0x50000000 - 0x5ffffff	N	N	PCMCIA 1
0x60000000 - 0x600007ff	Y	Y	On-chip SRAM
0x80000000 - 0x8ffffff	N	N	I/O registers
0xc0000000 - 0xc001ffff	N	Y	LCD buffer (if configured)
0xe0000000 - 0xe1ffffff	Y	Y	NOR Flash (EDB7211, EDB7212)
0xe0000000 - 0xe0ffffff	Y	Y	NOR Flash (EDB7312)
0xf0000000 - 0xf1ffffff	Y	Y	NAND Flash

The flash based RedBoot image occupies virtual addresses 0xe0000000 - 0xe003ffff.

## Platform Resource Usage

The EP7xxx timer #2 is used as a polled timer to provide timeout support for network and XModem file transfers.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=edb7211
export TARGET=edb7212
export TARGET=edb7312
export ARCH_DIR=arm
export PLATFORM_DIR=edb7xxx
```

Use one of the TARGET settings only.

The names of configuration files are listed above with the description of the associated modes.

## ARM/ARM9 Agilent AAED2000

### Overview

RedBoot supports the serial and ethernet ports on the board. The default serial port settings are 38400,8,N,1. RedBoot also supports flash management on the AAED2000.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_primary_ROMRAM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_primary_RAM.ecm

### Initial Installation Method

It is possible to install RedBoot in one of two ways. Either as the primary bootmonitor on the board (installed to blocks 0-1 of the flash) or as the secondary bootmonitor on the board (installed

to blocks 1-2 of the flash).

Presently, only the former method is supported.

## RedBoot as Primary Bootmonitor

RedBoot is installed in flash using the on-board ARM Boot Monitor.

Boot the board while pressing SPACE. This should bring up the Boot Monitor:

```
ARM bootPROM [Version 1.3] Rebuilt on Jul 16 2001 at 16:21:36
Running on a P920 board Evaluation Board
Board Revision V1.0, ARM920T processor Processor
Memory Size is 32MBytes, Flash Size is 32MBytes
Copyright (c) ARM Limited 1999 - 2001. All rights reserved.
Board designed by ARM Limited
Hardware support provided at http://www.arm.com/
For help on the available commands type ? or h
boot Monitor >
```

Download the RAM mode image of RedBoot configured as a primary bootmonitor using the ARM bootmonitor's SREC-download command:

```
boot Monitor > m
Load Motorola S-Record image into memory and execute it
The S-Record loader only accepts input on the serial port.
Record addresses must be between 0x00008000 and 0x01E0F510.
Type Ctrl/C to exit loader.
```

Use the terminal emulator's ASCII upload command, or (on Linux) simply cat the file to the serial port:

```
$ cat redboot_primary_RAM/redboot.srec >/dev/ttyS1
```

You should see RedBoot start up:

```
FLASH configuration checksum error or invalid key
Ethernet eth0: MAC address 00:30:d3:03:04:99
IP: 192.168.42.111, Default server: 192.168.42.3

RedBoot(tm) bootstrap and debug environment [RAM]
Non-certified release, version UNKNOWN - built 13:15:40, Nov  9 2001

Platform: AAED2000 system (ARM9) [Primary]
Copyright (C) 2000, 2001, Red Hat, Inc.

RAM: 0x00000000-0x01f80000, 0x0006f208-0x01f51000 available
FLASH: 0x60000000 - 0x62000000, 256 blocks of 0x00020000 bytes each.
RedBoot>
```

As can be seen from the output above, the network has been configured to give the board an IP address and information about the default server. If things are not set up on your network, you can still continue, but use the Y-modem download method when loading the RedBoot ROMRAM mode image. Now initialize RedBoot's FIS:

```
RedBoot> fis init
About to initialize [format] FLASH image system - continue (y/n)? y
*** Initialize FLASH Image System
    Warning: device contents not erased, some blocks may not be usable
... Erase from 0x61fe0000-0x62000000: .
... Program from 0x01f5f000-0x01f5f300 at 0x61fe0000: .
```

Download the ROMRAM mode image of RedBoot via ethernet:

```
RedBoot> load -b %{FREEMEMLO} redboot_primary_ROMRAM/redboot.srec
```

or using serial Y-modem protocol:

```
RedBoot> load -mode ymodem -b %{FREEMEMLO}
```

(Use the terminal emulator's Y-modem upload command to send the file `redboot_primary_ROMRAM/redboot.srec`.) When the image has been downloaded, program it into flash:

```
Address offset = 0x00ff8000
Entry point: 0x00008040, address range: 0x00008000-0x0002da80
RedBoot> fi cr RedBoot
An image named 'RedBoot' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot'
    at 0x60000000..0x6003ffff from 0x00100000 - continue (y/n)? y
... Erase from 0x60000000-0x60040000: ..
... Program from 0x00100000-0x00140000 at 0x60000000: ..
... Erase from 0x61fe0000-0x62000000: .
... Program from 0x01f5f000-0x01f7f000 at 0x61fe0000: .
```

Now reset the board. You should see the RedBoot banner.

## Special RedBoot Commands

The `exec` command which allows the loading and execution of Linux kernels, is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The `exec` parameters used for the AAED2000 are:

`-b <addr>`

Location Linux kernel was loaded to

`-l <len>`  
Length of kernel

`-c "params"`  
Parameters passed to kernel

`-r <addr>`  
'initrd' ramdisk location

`-s <len>`  
Length of initrd ramdisk

The parameters for kernel image base and size are automatically set after a load operation. So one way of starting the kernel would be:

```
RedBoot> load -r -b 0x100000 zImage
Raw file loaded 0x00100000-0x001a3d6c
RedBoot> exec -c "console=ttyAC0,38400"
Using base address 0x00100000 and length 0x000a3d6c
Uncompressing Linux.....
```

An image could also be put in flash and started directly:

```
RedBoot> exec -b 0x60040000 -l 0xc0000 -c "console=ttyAC0,38400"
Uncompressing Linux.....
```

## Memory Maps

The MMU page tables are located at 0x4000.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
0x00000000 - 0x01ffffff	Flash
0x10000000 - 0x100ffffff	Ethernet
0x30000000 - 0x300ffffff	Board registers
0x40000000 - 0x4ffffff	PCMCIA Slot (0)
0x50000000 - 0x5ffffff	Compact Flash Slot (1)
0x80000000 - 0x800037ff	I/O registers

```
0xb0060000 - 0xb00fffff    On-chip SRAM
0xf0000000 - 0xfd3fffff    SDRAM
```

Virtual Address Range	C	B	Description
0x00000000 - 0x01f7ffff	Y	Y	SDRAM
0x01f80000 - 0x01ffffff	Y	Y	SDRAM (used for LCD frame buffer)
0x10000000 - 0x100fffff	N	N	Ethernet
0x30000000 - 0x300fffff	N	N	Board registers
0x40000000 - 0x4ffffff	N	N	PCMCIA Slot (0)
0x50000000 - 0x5ffffff	N	N	Compact Flash Slot (1)
0x60000000 - 0x61ffffff	N	N	Flash
0x80000000 - 0x800037ff	N	N	I/O registers
0xf0000000 - 0xfffffff	N	N	SDRAM (uncached)

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=aaed
export ARCH_DIR=arm
export PLATFORM_DIR=arm9/aaed2000
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/ARM9 Cirrus Logic SEB9312 (EP93xx) (aka SEB9213)

### Overview

RedBoot supports the serial port labelled 'modem inteface' on the board and the ethernet port. The default serial port settings are 38400,8,N,1. RedBoot also supports flash management on the SEB9312.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

**NOTE:** The cache is currently disabled as this feature does not seem to work properly with the beta silicon; it interacts badly with flash management activities and network usage.

## Initial Installation Method

A Windows or Linux utility is used to program flash using the 'modem interface' serial port via on-chip programming firmware. See board documentation for details on in situ flash programming.

## Special RedBoot Commands

No special commands.

One special **fconfig** option is provided to control the ethernet station address (ESA or 'MAC address').

```
RedBoot> fconfig -l
....
Local IP address: 10.16.19.10
Default server IP address: 10.16.19.66
Network hardware address [MAC]: 0x00:0x12:0x34:0x56:0x78:0xAB
...
RedBoot> fconfig ep93xx_esa
ep93xx_esa: 0x00:0x12:0x34:0x56:0x78:0xAB
```

## Memory Maps

The MMU page tables are located at the end of DRAM.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range			Description
-----			-----
0x00000000 - 0x01ffffff			DRAM
0x24000000 - 0x247ffffff			Flash
0x28000000 - 0x280ffffff			SRAM
0x80000000 - 0x8fffffff			I/O registers
Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x01ffffff	Y	Y	DRAM
0x24000000 - 0x247ffffff	Y	Y	Flash
0x28000000 - 0x2800ffff	Y	Y	On-chip SRAM
0x80000000 - 0x8fffffff	N	N	I/O registers
0xC0000000 - 0xC1ffffff	N	N	Non-cachable access to DRAM

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=seb9312
export ARCH_DIR=arm
export PLATFORM_DIR=arm9/ep93xx
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/StrongARM(SA110) Intel EBSA 285

### Overview

RedBoot uses the single EBSA-285 serial port. The default serial port settings are 38400,8,N,1. If the EBSA-285 is used as a host on a PCI backplane, ethernet is supported using an Intel PRO/100+ ethernet adapter. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation Method

A linux application is used to program the flash over the PCI bus. Sources and build instructions for this utility are located in the RedBoot sources in: `packages/hal/arm/ebsa285/current/support/linux/safl_util`

### Communication Channels

Serial, Intel PRO 10/100+ 82559 PCI ethernet card.

### Special RedBoot Commands

None.

### Memory Maps

Physical and virtual mapping are mapped one to one on the EBSA-285 using a first level page table located at address 0x4000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Address Range	C	B	Description
0x00000000 - 0x01ffffff	Y	Y	SDRAM
0x40000000 - 0x400fffff	N	N	21285 Registers
0x41000000 - 0x413fffff	Y	N	flash
0x42000000 - 0x420fffff	N	N	21285 CSR Space
0x50000000 - 0x50ffffff	Y	Y	Cache Clean
0x78000000 - 0x78ffffff	N	N	Outbound Write Flush
0x79000000 - 0x7c0fffff	N	N	PCI IACK/Config/IO
0x80000000 - 0xffffffff	N	Y	PCI Memory

## Platform Resource Usage

Timer3 is used as a polled timer to provide timeout support for networking and XModem file transfers.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=ebsa285
export ARCH_DIR=arm
export PLATFORM_DIR=ebsa285
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA1100) Intel Brutus

## Overview

RedBoot supports both board serial ports on the Brutus board. The default serial port settings are 38400,8,N,1. flash management is not currently supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

Device programmer is used to program socketed flash parts.

## Special RedBoot Commands

None.

## Memory Maps

The first level page table is located at physical address 0xc0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
----- 0x00000000 - 0x000fffff	----- Boot ROM

```

0x08000000 - 0x083ffffff Application flash
0x10000000 - 0x100ffffff SRAM
0x18000000 - 0x180ffffff Chip Select 3
0x20000000 - 0x3fffffff PCMCIA
0x80000000 - 0xbfffffff SA-1100 Internal Registers
0xc0000000 - 0xc7fffffff DRAM Bank 0
0xc8000000 - 0xcfffffff DRAM Bank 1
0xd0000000 - 0xd7fffffff DRAM Bank 2
0xd8000000 - 0xdffffffff DRAM Bank 3
0xe0000000 - 0xe7fffffff Cache Clean

```

Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x003ffffff	Y	Y	DRAM Bank 0
0x00400000 - 0x007ffffff	Y	Y	DRAM Bank 1
0x00800000 - 0x00bffffff	Y	Y	DRAM Bank 2
0x00c00000 - 0x00fffffff	Y	Y	DRAM Bank 3
0x08000000 - 0x083ffffff	Y	Y	Application flash
0x10000000 - 0x100ffffff	Y	N	SRAM
0x20000000 - 0x3fffffff	N	N	PCMCIA
0x40000000 - 0x400ffffff	Y	Y	Boot ROM
0x80000000 - 0xbfffffff	N	N	SA-1100 Internal Registers
0xe0000000 - 0xe7fffffff	Y	Y	Cache Clean

## Platform Resource Usage

The SA11x0 OS timer is used as a polled timer to provide timeout support for XModem file transfers.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```

export TARGET=brutus
export ARCH_DIR=arm
export PLATFORM_DIR=s11x0/brutus

```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA1100) Intel SA1100 Multimedia Board

## Overview

RedBoot supports both board serial ports. The default serial port settings are 38400,8,N,1. flash management is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

A device programmer is used to program socketed flash parts.

## Special RedBoot Commands

None.

## Memory Maps

The first level page table is located at physical address 0xc0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range      Description

Virtual Address Range	C	B	Description
0x00000000 - 0x000fffff			Boot flash
0x08000000 - 0x083fffff			Application flash
0x10000000 - 0x107fffff			SA-1101 Board Registers
0x18000000 - 0x180fffff			Ct8020 DSP
0x18400000 - 0x184fffff			XBusReg
0x18800000 - 0x188fffff			SysRegA
0x18c00000 - 0x18cfffff			SysRegB
0x19000000 - 0x193fffff			Spare CPLD A
0x19400000 - 0x197fffff			Spare CPLD B
0x20000000 - 0x3fffffff			PCMCIA
0x80000000 - 0xbfffffff			SA1100 Internal Registers
0xc0000000 - 0xc07fffff			DRAM Bank 0
0xe0000000 - 0xe7fffffff			Cache Clean
0x00000000 - 0x007fffff	Y	Y	DRAM Bank 0
0x08000000 - 0x083fffff	Y	Y	Application flash
0x10000000 - 0x100fffff	N	N	SA-1101 Registers
0x18000000 - 0x180fffff	N	N	Ct8020 DSP
0x18400000 - 0x184fffff	N	N	XBusReg
0x18800000 - 0x188fffff	N	N	SysRegA
0x18c00000 - 0x18cfffff	N	N	SysRegB
0x19000000 - 0x193fffff	N	N	Spare CPLD A
0x19400000 - 0x197fffff	N	N	Spare CPLD B
0x20000000 - 0x3fffffff	N	N	PCMCIA
0x50000000 - 0x500fffff	Y	Y	Boot flash
0x80000000 - 0xbfffffff	N	N	SA1100 Internal Registers
0xc0000000 - 0xc07fffff	N	Y	DRAM Bank 0
0xe0000000 - 0xe7fffffff	Y	Y	Cache Clean

## Platform Resource Usage

The SA11x0 OS timer is used as a polled timer to provide timeout support for XModem file transfers.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=sal1100mm
export ARCH_DIR=arm
export PLATFORM_DIR=sal1x0/sal1100mm
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/StrongARM(SA1110) ASCOM/ACN PLC2 Board

### Overview

RedBoot supports the board serial ports attached to UART1 and UART3. Both channels are used for the RedBoot prompt et al, and you can connect using GDB to either.

The default serial port settings are 38400,8,N,1.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
POST	[ROM]	RedBoot running at address 0x40000 in flash, for cooperation with customer POST code.	redboot_POST.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

A Linux utility Jflash is used to program FLASH over a parallel port driven JTAG interface. A special hardware box from ACN is required. After that, RedBoot can be managed and upgraded in the usual manner using its own flash management commands in the usual manner; **fis init** will fill in appropriate defaults for the flash addresses concerned.

## Special RedBoot Commands

None.

## Memory Maps

The first level page table is located at physical address 0xc0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range			Description
-----			-----
0x00000000 - 0x007ffffff			8Mb flash (nCS0)
0x18000000 - 0x180ffffff			Altera FPGA and X-Bus (nCS3)
0x20000000 - 0x2ffffff			PCMCIA slot 0 - LAN91C96 Ethernet
0x80000000 - 0xbffffff			SA-1110 Internal Registers
0xc0000000 - 0xc7ffffff			DRAM Bank 0
0xc8000000 - 0xcffffff			DRAM Bank 1
0xe0000000 - 0xe7ffffff			Cache Clean

  

Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x001ffffff	Y	Y	DRAM - 8Mb to 32Mb
0x18000000 - 0x180ffffff	N	N	Altera FPGA and X-Bus (nCS3)
0x20000000 - 0x2ffffff	N	N	PCMCIA slot 0 - LAN91C96 Ethernet
0x50000000 - 0x507ffffff	Y	Y	8Mb flash (nCS0)
0x80000000 - 0xbffffff	N	N	SA-1110 Internal Registers
0xc0000000 - 0xc0ffffff	N	Y	DRAM Bank 0:8 or 16Mb
0xc8000000 - 0xc8ffffff	N	Y	DRAM Bank 1:8 or 16Mb or absent
0xe0000000 - 0xe7ffffff	Y	Y	Cache Clean

SDRAM can be any of

1 x 8Mb = 8Mb    2 x 8Mb = 16Mb  
1 x 16Mb = 16Mb    2 x 16Mb = 32Mb

All are programmed the same way in the memory controller. Startup code detects which is fitted and programs the memory map accordingly. If the device(s) is 8Mb, then there are gaps in the physical memory map, because a high order address bit is not connected. The gaps are the higher 2Mb out of every 4Mb.

The SA11x0 OS timer is used as a polled timer to provide timeout support within RedBoot.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=plc2  
export ARCH_DIR=arm  
export PLATFORM_DIR=sa11x0/plc2
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA1110) Intel SA1110 (Assabet)

## Overview

RedBoot supports the board serial port and the compact flash ethernet port. The default serial port settings are 38400,8,N,1. RedBoot also supports flash management on the Assabet.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

A Windows or Linux utility is used to program flash over parallel port driven JTAG interface. See board documentation for details on in situ flash programming.

The flash parts are also socketed and may be programmed in a suitable device programmer.

## Special RedBoot Commands

None.

## Memory Maps

The first level page table is located at physical address 0xc0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range			Description
-----			-----
0x00000000 - 0x07ffffff			flash
0x08000000 - 0x0fffffff			SA-1111 Board flash
0x10000000 - 0x17ffffff			Board Registers
0x18000000 - 0x1fffffff			Ethernet
0x20000000 - 0x2fffffff			SA-1111 Board PCMCIA
0x30000000 - 0x3fffffff			Compact Flash
0x40000000 - 0x47ffffff			SA-1111 Board
0x48000000 - 0x4bffffff			GFX
0x80000000 - 0xbfffffff			SA-1110 Internal Registers
0xc0000000 - 0xc7ffffff			DRAM Bank 0
0xc8000000 - 0xcfffffff			DRAM Bank 1
0xd0000000 - 0xd7ffffff			DRAM Bank 2
0xd8000000 - 0xdfffffff			DRAM Bank 3
0xe0000000 - 0xe7ffffff			Cache Clean

  

Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x01ffffff	Y	Y	DRAM Bank 0

```
0x08000000 - 0x0fffffff Y Y SA-1111 Board flash
0x10000000 - 0x17fffffff N N Board Registers
0x18000000 - 0x1fffffff N N Ethernet
0x20000000 - 0x2fffffff N N SA-1111 Board PCMCIA
0x30000000 - 0x3fffffff N N Compact Flash
0x40000000 - 0x47fffffff N N SA-1111 Board
0x48000000 - 0x4bfffffff N N GFX
0x50000000 - 0x57fffffff Y Y flash
0x80000000 - 0xbfffffff N N SA-1110 Internal Registers
0xc0000000 - 0xc1fffffff N Y DRAM Bank 0
0xe0000000 - 0xe7fffffff Y Y Cache Clean
```

## Platform Resource Usage

The SA11x0 OS timer is used as a polled timer to provide timeout support for network and XModem file transfers.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=assabet
export ARCH_DIR=arm
export PLATFORM_DIR=s11x0/assabet
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA11X0) Bright Star Engineering commEngine and nanoEngine

## Overview

RedBoot supports a serial port and the built in ethernet port for communication and downloads. The default serial port settings are 38400,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
POST	[ROM]	RedBoot running from the first free flash block at 0x40000.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation

Unlike other targets, the nanoEngine comes equipped with boot firmware which you cannot modify. See chapter 5, "nanoEngine Firmware" of the *nanoEngine Hardware Reference Manual* (we refer to "July 17, 2000 Rev 0.6") from Bright Star Engineering.

Because of this, eCos, and therefore Redboot, only supports a special configuration of the ROM mode, starting at offset 0x40000 in the flash.

Briefly, the POST-configuration RedBoot image lives in flash following the BSE firmware. The BSE firmware is configured, using its standard **bootcmd** command, to run RedBoot at startup.

## Download Instructions

You can perform the initial load of the POST-configuration RedBoot image into flash using the BSE firmware's **load** command. This will load a binary file, using TFTP, and program it into flash in one operation. Because no memory management is used in the BSE firmware, flash is mapped from address zero upwards, so the address for the RedBoot POST image is 0x40000. You must use the binary version of RedBoot for this, `redboot-post.bin`.

This assumes you have set up the other BSE firmware config parameters such that it can communicate over your network to your TFTP server.

```
>load redboot-post.bin 40000
loading ... erasing blk at 00040000
erasing blk at 00050000
94168 bytes loaded cksum 00008579
done
>
> set bootcmd "go 40000"
```

```
> get
myip = 10.16.19.198
netmask = 255.255.255.0
eth = 0
gateway = 10.16.19.66
serverip = 10.16.19.66
bootcmd = go 40000
>
```

**NOTE:** the BSE firmware runs its serial IO at 9600 Baud; RedBoot runs instead at 38400 Baud. You must select the right baud rate in your terminal program to be able to set up the BSE firmware.

After a reset, the BSE firmware will print

```
Boot: BSE 2000 Sep 12 2000 14:00:30
autoboot: "go 40000" [hit ESC to abort]
```

and then RedBoot starts, switching to 38400 Baud.

Once you have installed a bootable RedBoot in the system in this manner, we advise re-installing using the generic method described in Chapter 4 in order that the Flash Image System contains an appropriate description of the flash entries.

## Cohabiting with POST in Flash

The configuration file named `redboot_POST.ecm` configures RedBoot to build for execution at address `0x50040000` (or, during bootup, `0x00040000`). This is to allow power-on self-test (POST) code or immutable firmware to live in the lower addresses of the flash and to run before RedBoot gets control. The assumption is that RedBoot will be entered at its base address in physical memory, that is `0x00040000`.

Alternatively, for testing, you can call it in an already running system by using **go 0x50040040** at another RedBoot prompt, or a branch to that address. The address is where the reset vector points. It is reported by RedBoot's **load** command and listed by the **fis list** command, amongst other places.

Using the POST configuration enables a normal config option which causes linking and initialization against memory layout files called "...post..." rather than "...rom..." or "...ram..." in the `include/pkgconf` directory. Specifically:

```
include/pkgconf/mlt_arm_s11x0_nano_post.h
include/pkgconf/mlt_arm_s11x0_nano_post.ldi
include/pkgconf/mlt_arm_s11x0_nano_post.mlt
```

It is these you should edit if you wish to move the execution address from 0x50040000 in the POST configuration. Startup mode naturally remains ROM in this configuration.

Because the nanoEngine contains immutable boot firmware at the start of flash, RedBoot for this target is configured to reserve that area in the Flash Image System, and to create by default an entry for the POST mode RedBoot.

```
RedBoot> fis list
Name                FLASH addr  Mem addr    Length     Entry point
(reserved)          0x50000000 0x50000000 0x00040000 0x00000000
RedBoot[post]      0x50040000 0x00100000 0x00020000 0x50040040
RedBoot config     0x503E0000 0x503E0000 0x00010000 0x00000000
FIS directory      0x503F0000 0x503F0000 0x00010000 0x00000000
RedBoot>
```

The entry "(reserved)" ensures that the FIS cannot attempt to overwrite the BSE firmware, thus ensuring that the board remains bootable and recoverable even after installing a broken RedBoot image.

## Special RedBoot Commands

The nanoEngine/commEngine has one or two Intel i82559 Ethernet controllers installed, but these have no associated serial EEPROM in which to record their Ethernet Station Address (ESA, or MAC address). The BSE firmware records an ESA for the device it uses, but this information is not available to RedBoot; we cannot share it.

To keep the ESAs for the two ethernet interfaces, two new items of RedBoot configuration data are introduced. You can list them with the RedBoot command **fconfig -l** thus:

```
RedBoot> fconfig -l
Run script at boot: false
Use BOOTP for network configuration: false
Local IP address: 10.16.19.91
Default server IP address: 10.16.19.66
Network hardware address [MAC] for eth0: 0x00:0xB5:0xE0:0xB5:0xE0:0x99
Network hardware address [MAC] for eth1: 0x00:0xB5:0xE0:0xB5:0xE0:0x9A
GDB connection port: 9000
Network debug at boot time: false
RedBoot>
```

You should set them before running RedBoot or eCos applications with the board connected to a network. The **fconfig** command can be used as for any configuration data item; the entire ESA is entered in one line.

## Memory Maps

The first level page table is located at physical address 0xc0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range			Description
0x00000000 - 0x003ffffff			4Mb FLASH (nCS0)
0x18000000 - 0x18ffffff			Internal PCI bus - 2 x i82559 ethernet
0x40000000 - 0x4ffffff			External IO or PCI bus
0x80000000 - 0xbffffff			SA-1110 Internal Registers
0xc0000000 - 0xc7ffffff			DRAM Bank 0 - 32Mb SDRAM
0xc8000000 - 0xcffffff			DRAM Bank 1 - empty
0xe0000000 - 0xe7ffffff			Cache Clean

  

Virtual Address Range	C	B	Description
0x00000000 - 0x001ffffff	Y	Y	DRAM - 8Mb to 32Mb
0x18000000 - 0x180ffff	N	N	Internal PCI bus - 2 x i82559 ethernet
0x40000000 - 0x4ffffff	N	N	External IO or PCI bus
0x50000000 - 0x51ffffff	Y	Y	Up to 32Mb FLASH (nCS0)
0x80000000 - 0xbffffff	N	N	SA-1110 Internal Registers
0xc0000000 - 0xc0ffffff	N	Y	DRAM Bank 0: 8 or 16Mb
0xc8000000 - 0xc8ffffff	N	Y	DRAM Bank 1: 8 or 16Mb or absent
0xe0000000 - 0xe7ffffff	Y	Y	Cache Clean

The ethernet devices use a "PCI window" to communicate with the CPU. This is 1Mb of SDRAM which is shared with the ethernet devices that are on the PCI bus. It is neither cached nor buffered, to ensure that CPU and PCI accesses see correct data in the correct order. By default it is configured to be megabyte number 30, at addresses 0x01e00000-0x01efffff. This can be modified, and indeed must be, if less than 32Mb of SDRAM is installed, via the memory layout tool, or by moving the section `__pci_window` referred to by symbols `CYGMEM_SECTION_pci_window*` in the linker script.

Though the nanoEngine ships with 32Mb of SDRAM all attached to DRAM bank 0, the code can cope with any of these combinations also; "2 x " in this context means one device in each DRAM Bank.

1 x 8Mb = 8Mb    2 x 8Mb = 16Mb  
 1 x 16Mb = 16Mb    2 x 16Mb = 32Mb

All are programmed the same in the memory controller.

Startup code detects which is fitted and programs the memory map accordingly. If the device(s) is 8Mb, then there are gaps in the physical memory map, because a high order address bit is not connected. The gaps are the higher 2Mb out of every 4Mb.

The SA11x0 OS timer is used as a polled timer to provide timeout support within RedBoot.

## Nano Platform Port

The nano is in the set of SA11X0-based platforms. It uses the arm architectural HAL, the sa11x0 variant HAL, plus the nano platform hal. These are components

```
CYGPKG_HAL_ARM          hal/arm/arch/  
CYGPKG_HAL_ARM_SA11X0  hal/arm/sa11x0/var  
CYGPKG_HAL_ARM_SA11X0_NANO  hal/arm/sa11x0/nano
```

respectively.

The target name is "nano" which includes all these, plus the ethernet driver packages, flash driver, and so on.

## Ethernet Driver

The ethernet driver is in two parts:

A generic ether driver for Intel i8255x series devices, specifically the i82559, is `devs/eth/intel/i82559`. Its package name is `CYGPKG_DEVS_ETH_INTEL_I82559`.

The platform-specific ether driver is `devs/eth/arm/nano`. Its package is `CYGPKG_DEVS_ETH_ARM_NANO`. This tells the generic driver the address in IO memory of the chip, for example, and other configuration details. This driver picks up the ESA from RedBoot's configuration data - unless configured to use a static ESA in the usual manner.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=nano  
export ARCH_DIR=arm  
export PLATFORM_DIR=sal1x0/nano
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA11X0) Compaq iPAQ PocketPC

## Overview

RedBoot supports the serial port via cradle or cable, and Compact Flash ethernet cards if fitted for communication and downloads. The LCD touchscreen may also be used for the console, although by default RedBoot will switch exclusively to one channel once input arrives.

The default serial port settings are 38400,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
WinCE	[RAM]	RedBoot running from RAM, started from OSloader.	redboot_WinCE.ecm

## Initial Installation

RedBoot ROM and WinCE mode images are needed by the installation process.

### Installing RedBoot on the iPAQ using Windows/CE

The Windows/CE environment originally shipped with the iPAQ contains a hidden mini-loader, sometimes referred to as the "Parrot" loader. This loader can be started by holding down the action button (the joypad) while resetting the unit or when powering on. At this point, a blue bird will appear on the LCD screen. Also at this point, a simple loader can be accessed over the serial port at 115200/8N1. Using this loader, the contents of the iPAQ flash memory can be saved to a Compact Flash memory card.

**NOTE:** We have only tested this operation with a 32Mbyte CF memory card. Given that the backup will take 16MBytes + 1KByte, something more than a 16MByte card will be required.

Use the "r2c" command to dump Flash contents to the CF memory card. Once this completes, RedBoot can be installed with no fear since the Parrot loader can be used to restore the Flash contents at a later time.

If you expect to completely recover the state of the iPAQ Win/CE environment, then HotSync should be run to backup all "RAM" files as well before installing RedBoot.

The next step in installing RedBoot on the iPAQ actually involves Windows/CE, which is the native environment on the unit. Using WinCE, you need to install an application which will run a RAM based version of RedBoot. Once this is installed and running, RedBoot can be used to update the flash with a native/ROM version of RedBoot.

- Using ActiveSync, copy the file OSloader to your iPAQ.
- Using ActiveSync, copy the file redboot\_WinCE.bin to the iPAQ as bootldr in its root directory. Note: this is not the top level folder displayed by Windows (Mobile Device), but rather the 'My Pocket PC' folder within it.
- Execute OSloader. If you didn't create a shortcut, then you will have to poke around for it using the WinCE file explorer.
- Choose the Tools->BootLdr->Run after loading from file menu item.

At this point, the RAM based version of RedBoot should be running. You should be able to return to this point by just executing the last two steps of the previous process if necessary.

## **Installing RedBoot on the iPAQ - using the Compaq boot loader**

This method of installation is no longer supported. If you have previously installed either the Compaq boot loader or older versions of RedBoot, restore the Win/CE environment and proceed as outlined above.

## **Setting up and testing RedBoot**

When RedBoot first comes up, it will want to initialize its LCD touch screen parameters. It does this by displaying a keyboard graphic and asks you to press certain keys. Using the stylus, press and hold until the prompt is withdrawn. When you lift the stylus, RedBoot will continue with the next calibration.

Once the LCD touchscreen has been calibrated, RedBoot will start. The calibration step can be skipped by pressing the return/abort button on the unit (right most button with a curved arrow icon). Additionally, the unit will assume default values if the screen is not touched within about 15 seconds.

Once RedBoot has started, you should get information similar to this on the LCD screen. It will also appear on the serial port at 38400,8,N,1.

```
RedBoot(tm) bootstrap and debug environment [ROM]
Non-certified release, version UNKNOWN - built 06:17:41, Mar 19 2001
Platform: Compaq iPAQ Pocket PC (StrongARM 1110)
```

```
Copyright (C) 2000, 2001, Red Hat, Inc.
```

```
RAM: 0x00000000-0x01fc0000, 0x0001f200-0x01f70000 available
FLASH: 0x50000000 - 0x51000000, 64 blocks of 0x00040000 bytes
each.
```

Since the LCD touchscreen is only 30 characters wide, some of this data will be off the right hand side of the display. The joystick may be used to pan left and right in order to see the full lines.

If you have a Compact Flash ethernet card, RedBoot should find it. You'll need to have BOOTP enabled for this unit (see your sysadmin for details). If it does, it will print a message like:

```
... Waiting for network card: .Ready!
Socket Communications Inc: CF+ LPE Revision E 08/04/99
IP: 192.168.1.34, Default server: 192.168.1.101
```

## Installing RedBoot permanently

Once you are satisfied with the setup and that RedBoot is operating properly in your environment, you can set up your iPAQ unit to have RedBoot be the bootstrap application.

### CAUTION

This step will destroy your Windows/CE environment.

Before you take this step, it is strongly recommended you save your WinCE FLASH contents as outlined above using the "parrot" loader, or by using the Compaq OSloader:

- Using OSloader on the iPAQ, select the Tools->Flash->Save to files.... menu item.
- Four (4) files, 4MB each in size will be created.
- After each file is created, copy the file to your computer, then delete the file from the iPAQ to make room in the WinCE ramdisk for the next file.

You will need to download the version of RedBoot designed as the ROM bootstrap. Then install it permanently using these commands:

```
RedBoot> lo -r -b 0x100000 redboot_ROM.bin
RedBoot> fi loc -f 0x50000000 -l 0x40000
RedBoot> fis init
RedBoot> fi unl -f 0x50040000 -l 0x40000
RedBoot> fi cr RedBoot -b 0x100000
RedBoot> fi loc -f 0x50040000 -l 0x40000
RedBoot> reset
```

## WARNING

You must type these commands exactly! Failure to do so may render your iPAQ totally useless. Once you've done this, RedBoot should come up every time you reset.

## Restoring Windows/CE

To restore Windows/CE from the backup taken in the Section called *Installing RedBoot permanently*, visit <http://www.handhelds.org/projects/wincerestoration.html> for directions.

## Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the iPAQ are:

**-b** <addr>

Location Linux kernel was loaded to

**-l** <len>

Length of kernel

**-c** "params"

Parameters passed to kernel

**-r** <addr>

'initrd' ramdisk location

`-s <len>`

Length of initrd ramdisk

Linux kernels may be run on the iPAQ using the sources from the anonymous CVS repository at the Handhelds project (<http://www.handhelds.org/>) with the `elinux.patch` patch file applied. This file can be found in the `misc/` subdirectory of the iPAQ platform HAL in the RedBoot sources, normally `hal/arm/sa11x0/ipaq/VERSION/misc/`

On the iPAQ (and indeed all SA11x0 platforms), Linux expects to be loaded at address `0xC0008000` and the entry point is also at `0xC0008000`.

## Memory Maps

RedBoot sets up the following memory map on the iPAQ: The first level page table is located at physical address `0xC0004000`. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
0x00000000 - 0x01ffffff	16Mb to 32Mb FLASH (nCS0) [organized as below]
0x00000000 - 0x0003ffff	Parrot Loader
0x00400000 - 0x0007ffff	RedBoot
0xf8000000 - 0x00fbffff	Fconfig data
0xfc000000 - 0x00ffffff	FIS directory
0x30000000 - 0x3fffffff	Compact Flash
0x48000000 - 0x4bffffff	iPAQ internal registers
0x80000000 - 0xbfffffff	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	DRAM Bank 0 - 32Mb SDRAM
0xe0000000 - 0xe7ffffff	Cache Clean

Virtual Address Range	C	B	Description
0x00000000 - 0x01ffffff	Y	Y	DRAM - 32Mb
0x30000000 - 0x3fffffff	N	N	Compact Flash
0x48000000 - 0x4bffffff	N	N	iPAQ internal registers
0x50000000 - 0x51ffffff	Y	Y	Up to 32Mb FLASH (nCS0)
0x80000000 - 0xbfffffff	N	N	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	N	Y	DRAM Bank 0: 32Mb
0xe0000000 - 0xe7ffffff	Y	Y	Cache Clean

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=ipaq
export ARCH_DIR=arm
export PLATFORM_DIR=s11x0/ipaq
```

The names of configuration files are listed above with the description of the associated modes.

## ARM/StrongARM(SA11X0) Intrinsyc CerfCube

### Overview

RedBoot supports the serial port and the builtin ethernet connection for communication and downloads.

The default serial port settings are 38400,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation

The original boot loader supplied with the CerfCube can be used to install RedBoot. Connect to the device using a serial port at 38400/8N1. Copy the binary RedBoot ROM mode image to an

available TFTP server. Issue these commands to the Intrinsic loader:

```
download tftp:x.x.x.x redboot_ROM.bin 0xc0000000
flashloader 0x00000000 0xc0000000 0x20000
```

where *x.x.x.x* is the IP address of the TFTP server.

**NOTE:** Other installation methods may be available via the Intrinsic loader. Contact Intrinsic for details.

## Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the CerfCube are:

-b *<addr>*

Location Linux kernel was loaded to

-l *<len>*

Length of kernel

-c "*params*"

Parameters passed to kernel

-r *<addr>*

'initrd' ramdisk location

-s *<len>*

Length of initrd ramdisk

## Memory Maps

RedBoot sets up the following memory map on the CerfCube: The first level page table is located at physical address 0xC0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
-----	-----
0x00000000 - 0x01ffffff	16Mb to 32Mb FLASH (nCS0) [organized as below]
0x00000000 - 0x0001ffff	RedBoot
0x02000000 - 0x0003ffff	RedBoot [RAM version]
0xfc000000 - 0x00fdffff	Fconfig data
0xfe000000 - 0x00ffffff	FIS directory
0x0f000000 - 0x0ffffff	Onboard ethernet
0x10000000 - 0x17ffffff	CerfCube internal registers
0x20000000 - 0x3ffffff	PCMCIA / Compact Flash
0x80000000 - 0xbffffff	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	DRAM Bank 0 - 32Mb SDRAM
0xe0000000 - 0xe7ffffff	Cache Clean

Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x01ffffff	Y	Y	DRAM - 32Mb
0x08000000 - 0x0ffffff	N	N	Onboard ethernet controller
0x10000000 - 0x17ffffff	N	N	CerfCube internal registers
0x20000000 - 0x3ffffff	N	N	PCMCIA / Compact Flash
0x50000000 - 0x51ffffff	Y	Y	Up to 32Mb FLASH (nCS0)
0x80000000 - 0xbffffff	N	N	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	N	Y	DRAM Bank 0: 32Mb
0xe0000000 - 0xe7ffffff	Y	Y	Cache Clean

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=cerf
export ARCH_DIR=arm
export PLATFORM_DIR=sallx0/cerf
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/StrongARM(SA11X0) Symbol PPT2800 Series Portable Pen Terminal

## Overview

RedBoot supports the serial port via cradle or cable. The LCD will display a splash screen, but cannot be used for the console.

The default serial port settings are 115200,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
SymbolIPL	[SymbolIPL]	RedBoot running from the board's flash, as a secondary boot monitor, started by the IPL.	redboot_SymbolIPL.ecm

## Initial Installation

The SymbolIPL mode RedBoot SHEX image (`redboot_SymbolIPL.shex`) is downloaded as a normal operating system image, to reside in the 'OS partition' of the system flash and be started by the IPL. The ROM mode RedBoot will replace the IPL in the system flash boot sector.

## Installing RedBoot on the PPT2800 using the IPL

The Windows/CE environment originally shipped with the PPT2800 contains a hidden mini-loader, referred to as the "IPL". This loader can be started by holding down the App1 and App4 buttons while resetting the unit or when powering on. At this point, a menu will appear on the LCD screen. To replace the IPL with RedBoot select a baud rate, then select 'IPL' as the

partition to download. Then send the ROM mode RedBoot SHEX image (`redboot_ROM.shex`) to the serial port of the device. A progress meter should be displayed on the LCD, followed by instructions to perform a hard reset. Do this, and RedBoot should start.

Once RedBoot has started, you should see a splash screen appear on the LCD and on the serial port.

## Restoring the IPL

### WARNING

After restoring the IPL from its original Symbol HEX file, it is extremely important to ensure that the entire flash device is unprotected. RedBoot locks the flash chips to guard against accidental erasure or modification, but the IPL cannot unlock them. This can lead to a non-functional unit.

To replace RedBoot with the IPL, first load the IPL image into RAM with the following command:

```
RedBoot> load -b %{FREEMEMLO} -m ymodem
```

Send the `ipl.hex` file and then program it into flash using the **fis write** command:

```
RedBoot> fis write -b %{FREEMEMLO} -f 0x50000000 -l 0x80000
```

Next, ensure the system flash is entirely unprotected:

```
RedBoot> fis unlock -f 0x50000000 -l 0x02000000
```

After this command completes, it is safe to reset the unit using the **reset** command or a hard reset.

## Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the Symbol PPT2800 are:

`-b <addr>`

Location Linux kernel was loaded to

- l <len>  
Length of kernel
- c "params"  
Parameters passed to kernel
- r <addr>  
'initrd' ramdisk location
- s <len>  
Length of initrd ramdisk

Linux kernels for the Symbol PPT2800 differ from normal ARM kernels in that they are configured to decompress directly from flash. Rather than loading the zImage into RAM and then executing it, RedBoot executes it directly from the flash. It is normal to place the Linux kernel zImage in flash at virtual address 0x50080000, and to pass the corresponding physical address 0x80000 to the RedBoot **exec** command, as follows:

```
RedBoot> exec -c "console=ttysA0,115200 root=/dev/mtdblock3" 0x80000
Using base address 0x00000000 and length 0x00000000
Uncompressing Linux..... done, booting the
```

## Memory Maps

RedBoot sets up the following memory map on the PPT2800: The first level page table is located at physical address 0xC0004000. No second level tables are used.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
0x00000000 - 0x01ffffff	32MB FLASH (nCS0) [organized as below]
0x000000 - 0x0003ffff	RedBoot
0x1f8000 - 0x01fbffff	Fconfig data
0x1fc000 - 0x01ffffff	FIS directory
0x1000000 - 0x10ffffff	PPT2800 EGPIO register
0x80000000 - 0xbfffffff	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	DRAM Bank 0 - 32MB SDRAM
0xe0000000 - 0xe7ffffff	Cache Clean

Virtual Address Range	C	B	Description
0x00000000 - 0x01ffffff	Y	Y	DRAM - 32MB
0x10000000 - 0x10ffffff	N	N	PPT2800 EGPIO register
0x50000000 - 0x51ffffff	Y	Y	32MB FLASH (nCS0)
0x80000000 - 0xbfffffff	N	N	SA-1110 Internal Registers
0xc0000000 - 0xc1ffffff	N	Y	DRAM Bank 0: 32MB
0xe0000000 - 0xe7ffffff	Y	Y	Cache Clean

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=symbol2800
export ARCH_DIR=arm
export PLATFORM_DIR=sal1x0/symbol2800
```

The names of configuration files are listed above with the description of the associated modes.

# ARM/Xscale Cyclone IQ80310

## Overview

RedBoot supports both serial ports and the built-in ethernet port for communication and downloads. The default serial port settings are 115200,8,N,1. RedBoot also supports flash management for the onboard 8MB flash.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm

Configuration	Mode	Description	File
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
ROMA	[ROM]	RedBoot running from flash address 0x40000, with ARM bootloader in flash boot sector.	redboot_ROMA.ecm
RAMA	[RAM]	RedBoot running from RAM with ARM bootloader in flash boot sector.	redboot_RAMA.ecm

## Initial Installation Method

The board manufacturer provides a DOS application which is capable of programming the flash over the PCI bus, and this is required for initial installations of RedBoot. Please see the board manual for information on using this utility. In general, the process involves programming one of the two flash based RedBoot images to flash. The ROM mode RedBoot (which runs from the flash boot sector) should be programmed to flash address 0x00000000. The ROMA RedBoot mode (which is started by the ARM bootloader) should be programmed to flash address 0x00004000.

To install RedBoot to run from the flash boot sector, use the manufacturer's flash utility to install the ROM mode image at address zero.

To install RedBoot to run from address 0x40000 with the ARM bootloader in the flash boot sector, use the manufacturer's flash utility to install the ROMA mode image at address 0x40000.

After booting the initial installation of RedBoot, this warning may be printed:

```
flash configuration checksum error or invalid key
```

This is normal, and indicates that the flash must be configured for use by RedBoot. Even if the above message is not printed, it may be a good idea to reinitialize the flash anyway. Do this with the **fis** command:

```
RedBoot> fis init
About to initialize [format] flash image system - continue (y/n)? y
*** Initialize flash Image System
Warning: device contents not erased, some blocks may not be usable
... Unlock from 0x007e0000-0x00800000: .
```

```
... Erase from 0x007e0000-0x00800000: .
... Program from 0x1afd0000-0x1afd0400 at 0x007e0000: .
... Lock from 0x007e0000-0x00800000: .
Followed by the fconfig command:
RedBoot> fconfig
Run script at boot: false
Use BOOTP for network configuration: false
Local IP address: 192.168.1.153
Default server IP address: 192.168.1.10
GDB connection port: 1000
Network debug at boot time: false
Update RedBoot non-volatile configuration - continue (y/n)? y
... Unlock from 0x007c0000-0x007e0000: .
... Erase from 0x007c0000-0x007e0000: .
... Program from 0xa0013018-0xa0013418 at 0x007c0000: .
... Lock from 0x007c0000-0x007e0000: .
```

**Note:** When later updating RedBoot in situ, it is important to use a matching ROM and RAM mode pair of images. So use either RAM/ROM or RAMA/ROMA images. Do not mix them.

## Error codes

RedBoot uses the two digit LED display to indicate errors during board initialization. Possible error codes are:

88 - Unknown Error  
55 - I2C Error  
FF - SDRAM Error  
01 - No Error

## Using RedBoot with ARM Bootloader

RedBoot can coexist with ARM tools in flash on the IQ80310 board. In this configuration, the ARM bootloader will occupy the flash boot sector while RedBoot is located at flash address 0x40000. The sixteen position rotary switch is used to tell the ARM bootloader to jump to the RedBoot image located at address 0x40000. RedBoot is selected by switch position 0 or 1. Other switch positions are used by the ARM firmware and RedBoot will not be started.

## Special RedBoot Commands

A special RedBoot command, **diag**, is used to access a set of hardware diagnostics provided by the board manufacturer. To access the diagnostic menu, enter **diag** at the RedBoot prompt:

```
RedBoot> diag
Entering Hardware Diagnostics - Disabling Data Cache!
1 - Memory Tests
2 - Repeating Memory Tests
3 - 16C552 DUART Serial Port Tests
4 - Rotary Switch S1 Test for positions 0-3
5 - seven Segment LED Tests
6 - Backplane Detection Test
7 - Battery Status Test
8 - External Timer Test
9 - i82559 Ethernet Configuration
10 - i82559 Ethernet Test
11 - Secondary PCI Bus Test
12 - Primary PCI Bus Test
13 - i960Rx/303 PCI Interrupt Test
14 - Internal Timer Test
15 - GPIO Test
0 - quit Enter the menu item number (0 to quit):
```

Tests for various hardware subsystems are provided, and some tests require special hardware in order to execute normally. The Ethernet Configuration item may be used to set the board ethernet address.

## IQ80310 Hardware Tests

```
1 - Memory Tests
2 - Repeating Memory Tests
3 - 16C552 DUART Serial Port Tests
4 - Rotary Switch S1 Test for positions 0-3
5 - 7 Segment LED Tests
6 - Backplane Detection Test
7 - Battery Status Test
8 - External Timer Test
9 - i82559 Ethernet Configuration
10 - i82559 Ethernet Test
11 - i960Rx/303 PCI Interrupt Test
12 - Internal Timer Test
13 - Secondary PCI Bus Test
14 - Primary PCI Bus Test
15 - Battery Backup SDRAM Memory Test
16 - GPIO Test
```

```
17 - Repeat-On-Fail Memory Test
18 - Coyonosa Cache Loop (No return)
19 - Show Software and Hardware Revision
0 - quit
Enter the menu item number (0 to quit):
```

Tests for various hardware subsystems are provided, and some tests require special hardware in order to execute normally. The Ethernet Configuration item may be used to set the board ethernet address.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=iq80310
export ARCH_DIR=arm
export PLATFORM_DIR=iq80310
```

The names of configuration files are listed above with the description of the associated modes.

## Interrupts

RedBoot uses an interrupt vector table which is located at address 0xA000A004. Entries in this table are pointers to functions with this prototype::

```
int irq_handler( unsigned vector, unsigned data )
```

On an IQ80310 board, the vector argument is one of 49 interrupts defined in `hal/arm/iq80310/current/include/hal_platform_ints.h::`

```
// *** 80200 CPU ***
#define CYGNUM_HAL_INTERRUPT_reserved0      0
#define CYGNUM_HAL_INTERRUPT_PMU_PMN0_OVFL 1 // See Ch.12 - Performance Mon.
#define CYGNUM_HAL_INTERRUPT_PMU_PMN1_OVFL 2 // PMU counter 0/1 overflow
#define CYGNUM_HAL_INTERRUPT_PMU_CCNT_OVFL 3 // PMU clock overflow
#define CYGNUM_HAL_INTERRUPT_BCU_INTERRUPT 4 // See Ch.11 - Bus Control Unit
#define CYGNUM_HAL_INTERRUPT_NIRQ          5 // external IRQ
#define CYGNUM_HAL_INTERRUPT_NFIQ         6 // external FIQ

// *** XINT6 interrupts ***
```

## Chapter 5. Installation and Testing

```
#define CYGNUM_HAL_INTERRUPT_DMA_0          7
#define CYGNUM_HAL_INTERRUPT_DMA_1          8
#define CYGNUM_HAL_INTERRUPT_DMA_2          9
#define CYGNUM_HAL_INTERRUPT_GTSC          10 // Global Time Stamp Counter
#define CYGNUM_HAL_INTERRUPT_PEC          11 // Performance Event Counter
#define CYGNUM_HAL_INTERRUPT_AAIP          12 // application accelerator unit

// *** XINT7 interrupts ***
// I2C interrupts
#define CYGNUM_HAL_INTERRUPT_I2C_TX_EMPTY  13
#define CYGNUM_HAL_INTERRUPT_I2C_RX_FULL   14
#define CYGNUM_HAL_INTERRUPT_I2C_BUS_ERR   15
#define CYGNUM_HAL_INTERRUPT_I2C_STOP      16
#define CYGNUM_HAL_INTERRUPT_I2C_LOSS      17
#define CYGNUM_HAL_INTERRUPT_I2C_ADDRESS   18

// Messaging Unit interrupts
#define CYGNUM_HAL_INTERRUPT_MESSAGE_0     19
#define CYGNUM_HAL_INTERRUPT_MESSAGE_1     20
#define CYGNUM_HAL_INTERRUPT_DOORBELL      21
#define CYGNUM_HAL_INTERRUPT_NMI_DOORBELL  22
#define CYGNUM_HAL_INTERRUPT_QUEUE_POST    23
#define CYGNUM_HAL_INTERRUPT_OUTBOUND_QUEUE_FULL 24
#define CYGNUM_HAL_INTERRUPT_INDEX_REGISTER 25
// PCI Address Translation Unit
#define CYGNUM_HAL_INTERRUPT_BIST           26

// *** External board interrupts (XINT3) ***
#define CYGNUM_HAL_INTERRUPT_TIMER          27 // external timer
#define CYGNUM_HAL_INTERRUPT_ETHERNET      28 // onboard enet
#define CYGNUM_HAL_INTERRUPT_SERIAL_A      29 // 16x50 uart A
#define CYGNUM_HAL_INTERRUPT_SERIAL_B      30 // 16x50 uart B
#define CYGNUM_HAL_INTERRUPT_PCI_S_INTD    31 // secondary PCI INTD
// The hardware doesn't (yet?) provide masking or status for these
// even though they can trigger cpu interrupts. ISRs will need to
// poll the device to see if the device actually triggered the
// interrupt.
#define CYGNUM_HAL_INTERRUPT_PCI_S_INTC    32 // secondary PCI INTC
#define CYGNUM_HAL_INTERRUPT_PCI_S_INTB    33 // secondary PCI INTB
#define CYGNUM_HAL_INTERRUPT_PCI_S_INTA    34 // secondary PCI INTA

// *** NMI Interrupts go to FIQ ***
#define CYGNUM_HAL_INTERRUPT_MCU_ERR       35
#define CYGNUM_HAL_INTERRUPT_PATU_ERR      36
```

```

#define CYGNUM_HAL_INTERRUPT_SATU_ERR      37
#define CYGNUM_HAL_INTERRUPT_PBDG_ERR     38
#define CYGNUM_HAL_INTERRUPT_SBDG_ERR     39
#define CYGNUM_HAL_INTERRUPT_DMA0_ERR     40
#define CYGNUM_HAL_INTERRUPT_DMA1_ERR     41
#define CYGNUM_HAL_INTERRUPT_DMA2_ERR     42
#define CYGNUM_HAL_INTERRUPT_MU_ERR       43
#define CYGNUM_HAL_INTERRUPT_reserved52   44
#define CYGNUM_HAL_INTERRUPT_AAU_ERR      45
#define CYGNUM_HAL_INTERRUPT_BIU_ERR      46

// *** ATU FIQ sources ***
#define CYGNUM_HAL_INTERRUPT_P_SERR       47
#define CYGNUM_HAL_INTERRUPT_S_SERR       48

```

The data passed to the ISR is pulled from a data table (`hal_interrupt_data`) which immediately follows the interrupt vector table. With 49 interrupts, the data table starts at address `0xA000A0C8`.

An application may create a normal C function with the above prototype to be an ISR. Just poke its address into the table at the correct index and enable the interrupt at its source. The return value of the ISR is ignored by RedBoot.

## Memory Maps

The first level page table is located at `0xa0004000`. Two second level tables are also used. One second level table is located at `0xa0008000` and maps the first 1MB of flash. The other second level table is at `0xa0008400`, and maps the first 1MB of SDRAM.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	Description
-----	-----
0x00000000 - 0x00000fff	flash Memory
0x00001000 - 0x00001fff	80312 Internal Registers
0x00002000 - 0x007fffff	flash Memory
0x00800000 - 0x7fffffff	PCI ATU Outbound Direct Window
0x80000000 - 0x83ffffff	Primary PCI 32-bit Memory
0x84000000 - 0x87ffffff	Primary PCI 64-bit Memory
0x88000000 - 0x8bffffff	Secondary PCI 32-bit Memory

## Chapter 5. Installation and Testing

0x8c000000 - 0x8fffffff	Secondary PCI 64-bit Memory
0x90000000 - 0x9000ffff	Primary PCI IO Space
0x90010000 - 0x9001ffff	Secondary PCI IO Space
0x90020000 - 0x9fffffff	Unused
0xa0000000 - 0xbfffffff	SDRAM
0xc0000000 - 0xefffffff	Unused
0xf0000000 - 0xffffffff	80200 Internal Registers

Virtual Address Range	C	B	Description
-----	-	-	-----
0x00000000 - 0x00000fff	Y	Y	SDRAM
0x00001000 - 0x00001fff	N	N	80312 Internal Registers
0x00002000 - 0x007fffff	Y	N	flash Memory
0x00800000 - 0x7fffffff	N	N	PCI ATU Outbound Direct Window
0x80000000 - 0x83fffffff	N	N	Primary PCI 32-bit Memory
0x84000000 - 0x87fffffff	N	N	Primary PCI 64-bit Memory
0x88000000 - 0x8bfffffff	N	N	Secondary PCI 32-bit Memory
0x8c000000 - 0x8fffffff	N	N	Secondary PCI 64-bit Memory
0x90000000 - 0x9000ffff	N	N	Primary PCI IO Space
0x90010000 - 0x9001ffff	N	N	Secondary PCI IO Space
0xa0000000 - 0xbfffffff	Y	Y	SDRAM
0xc0000000 - 0xcfffffff	Y	Y	Cache Flush Region
0xd0000000 - 0xd0000fff	Y	N	first 4k page of flash
0xf0000000 - 0xffffffff	N	N	80200 Internal Registers

## Platform Resource Usage

The external timer is used as a polled timer to provide timeout support for networking and XModem file transfers.

## ARM/Xscale Intel IQ80321

### Overview

RedBoot supports the serial port and the built-in ethernet port for communication and downloads. The default serial port settings are 115200,8,N,1. RedBoot also supports flash management for the onboard 8MB flash.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

The board manufacturer provides a DOS application which is capable of programming the flash over the PCI bus, and this is required for initial installations of RedBoot. Please see the board manual for information on using this utility. In general, the process involves programming the ROM mode RedBoot image to flash. RedBoot should be programmed to flash address 0x00000000 using the DOS utility.

After booting the initial installation of RedBoot, this warning may be printed:

```
flash configuration checksum error or invalid key
```

This is normal, and indicates that the flash must be configured for use by RedBoot. Even if the above message is not printed, it may be a good idea to reinitialize the flash anyway. Do this with the **fis** command:

```
RedBoot> fis init
About to initialize [format] FLASH image system - continue (y/n)? y
*** Initialize FLASH Image System
Warning: device contents not erased, some blocks may not be usable
... Unlock from 0xf07e0000-0xf0800000: .
... Erase from 0xf07e0000-0xf0800000: .
... Program from 0x01ddf000-0x01ddf400 at 0xf07e0000: .
... Lock from 0xf07e0000-0xf0800000: .
```

## Switch Settings

The 80321 board is highly configurable through a number of switches and jumpers. RedBoot makes some assumptions about board configuration and attention must be paid to these assump-

tions for reliable RedBoot operation:

- The onboard ethernet and the secondary slot may be placed in a private space so that they are not seen by a PC BIOS. If the board is to be used in a PC with BIOS, then the ethernet should be placed in this private space so that RedBoot and the BIOS do not conflict.
- RedBoot assumes that the board is plugged into a PC with BIOS. This requires RedBoot to detect when the BIOS has configured the PCI-X secondary bus. If the board is placed in a backplane, RedBoot will never see the BIOS configure the secondary bus. To prevent this wait, set switch S7E1-3 to ON when using the board in a backplane.
- For the remaining switch settings, the following is a known good configuration:

S1D1	All OFF
S7E1	7 is ON, all others OFF
S8E1	2,3,5,6 are ON, all others OFF
S8E2	2,3 are ON, all others OFF
S9E1	3 is ON, all others OFF
S4D1	1,3 are ON, all others OFF
J9E1	2,3 jumpered
J9F1	2,3 jumpered
J3F1	Nothing jumpered
J3G1	2,3 jumpered
J1G2	2,3 jumpered

## LED Codes

RedBoot uses the two digit LED display to indicate status during board initialization. Possible codes are:

LED    Actions

-----

Power-On/Reset  
88  
Set the CPSR  
Enable coprocessor access  
Drain write and fill buffer  
Setup PBIU chip selects

A1

Enable the Icache  
A2 Move FLASH chip select from 0x0 to 0xF0000000  
Jump to new FLASH location  
A3 Setup and enable the MMU  
A4 I2C interface initialization  
90 Wait for I2C initialization to complete  
91 Send address (via I2C) to the DIMM  
92 Wait for transmit complete  
93 Read SDRAM PD data from DIMM  
94 Read remainder of EEPROM data.  
An error will result in one of the following  
error codes on the LEDs:  
77 BAD EEPROM checksum  
55 I2C protocol error  
FF bank size error  
A5 Setup DDR memory interface  
A6 Enable branch target buffer  
Drain the write & fill buffers  
Flush Icache, Dcache and BTB  
Flush instruction and data TLBs  
Drain the write & fill buffers  
SL ECC Scrub Loop  
SE  
A7 Clean, drain, flush the main Dcache  
A8 Clean, drain, flush the mini Dcache  
Flush Dcache  
Drain the write & fill buffers  
A9 Enable ECC  
AA

```
    Save SDRAM size
    Move MMU tables into RAM
AB
    Clean, drain, flush the main Dcache
    Clean, drain, flush the mini Dcache
    Drain the write & fill buffers
AC
    Set the TTB register to DRAM mmu_table
AD
    Set mode to IRQ mode
A7
    Move SWI & Undefined "vectors" to RAM (at 0x0)
A6
    Switch to supervisor mode
A5
    Move remaining "vectors" to RAM (at 0x0)
A4
    Copy DATA to RAM
    Initialize interrupt exception environment
    Initialize stack
    Clear BSS section
A3
    Call platform specific hardware initialization
A2
    Run through static constructors
A1
    Start up the eCos kernel or RedBoot
```

## Special RedBoot Commands

A special RedBoot command, **diag**, is used to access a set of hardware diagnostics. To access the diagnostic menu, enter **diag** at the RedBoot prompt:

```
RedBoot> diag
Entering Hardware Diagnostics - Disabling Data Cache!

    IQ80321 Hardware Tests

    1 - Memory Tests
    2 - Repeating Memory Tests
    3 - Repeat-On-Fail Memory Tests
    4 - Rotary Switch S1 Test
    5 - 7 Segment LED Tests
```

```
6 - i82544 Ethernet Configuration
7 - Battery Status Test
8 - Battery Backup SDRAM Memory Test
9 - Timer Test
10 - PCI Bus test
11 - CPU Cache Loop (No Return)
0 - quit
Enter the menu item number (0 to quit):
```

Tests for various hardware subsystems are provided, and some tests require special hardware in order to execute normally. The Ethernet Configuration item may be used to set the board ethernet address.

## Memory Tests

This test is used to test installed DDR SDRAM memory. Five different tests are run over the given address ranges. If errors are encountered, the test is aborted and information about the failure is printed. When selected, the user will be prompted to enter the base address of the test range and its size. The numbers must be in hex with no leading "0x"

```
Enter the menu item number (0 to quit): 1

Base address of memory to test (in hex): 100000

Size of memory to test (in hex): 200000

Testing memory from 0x00100000 to 0x002fffff.
```

```
Walking 1's test:
0000000100000002000000040000000800000010000000200000004000000080
0000010000000200000004000000080000001000000020000000400000008000
0001000000020000000400000008000000100000002000000040000000800000
0100000002000000040000000800000010000000200000004000000080000000
passed
32-bit address test: passed
32-bit address bar test: passed
8-bit address test: passed
Byte address bar test: passed
Memory test done.
```

## Repeating Memory Tests

The repeating memory tests are exactly the same as the above memory tests, except that the tests are automatically rerun after completion. The only way out of this test is to reset the board.

## Repeat-On-Fail Memory Tests

This is similar to the repeating memory tests except that when an error is found, the failing test continuously retries on the failing address.

## Rotary Switch S1 Test

This tests the operation of the sixteen position rotary switch. When run, this test will display the current position of the rotary switch on the LED display. Slowly dial through each position and confirm reading on LED.

## 7 Segment LED Tests

This tests the operation of the seven segment displays. When run, each LED cycles through 0 through F and a decimal point.

## i82544 Ethernet Configuration

This test initializes the ethernet controller's serial EEPROM if the current contents are invalid. In any case, this test will also allow the user to enter a six byte ethernet MAC address into the serial EEPROM.

```
Enter the menu item number (0 to quit): 6
```

```
Current MAC address: 00:80:4d:46:00:02  
Enter desired MAC address: 00:80:4d:46:00:01  
Writing to the Serial EEPROM... Done
```

```
***** Reset The Board To Have Changes Take Effect *****
```

## Battery Status Test

This tests the current status of the battery. First, the test checks to see if the battery is installed and reports that finding. If the battery is installed, the test further determines whether the battery status is one or more of the following:

- Battery is charging.
- Battery is fully discharged.
- Battery voltage measures within normal operating range.

## Battery Backup SDRAM Memory Test

This tests the battery backup of SDRAM memory. This test is a three step process:

1. Select Battery backup test from main diag menu, then write data to SDRAM.
2. Turn off power for 60 seconds, then repower the board.
3. Select Battery backup test from main diag menu, then check data that was written in step 1.

## Timer Test

This tests the internal timer by printing a number of dots at one second intervals.

## PCI Bus Test

This tests the secondary PCI-X bus and socket. This test requires that an IQ80310 board be plugged into the secondary slot of the IOP321 board. The test assumes at least 32MB of installed memory on the IQ80310. That memory is mapped into the IOP321 address space and the memory tests are run on that memory.

## CPU Cache Loop

This test puts the CPU into a tight loop run entirely from the ICache. This should prevent all external bus accesses.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=iq80321
export ARCH_DIR=arm
export PLATFORM_DIR=xscale/iq80321
```

The names of configuration files are listed above with the description of the associated modes.

## Interrupts

RedBoot uses an interrupt vector table which is located at address 0x8004. Entries in this table are pointers to functions with this prototype::

```
int irq_handler( unsigned vector, unsigned data )
```

On an IQ80321 board, the vector argument is one of 32 interrupts defined in `hal/arm/xscale/iop321/current/include/hal_var_ints.h`::

```
// *** 80200 CPU ***
#define CYGNUM_HAL_INTERRUPT_DMA0_EOT      0
#define CYGNUM_HAL_INTERRUPT_DMA0_EOC     1
#define CYGNUM_HAL_INTERRUPT_DMA1_EOT      2
#define CYGNUM_HAL_INTERRUPT_DMA1_EOC     3
#define CYGNUM_HAL_INTERRUPT_RSVD_4        4
#define CYGNUM_HAL_INTERRUPT_RSVD_5        5
#define CYGNUM_HAL_INTERRUPT_AA_EOT        6
#define CYGNUM_HAL_INTERRUPT_AA_EOC       7
#define CYGNUM_HAL_INTERRUPT_CORE_PMON     8
#define CYGNUM_HAL_INTERRUPT_TIMER0        9
#define CYGNUM_HAL_INTERRUPT_TIMER1       10
#define CYGNUM_HAL_INTERRUPT_I2C_0        11
#define CYGNUM_HAL_INTERRUPT_I2C_1        12
#define CYGNUM_HAL_INTERRUPT_MESSAGING    13
#define CYGNUM_HAL_INTERRUPT_ATU_BIST     14
#define CYGNUM_HAL_INTERRUPT_PERFMON     15
#define CYGNUM_HAL_INTERRUPT_CORE_PMU     16
#define CYGNUM_HAL_INTERRUPT_BIU_ERR      17
#define CYGNUM_HAL_INTERRUPT_ATU_ERR      18
#define CYGNUM_HAL_INTERRUPT_MCU_ERR      19
#define CYGNUM_HAL_INTERRUPT_DMA0_ERR     20
#define CYGNUM_HAL_INTERRUPT_DMA1_ERR     22
#define CYGNUM_HAL_INTERRUPT_AA_ERR       23
#define CYGNUM_HAL_INTERRUPT_MSG_ERR      24
#define CYGNUM_HAL_INTERRUPT_SSP          25
#define CYGNUM_HAL_INTERRUPT_RSVD_26      26
#define CYGNUM_HAL_INTERRUPT_XINT0        27
#define CYGNUM_HAL_INTERRUPT_XINT1        28
#define CYGNUM_HAL_INTERRUPT_XINT2        29
#define CYGNUM_HAL_INTERRUPT_XINT3        30
#define CYGNUM_HAL_INTERRUPT_HPI          31
```

The data passed to the ISR is pulled from a data table (`hal_interrupt_data`) which immediately follows the interrupt vector table. With 32 interrupts, the data table starts at address 0x8084.



## Chapter 5. Installation and Testing

0x20000000 - 0x9fffffff	0 0 0	ATU Outbound Direct Window
0xa0000000 - 0xb00ffffff	0 0 0	ATU Outbound Translate Windows
0xc0000000 - 0xdfffffff	0 0 0	Uncached alias for SDRAM
0xe0000000 - 0xe00ffffff	1 1 1	Cache flush region (no phys mem)
0xf0000000 - 0xf0800000	0 1 0	FLASH (PBIU CS0)
0xfe800000 - 0xfe800fff	0 0 0	UART (PBIU CS1)
0xfe840000 - 0xfe840fff	0 0 0	Left 7-segment LED (PBIU CS3)
0xfe850000 - 0xfe850fff	0 0 0	Right 7-segment LED (PBIU CS2)
0xfe8d0000 - 0xfe8d0fff	0 0 0	Rotary Switch (PBIU CS4)
0xfe8f0000 - 0xfe8f0fff	0 0 0	Battery Status (PBIU CS5)
0xfff00000 - 0xffffffff	0 0 0	IOP321 Memory mapped Registers

Alternate Virtual Map	X C B	Description
-----	- - -	-----
0x00000000 - 0x000ffffff	1 1 1	Alias for 1st MB of SDRAM
0x00100000 - 0x7fffffff	0 0 0	ATU Outbound Direct Window
0x80000000 - 0x900ffffff	0 0 0	ATU Outbound Translate Windows
0xa0000000 - 0xbfffffff	1 1 1	SDRAM
0xc0000000 - 0xdfffffff	0 0 0	Uncached alias for SDRAM
0xe0000000 - 0xe00ffffff	1 1 1	Cache flush region (no phys mem)
0xf0000000 - 0xf0800000	0 1 0	FLASH (PBIU CS0)
0xfe800000 - 0xfe800fff	0 0 0	UART (PBIU CS1)
0xfe840000 - 0xfe840fff	0 0 0	Left 7-segment LED (PBIU CS3)
0xfe850000 - 0xfe850fff	0 0 0	Right 7-segment LED (PBIU CS2)
0xfe8d0000 - 0xfe8d0fff	0 0 0	Rotary Switch (PBIU CS4)
0xfe8f0000 - 0xfe8f0fff	0 0 0	Battery Status (PBIU CS5)
0xfff00000 - 0xffffffff	0 0 0	IOP321 Memory mapped Registers

## Platform Resource Usage

The IOP321 programmable timer0 is used for timeout support for networking and XModem file transfers.

# ARM/Xscale Intel DBPXA27XC0

## Overview

RedBoot supports the FFUART on the CPU card and the built-in ethernet port for communication and downloads. The default serial port settings are 115200,8,N,1. RedBoot also supports flash management for the 32MB boot flash on the CPU card.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the CPU daughtercard flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

The board manufacturer provides a Windows application which is capable of programming the flash over JATG interface using the PC parallel port. This application is necessary for initial installations of RedBoot. Please see the board manual for more information on using this utility. In general, the process involves programming the ROM mode RedBoot image to flash address 0x00000000.

After booting the initial installation of RedBoot, this warning may be printed:

```
flash configuration checksum error or invalid key
```

This is normal, and indicates that the flash must be configured for use by RedBoot. Even if the above message is not printed, it may be a good idea to reinitialize the flash anyway. Do this with the **fis** command:

```
RedBoot> fis init
About to initialize [format] FLASH image system - continue (y/n)? y
*** Initialize FLASH Image System
Warning: device contents not erased, some blocks may not be usable
... Unlock from 0xf1fc0000-0xf2000000: .
... Erase from 0xf1fc0000-0xf2000000: .
... Program from 0x03fbf000-0x03fff000 at 0xf1fc0000: .
... Lock from 0xf1fc0000-0xf2000000: .
```

## Switch Settings

The DBPXA27XC0 board is configurable through a number of switches and jumpers. RedBoot makes some assumptions about board configuration and attention must be paid to these assumptions for reliable RedBoot operation. Specifically, SW1 and SW2 on the DBPXA27XC0 main board should be in the dot position.

## LED Codes

RedBoot uses the 8 digit LED display to indicate status during board initialization. Possible codes are:

LED    Actions

---

	Power-On/Reset
	Set the CPSR
	Enable coprocessor access
	Drain write and fill buffer
	Setup GPIO lines
	Setup PBIU chip selects
25000FFF	
	Delay 200usec
24000FFF	
	Initialize MSCx registers
	Initialize MECR, MCMEM0, MCMEM1, MCATT0, MCATT1, MCIO0, MCIO1
24100FFF	
	Initialize MDREFR
24200FFF	
	Initialize SXCNFG
24300FFF	
	Initialize MDCNFG
24400FFF	
	Trigger SDRAM refresh cycles
24500FFF	
	Enable SDRAM partitions
24600FFF	
	Enable SDRAM auto-powerdown
25800FFF	
	Setup clocks
25820FFF	
	Frequency change
25830FFF	
	Setup page table

```

25830FFF
    Setup domain permissions
25840FFF
    Turn on MMU
25850FFF
    Enable D-Cache
00000000
    Start up the eCos kernel or RedBoot

```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```

export TARGET=pxa270
export ARCH_DIR=arm
export PLATFORM_DIR=xscale/pxa270

```

The names of configuration files are listed above with the description of the associated modes.

## Interrupts

RedBoot uses an interrupt vector table which is located at address 0x8004. Entries in this table are pointers to functions with this prototype::

```
int irq_handler( unsigned vector, unsigned data )
```

On the DBPXA27XC0 board, the vector argument is one of many interrupts defined in `hal/arm/xscale/pxa270/current/include/hal_var_ints.h`:

```

#define CYGNUM_HAL_INTERRUPT_SSP3           0
#define CYGNUM_HAL_INTERRUPT_MSL           1
#define CYGNUM_HAL_INTERRUPT_USB_HOST2     2
#define CYGNUM_HAL_INTERRUPT_USB_HOST1     3
#define CYGNUM_HAL_INTERRUPT_KEYPAD        4
#define CYGNUM_HAL_INTERRUPT_MEMSTICK      5
#define CYGNUM_HAL_INTERRUPT_POWER_I2C     6
#define CYGNUM_HAL_INTERRUPT_TIMERX        7
#define CYGNUM_HAL_INTERRUPT_GPIO0         8
#define CYGNUM_HAL_INTERRUPT_GPIO1         9
#define CYGNUM_HAL_INTERRUPT_GPIO2_120    10
#define CYGNUM_HAL_INTERRUPT_USB_CLIENT    11

```

## Chapter 5. Installation and Testing

```
#define CYGNUM_HAL_INTERRUPT_CORE_PMU      12
#define CYGNUM_HAL_INTERRUPT_I2S          13
#define CYGNUM_HAL_INTERRUPT_AC97         14
#define CYGNUM_HAL_INTERRUPT_USIM         15
#define CYGNUM_HAL_INTERRUPT_SSP2         16
#define CYGNUM_HAL_INTERRUPT_LCD          17
#define CYGNUM_HAL_INTERRUPT_I2C          18
#define CYGNUM_HAL_INTERRUPT_ICP          19
#define CYGNUM_HAL_INTERRUPT_STUART       20
#define CYGNUM_HAL_INTERRUPT_BTUART       21
#define CYGNUM_HAL_INTERRUPT_FFUART       22
#define CYGNUM_HAL_INTERRUPT_FLASH        23
#define CYGNUM_HAL_INTERRUPT_SSP1         24
#define CYGNUM_HAL_INTERRUPT_DMA           25
#define CYGNUM_HAL_INTERRUPT_TIMER0        26
#define CYGNUM_HAL_INTERRUPT_TIMER1        27
#define CYGNUM_HAL_INTERRUPT_TIMER2        28
#define CYGNUM_HAL_INTERRUPT_TIMER3        29
#define CYGNUM_HAL_INTERRUPT_HZ           30
#define CYGNUM_HAL_INTERRUPT_ALARM        31
#define NOT_USED_32                        32
#define NOT_USED_33                        33
#define CYGNUM_HAL_INTERRUPT_GPIO2        34
...
#define CYGNUM_HAL_INTERRUPT_GPIO120      152
#define CYGNUM_HAL_INTERRUPT_MMC_CARD     153
#define CYGNUM_HAL_INTERRUPT_USIM_CARD    154
#define CYGNUM_HAL_INTERRUPT_USB_CABLE    155
#define CYGNUM_HAL_INTERRUPT_ETHERNET     156
#define CYGNUM_HAL_INTERRUPT_AC97_CODECS  157
#define CYGNUM_HAL_INTERRUPT_PEN          158
#define CYGNUM_HAL_INTERRUPT_MS_INSERT    159
#define CYGNUM_HAL_INTERRUPT_EXBRD        160
#define CYGNUM_HAL_INTERRUPT_RSVD8        161
#define CYGNUM_HAL_INTERRUPT_PCMCIA0_CARD  162
#define CYGNUM_HAL_INTERRUPT_PCMCIA0_STAT 163
#define CYGNUM_HAL_INTERRUPT_PCMCIA0      164
#define CYGNUM_HAL_INTERRUPT_RSVD12       165
#define CYGNUM_HAL_INTERRUPT_PCMCIA1_CARD 166
#define CYGNUM_HAL_INTERRUPT_PCMCIA1_STAT 167
#define CYGNUM_HAL_INTERRUPT_PCMCIA1      168
```

The data passed to the ISR is pulled from a data table (`hal_interrupt_data`) which immediately follows the interrupt vector table. With 169 interrupts, the data table starts at address `0x82a8`.

An application may create a normal C function with the above prototype to be an ISR. Just poke its address into the table at the correct index and enable the interrupt at its source. The return value of the ISR is ignored by RedBoot.

## Memory Maps

The RAM based page table is located at RAM start + 0x4000.

**NOTE:** The virtual memory maps in this section use a C, B, and X column to indicate the caching policy for the region..

X	C	B	Description
-	-	-	-----
0	0	0	Uncached/Unbuffered
0	0	1	Uncached/Buffered
0	1	0	Cached/Buffered      Write Through, Read Allocate
0	1	1	Cached/Buffered      Write Back, Read Allocate
1	0	0	Invalid -- not used
1	0	1	Uncached/Buffered    No write buffer coalescing
1	1	0	Mini DCache - Policy set by Aux Ctl Register
1	1	1	Cached/Buffered      Write Back, Read/Write Allocate

Physical Address Range	Description
-----	-----
0x00000000 - 0x03ffffff	Boot flash                    (nCS0)
0x04000000 - 0x07ffffff	Application flash          (nCS1)
0x08000000 - 0x080fffff	Baseboard registers        (nCS2)
0x0a000000 - 0x0a1fffff	SRAM                         (nCS2)
0x10000000 - 0x100fffff	Ethernet                    (nCS4)
0x20000000 - 0x2ffffff	PCMCIA/CF Slot 0
0x30000000 - 0x3ffffff	PCMCIA/CF Slot 1
0x40000000 - 0x43ffffff	CPU memory-mapped registers
0x44000000 - 0x47ffffff	LCD memory-mapped registers
0x48000000 - 0x4bffffff	Memory controller registers
0x4c000000 - 0x4ffffff	USB host
0xa0000000 - 0xa3ffffff	SDRAM bank 0                (nSDCS0)
0xa4000000 - 0xa7ffffff	SDRAM bank 1                (nSDCS0)

Virtual Address Map	X	C	B	Description
-----	-	-	-	-----
0x00000000 - 0x07ffffff	1	1	1	SDRAM
0x08000000 - 0x080fffff	0	0	0	Baseboard registers (nCS2)

```

0x0a000000 - 0x0a1ffffff 1 1 1 SRAM (nCS2)
0x10000000 - 0x100ffffff 0 0 0 Ethernet (nCS4)
0x20000000 - 0x2fffffff 0 0 0 PCMCIA/CF Slot 0
0x30000000 - 0x3fffffff 0 0 0 PCMCIA/CF Slot 1
0x40000000 - 0x43ffffff 0 0 0 CPU memory-mapped registers
0x44000000 - 0x47ffffff 0 0 0 LCD memory-mapped registers
0x48000000 - 0x4bffffff 0 0 0 Memory controller registers
0x4c000000 - 0x4fffffff 0 0 0 USB host
0xa0000000 - 0xa7ffffff 0 0 0 Uncached SDRAM alias
0xa8000000 - 0xa80fffff 1 1 1 D-cache flush region (no phys mem)
0xf0000000 - 0xf3ffffff 0 1 0 Boot flash (nCS0)
0xf4000000 - 0xf7ffffff 0 1 0 Application flash (nCS1)

```

## Platform Resource Usage

The PXA270 programmable OSTimer0 is used for timeout support for networking and XModem file transfers.

# CalmRISC/CalmRISC16 Samsung CalmRISC16 Core Evaluation Board

## Overview

The Samsung CalmRISC16 evaluation platform consists of two boards connected by a ribbon cable. One board contains the CPU core and memory. The other board is called the MDSChip board and provides the host interface. The calmRISC16 is a harvard architecture with separate 22-bit program and data addresses. The instruction set provides no instruction for writing to program memory. The MDSChip board firmware (called CalmBreaker) provides a pseudo register interface so that code running on the core has access to a serial channel and a mechanism to write to program memory. The serial channel is fixed at 57600-8-N-1 by the firmware. The CalmBreaker firmware also provides a serial protocol which allows a host to download a program and to start or stop the core board.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running via the MDSChip board.	redboot_ROM.ecm

## Initial Installation Method

The CalmRISC16 core is controlled through the MDSChip board. There is no non-volatile storage available for RedBoot, so RedBoot must be downloaded to the board on every power cycle. A small utility program is used to download S-record files to the eval board. Sources and build instructions for this utility are located in the RedBoot sources in: `packages/hal/calmrisc16/ceb/current/support`

To download the RedBoot image, first press the reset button on the MDSChip board. The green 'Run' LED on the core board should go off. Now, use the utility to download the RedBoot image with:

```
$ calmbreaker -p /dev/term/b --reset --srec-code -f redboot.elf
```

Note that the `-p /dev/term/b` specifies the serial port to use and will vary from system to system. The download will take about two minutes. After it finishes, start RedBoot with:

```
$ calmbreaker -p /dev/term/b --run
```

The 'Run' LED on the core board should be on. Connecting to the MDSboard with a terminal and typing enter should result in RedBoot reprinting the command prompt.

## Special RedBoot Commands

None.

## Special Note on Serial Channel

The MDSChip board uses a relatively slow microcontroller to provide the pseudo-register interface to the core board. This pseudo-register interface provides access to the serial channel and write access to program memory. Those interfaces are slow and the serial channel is easily overrun by a fast host. For this reason, GDB must be told to limit the size of code download packets to avoid serial overrun. This is done with the following GDB command:

```
(gdb) set download-write-size 25
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=calm16_ceb
export ARCH_DIR=calmrisc16
export PLATFORM_DIR=ceb
```

The names of configuration files are listed above with the description of the associated modes.

# CalmRISC/CalmRISC32 Samsung CalmRISC32 Core Evaluation Board

## Overview

The Samsung CalmRISC32 evaluation platform consists of two boards connected by a ribbon cable. One board contains the CPU core and memory. The other board is called the MDSChip board and provides the host interface. The calmRISC32 is a harvard architecture with separate 32-bit program and data addresses. The instruction set provides no instruction for writing to program memory. The MDSChip board firmware (called CalmBreaker) provides a pseudo register interface so that code running on the core has access to a serial channel and a mechanism to write to program memory. The serial channel is fixed at 57600-8-N-1 by the firmware. The CalmBreaker firmware also provides a serial protocol which allows a host to download a program and to start or stop the core board.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running via the MDSChip board.	redboot_ROM.ecm

## Initial Installation Method

The calmRISC32 core is controlled through the MDSChip board. There is no non-volatile storage available for RedBoot, so RedBoot must be downloaded to the board on every

power cycle. A small utility program is used to download S-record files to the eval board. Sources and build instructions for this utility are located in the RedBoot sources in: `packages/hal/calmrisc32/ceb/current/support`

To download the RedBoot image, first press the reset button on the MDSChip board. The green 'Run' LED on the core board should go off. Now, use the utility to download the RedBoot image with:

```
$ calmbreaker -p /dev/term/b --reset --srec-code -f redboot.elf
```

Note that the `'-p /dev/term/b'` specifies the serial port to use and will vary from system to system. The download will take about two minutes. After it finishes, start RedBoot with:

```
$ calmbreaker -p /dev/term/b --run
```

The 'Run' LED on the core board should be on. Connecting to the MDSboard with a terminal and typing enter should result in RedBoot reprinting the command prompt.

## Special RedBoot Commands

None.

## Special Note on Serial Channel

The MDSChip board uses a relatively slow microcontroller to provide the pseudo-register interface to the core board. This pseudo-register interface provides access to the serial channel and write access to program memory. Those interfaces are slow and the serial channel is easily overrun by a fast host. For this reason, GDB must be told to limit the size of code download packets to avoid serial overrun. This is done with the following GDB command:

```
(gdb) set download-write-size 25
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=calm32_ceb
export ARCH_DIR=calmrisc32
export PLATFORM_DIR=ceb
```

The names of configuration files are listed above with the description of the associated modes.

## FRV/FRV400 Fujitsu FR-V 400 (MB-93091)

### Overview

RedBoot supports both serial ports, which are available via the stacked serial connectors on the mother board. The topmost port is the default and is considered to be port 0 by RedBoot. The bottommost port is serial port 1. The default serial port settings are 38400,8,N,1.

FLASH management is also supported, but only for the FLASH device in IC7. This arrangement allows for IC8 to retain either the original Fujitsu board firmware, or some application specific contents.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation Method

RedBoot can be installed by directly programming the FLASH device in IC7 or by using the Fujitsu provided software to download and install a version into the FLASH device. Complete instructions are provided separately.

### Special RedBoot Commands

None.

## Memory Maps

The memory map of this platform is fixed by the hardware (cannot be changed by software). The only attributes which can be modified are control over cacheability, as noted below.

Address	Cache?	Resource
00000000-03FFFFFF	Yes	SDRAM (via plugin DIMM)
03F00000-03FFFFFF	No	SDRAM (used for PCI window)
10000000-1FFFFFFF	No	MB86943 PCI bridge
20000000-201FFFFF	No	SRAM
21000000-23FFFFFF	No	Motherboard resources
24000000-25FFFFFF	No	PCI I/O space
26000000-2FFFFFFF	No	PCI Memory space
30000000-FDFFFFFF	??	Unused
FE000000-FEFFFFFF	No	I/O devices
FF000000-FF1FFFFF	No	IC7 - RedBoot FLASH
FF200000-FF3FFFFF	No	IC8 - unused FLASH
FF400000-FFFFFFF	No	Misc other I/O

**NOTE:** The only configuration currently supported requires a 64MB SDRAM DIMM to be present on the CPU card. No other memory configuration is supported at this time.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=frv400
export ARCH_DIR=frv
export PLATFORM_DIR=frv400
```

The names of configuration files are listed above with the description of the associated modes.

## IA32/x86 x86-Based PC

### Overview

RedBoot supports two serial ports and an Intel i82559 based ethernet card (for example an Intel EtherExpress Pro 10/100) for communication and downloads. The default serial port settings are 38400,8,N,1.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
Floppy	[Floppy]	RedBoot running from a boot floppy disk installed in the A: drive of the PC.	redboot_ROM.ecm

### Initial Installation

RedBoot takes the form of a self-booting image that must be written onto a formatted floppy disk. The process will erase any file system or data that already exists on that disk, so proceed with caution.

For Red Hat Linux users, this can be done by:

```
$ dd conv=sync if=install/bin/redboot.bin of=/dev/fd0H1440
```

For NT Cygwin users, this can be done by first ensuring that the raw floppy device is mounted as `/dev/fd0`. To check if this is the case, type the command **mount** at the Cygwin bash prompt. If the floppy drive is already mounted, it will be listed as something similar to the following line:

```
\\.a: /dev/fd0 user binmode
```

If this line is not listed, then mount the floppy drive using the command:

```
$ mount -f -b //./a: /dev/fd0
```

To actually install the boot image on the floppy, use the command:

```
$ dd conv=sync if=install/bin/redboot.bin of=/dev/fd0
```

Insert this floppy in the A: drive of the PC to be used as a target and ensure that the BIOS is configured to boot from A: by default. On reset, the PC will boot from the floppy and be ready to be debugged via either serial line, or via the ethernet interface if it is installed.

**NOTE:** Unreliable floppy media may cause the write to silently fail. This can be determined if the RedBoot image does not correctly boot. In such cases, the floppy should be (unconditionally) reformatted using the **fdformat** command on Linux, or **format a: /u** on DOS/Windows.

## Flash management

PC RedBoot does not support any FLASH commands.

## Special RedBoot Commands

None.

## Memory Maps

All selectors are initialized to map the entire 32-bit address space in the familiar protected mode flat model. Page translation is not used. RAM up to 640K is mapped to 0x0 to 0xa0000. RAM above 640K is mapped from address 0x100000 upwards. Space is reserved between 0xa0000 and 0x100000 for option ROMs and the BIOS.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=pc
export ARCH_DIR=i386
export PLATFORM_DIR=pc
```

The names of configuration files are listed above with the description of the associated modes.

# MIPS/MIPS32(CoreLV 4Kc)+MIPS64(CoreLV 5Kc) Atlas Board

## Overview

RedBoot supports the DgbSer serial port and the built in ethernet port for communication and downloads. The default serial port settings are 115200,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation

RedBoot is installed using the code download facility built into the Atlas board. See the Atlas User manual for details, and also the Atlas download format in the Section called *Atlas download format*.

## Quick download instructions

Here are quick start instructions for downloading the prebuilt RedBoot image.

1. Locate the prebuilt files in the bin directory: `deleteall.dl` and `redboot.dl`.
2. Make sure switch S1-1 is OFF and switch S5-1 is ON. Reset the board and verify that the LED display reads `Flash DL`.
3. Make sure your parallel port is connected to the 1284 port Of the Atlas board.
4. Send the `deleteall.dl` file to the parallel port to erase previous images:

```
$ cat deleteall.dl >/dev/lp0
```

When this is complete, the LED display should read `Deleted`.

5. Send the ROM mode RedBoot image to the board:

```
$ cat redboot.dl >/dev/lp0
```

When this is complete, the LED display should show the last address programmed. This will be something like: 1fc17000.

6. Change switch S5-1 to OFF and reset the board. The LED display should read RedBoot.
7. Run the RedBoot **fs init** and **fconfig** commands to initialize the flash. See the Section called *Additional config options*, the Section called *Flash Image System (FIS)* in Chapter 2 and the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2 for details.

## Atlas download format

In order to download RedBoot to the Atlas board, it must be converted to the Atlas download format. There are different ways of doing this depending on which version of the developer's kit is shipped with the board.

The *Atlas Developer's Kit* CD contains an `srec2flash` utility. The source code for this utility is part of the `yamon/yamon-src-01.01.tar.gz` tarball on the Dev Kit CD. The path in the expanded tarball is `yamon/bin/tools`. To use `srec2flash` to convert the S-record file:

```
$ srec2flash -EL -S29 redboot.srec >redboot.dl
```

The *Atlas/Malta Developer's Kit* CD contains an `sreconv.pl` utility which requires Perl. This utility is part of the `yamon/yamon-src-02.00.tar.gz` tarball on the Dev Kit CD. The path in the expanded tarball is `yamon/bin/tools`. To use `sreconv` to convert the S-record file:

```
$ cp redboot_ROM.srec redboot_ROM.rec
$ sreconv.pl -ES L -A 29 redboot_ROM
```

The resulting file is named `redboot_ROM.fl`.

## Flash management

### Additional config options

The ethernet MAC address is stored in flash manually using the **fconfig** command. You can use the YAMON **setenv ethaddr** command to print out the board ethernet address. Typically, it is:

```
00:0d:a0:00:xx:xx
```

where `xx.xx` is the hex representation of the board serial number.

## Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this architecture (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for MIPS boards are:

**-b** *<addr>*

Location to store command line and environment passed to kernel

**-w** *<time>*

Wait time in seconds before starting kernel

**-c** *"params"*

Parameters passed to kernel

*<addr>*

Kernel entry point, defaulting to the entry point of the last image loaded

Linux kernels on MIPS platforms expect the entry point to be called with arguments in the registers equivalent to a C call with prototype:

```
void Linux(int argc, char **argv, char **envp);
```

RedBoot will place the appropriate data at the offset specified by the **-b** parameter, or by default at address 0x80080000, and will set the arguments accordingly when calling into the kernel.

The default entry point, if no image with explicit entry point has been loaded and none is specified, is 0x80000750.

## Interrupts

RedBoot uses an interrupt vector table which is located at address 0x80000400. Entries in this table are pointers to functions with this prototype:

```
int irq_handler( unsigned vector, unsigned data )
```

On an atlas board, the vector argument is one of 25 interrupts defined in `hal/mips/atlas/VERSION/include/plf_intr.h`:

```
#define CYGNUM_HAL_INTERRUPT_SER          0
#define CYGNUM_HAL_INTERRUPT_TIM0       1
#define CYGNUM_HAL_INTERRUPT_2         2
#define CYGNUM_HAL_INTERRUPT_3         3
```

```

#define CYGNUM_HAL_INTERRUPT_RTC                4
#define CYGNUM_HAL_INTERRUPT_COREHI            5
#define CYGNUM_HAL_INTERRUPT_CORELO            6
#define CYGNUM_HAL_INTERRUPT_7                 7
#define CYGNUM_HAL_INTERRUPT_PCIA              8
#define CYGNUM_HAL_INTERRUPT_PCIB              9
#define CYGNUM_HAL_INTERRUPT_PCIC             10
#define CYGNUM_HAL_INTERRUPT_PCID             11
#define CYGNUM_HAL_INTERRUPT_ENUM             12
#define CYGNUM_HAL_INTERRUPT_DEG              13
#define CYGNUM_HAL_INTERRUPT_ATXFAIL          14
#define CYGNUM_HAL_INTERRUPT_INTA             15
#define CYGNUM_HAL_INTERRUPT_INTB             16
#define CYGNUM_HAL_INTERRUPT_INTC            17
#define CYGNUM_HAL_INTERRUPT_INTD            18
#define CYGNUM_HAL_INTERRUPT_SERR            19
#define CYGNUM_HAL_INTERRUPT_HW1             20
#define CYGNUM_HAL_INTERRUPT_HW2             21
#define CYGNUM_HAL_INTERRUPT_HW3             22
#define CYGNUM_HAL_INTERRUPT_HW4             23
#define CYGNUM_HAL_INTERRUPT_HW5             24

```

The data passed to the ISR is pulled from a data table (`hal_interrupt_data`) which immediately follows the interrupt vector table. With 25 interrupts, the data table starts at address `0x80000464` on atlas.

An application may create a normal C function with the above prototype to be an ISR. Just poke its address into the table at the correct index and enable the interrupt at its source. The return value of the ISR is ignored by RedBoot.

## Memory Maps

Memory Maps RedBoot sets up the following memory map on the Atlas board.

```

Physical Address Range Description
-----
0x00000000 - 0x07ffffff SDRAM
0x08000000 - 0x17ffffff PCI Memory Space
0x18000000 - 0x1bffffff PCI I/O Space
0x1be00000 - 0x1bffffff System Controller
0x1c000000 - 0x1dffffff System flash
0x1e000000 - 0x1e3ffffff Monitor flash
0x1f000000 - 0x1fbffffff FPGA

```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=atlas_mips32_4kc
export TARGET=atlas_mips64_5kc
export ARCH_DIR=mips
export PLATFORM_DIR=atlas
```

Use one of the TARGET settings only.

The names of configuration files are listed above with the description of the associated modes.

# MIPS/MIPS32(CoreLV 4Kc)+MIPS64(CoreLV 5Kc) Malta Board

## Overview

RedBoot supports both front facing serial ports and the built in ethernet port for communication and downloads. The default serial port settings are 38400,8,N,1. RedBoot runs from and supports flash management for the system flash region.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation

RedBoot is installed using the code download facility built into the Malta board. See the Malta User manual for details, and also the Malta download format in the Section called *Malta down-*

*load format.*

## Quick download instructions

Here are quick start instructions for downloading the prebuilt RedBoot image.

1. Locate the prebuilt files in the bin directory: `deleteall.fl` and `redboot_ROM.fl`.
2. Make sure switch S5-1 is ON. Reset the board and verify that the LED display reads `Flash DL`.
3. Make sure your parallel port is connected to the 1284 port Of the Atlas board.
4. Send the `deleteall.fl` file to the parallel port to erase previous images:
 

```
$ cat deleteall.fl >/dev/lp0
```

 When this is complete, the LED display should read `Deleted`.
5. Send the RedBoot image to the board:
 

```
$ cat redboot_ROM.fl >/dev/lp0
```

 When this is complete, the LED display should show the last address programmed. This will be something like: `1fc17000`.
6. Change switch S5-1 to OFF and reset the board. The LED display should read `RedBoot`.
7. Run the RedBoot **fis init** and **fconfig** commands to initialize the flash. See the Section called *Flash Image System (FIS)* in Chapter 2 and the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2 for details.

## Malta download format

In order to download RedBoot to the Malta board, it must be converted to the Malta download format.

The *Atlas/Malta Developer's Kit* CD contains an `sreconv.pl` utility which requires Perl. This utility is part of the `yamon/yamon-src-02.00.tar.gz` tarball on the Dev Kit CD. The path in the expanded tarball is `yamon/bin/tools`. To use `sreconv` to convert the S-record file:

```
$ cp redboot_ROM.srec redboot_ROM.rec
$ sreconv.pl -ES L -A 29 redboot_ROM
```

The resulting file is named `redboot_ROM.fl`.

## Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this architecture (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for MIPS boards are:

**-b** *<addr>*

Location to store command line and environment passed to kernel

**-w** *<time>*

Wait time in seconds before starting kernel

**-c** *"params"*

Parameters passed to kernel

*<addr>*

Kernel entry point, defaulting to the entry point of the last image loaded

Linux kernels on MIPS platforms expect the entry point to be called with arguments in the registers equivalent to a C call with prototype:

```
void Linux(int argc, char **argv, char **envp);
```

RedBoot will place the appropriate data at the offset specified by the **-b** parameter, or by default at address 0x80080000, and will set the arguments accordingly when calling into the kernel.

The default entry point, if no image with explicit entry point has been loaded and none is specified, is 0x80000750.

## Interrupts

RedBoot uses an interrupt vector table which is located at address 0x80000200. Entries in this table are pointers to functions with this prototype:

```
int irq_handler( unsigned vector, unsigned data )
```

On the malta board, the vector argument is one of 22 interrupts defined in `hal/mips/malta/VERSION/include/plf_intr.h`:

```
#define CYGNUM_HAL_INTERRUPT_SOUTH_BRIDGE_INTR 0
#define CYGNUM_HAL_INTERRUPT_SOUTH_BRIDGE_SMI 1
#define CYGNUM_HAL_INTERRUPT_CBUS_UART 2
#define CYGNUM_HAL_INTERRUPT_COREHI 3
```

```

#define CYGNUM_HAL_INTERRUPT_CORELO          4
#define CYGNUM_HAL_INTERRUPT_COMPARE        5
#define CYGNUM_HAL_INTERRUPT_TIMER          6
#define CYGNUM_HAL_INTERRUPT_KEYBOARD       7
#define CYGNUM_HAL_INTERRUPT_CASCADE       8
#define CYGNUM_HAL_INTERRUPT_TTY1          9
#define CYGNUM_HAL_INTERRUPT_TTY0         10
#define CYGNUM_HAL_INTERRUPT_11           11
#define CYGNUM_HAL_INTERRUPT_FLOPPY       12
#define CYGNUM_HAL_INTERRUPT_PARALLEL     13
#define CYGNUM_HAL_INTERRUPT_REAL_TIME_CLOCK 14
#define CYGNUM_HAL_INTERRUPT_I2C          15
#define CYGNUM_HAL_INTERRUPT_PCI_AB       16
#define CYGNUM_HAL_INTERRUPT_PCI_CD       17
#define CYGNUM_HAL_INTERRUPT_MOUSE        18
#define CYGNUM_HAL_INTERRUPT_19           19
#define CYGNUM_HAL_INTERRUPT_IDE_PRIMARY   20
#define CYGNUM_HAL_INTERRUPT_IDE_SECONDARY 21

```

The data passed to the ISR is pulled from a data table (`hal_interrupt_data`) which immediately follows the interrupt vector table. With 22 interrupts, the data table starts at address `0x80000258`.

An application may create a normal C function with the above prototype to be an ISR. Just poke its address into the table at the correct index and enable the interrupt at its source. The return value of the ISR is ignored by RedBoot.

## Memory Maps

Memory Maps RedBoot sets up the following memory map on the Malta board.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address Range	C	B	Description
0x80000000 - 0x81ffffff	Y	Y	SDRAM
0x9e000000 - 0x9e3ffffff	Y	N	System flash (cached)
0x9fc00000 - 0x9fffffff	Y	N	System flash (mirrored)
0xa8000000 - 0xb7ffffff	N	N	PCI Memory Space
0xb4000000 - 0xb40ffffff	N	N	Galileo System Controller
0xb8000000 - 0xb80ffffff	N	N	Southbridge / ISA
0xb8100000 - 0xbbdffffff	N	N	PCI I/O Space
0xbe000000 - 0xbe3ffffff	N	N	System flash (noncached)
0xbf000000 - 0xbfffffff	N	N	Board logic FPGA

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=malta_mips32_4kc
export ARCH_DIR=mips
export PLATFORM_DIR=malta
```

The names of configuration files are listed above with the description of the associated modes.

## MIPS/RM7000 PMC-Sierra Ocelot

### Overview

RedBoot uses the front facing serial port. The default serial port settings are 38400,8,N,1. RedBoot also supports ethernet. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Additional commands

The **exec** command which allows the loading and execution of Linux kernels, is supported for this architecture (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for MIPS boards are:

`-b <addr>`

Location to store command line and environment passed to kernel

`-w <time>`

Wait time in seconds before starting kernel

`-c "params"`

Parameters passed to kernel

`<addr>`

Kernel entry point, defaulting to the entry point of the last image loaded

Linux kernels on MIPS platforms expect the entry point to be called with arguments in the registers equivalent to a C call with prototype:

```
void Linux(int argc, char **argv, char **envp);
```

RedBoot will place the appropriate data at the offset specified by the `-b` parameter, or by default at address `0x80080000`, and will set the arguments accordingly when calling into the kernel.

The default entry point, if no image with explicit entry point has been loaded and none is specified, is `0x80000750`.

## Memory Maps

RedBoot sets up the following memory map on the Ocelot board.

Note that these addresses are accessed through `kseg0/1` and thus translate to the actual address range `0x80000000-0xbfffffff`, depending on the need for caching/non-caching access to the bus.

**NOTE:** The virtual memory maps in this section use a C and B column to indicate whether or not the region is cached (C) or buffered (B).

Physical Address	Range	Description
0x00000000	- 0x0fffffff	SDRAM
0x10000000	- 0x10fffffff	PCI I/O space
0x12000000	- 0x13fffffff	PCI Memory space
0x14000000	- 0x1400ffff	Galileo system controller
0x1c000000	- 0x1c0000ff	PLD (board logic)
0x1fc00000	- 0x1fc7ffff	flash

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=ocelot
export ARCH_DIR=mips
export PLATFORM_DIR=rm7000/ocelot
```

The names of configuration files are listed above with the description of the associated modes.

## MIPS/UPD985XX ASCOM LAKI Board

### Overview

RedBoot uses the single LAKI serial port. The default serial port settings are 38400,8,N,1.

Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm
POST	[ROM]	RedBoot running at a higher address in the flash, for cooperation with customer POST code or other boot image.	redboot_POST.ecm

## Initial Installation Method

This assumes that you will install all 3 variants. Should you wish to preserve the customer boot-loader behaviour, don't bother with any mention of ROM configuration RedBoot below; just install POST and RAM configurations. You would then have to use the customer bootloader to start RedBoot if/when you want to use RedBoot and eCos.

The ASCOM boot image supports SRecord downloading over the serial line (as does RedBoot itself). Obtain SRecord versions of each RedBoot image using commands such as `mips64vr4100el-elf-objcopy -O srec install/bin/redboot.elf /tftpboot/redboot-RAM.srec`

See below for information about rebuilding RedBoot from sources.

## Run the RAM mode RedBoot

Load an SRecord RAM mode RedBoot image using the "SRecord download and execute" option in the ASCOM Boot image menu.

This is the initial splashscreen:

```
ascom PLC Bootloader                               [Ver. 2.0]
Jul 04 2001 - 14:51:39
System Information
  Top Memory address : 0xA07FFFE0
  Top Flash address  : 0xBFFFFFF80
```

```
*****
Press any key to enter menu, or wait for countdown
to start your default application!
*****
```

2

So press a key, to get the menu screen. Navigate to start S3 download and execute thus, then press enter:

```
PLC Bootloader [Ver. 2.0] Jul 04 2001 - 14:51:39
```

```
Boot Menu
=====

Configuration
view memory
jump in memory
boot from sdram
[START S3 DOWNLOAD AND EXECUTE]
start S3 download
```

```
start gdb-stub
jump at 0xbfc20000 (start Green Hills monserv)
```

[use : n or N - next, p or P - previous, x, X or enter - valid]

The bootloader will show this screen, with a rotating caret as is usual when the download starts:

```
ascom PLC Bootloader                               [Ver. 2.0]
Jul 04 2001 - 14:51:39

Bootloader starts ...
```

Send the SRecord version of RedBoot down the serial line. On LINUX `cat /tftpboot/redboot-RAM.srec > /dev/ttyS0` for example.

You should now have a running RedBoot.

## Initialize the Flash

Initialize the flash image system and RedBoot's flash configuration data.

```
RedBoot> fis init
....
```

Place a valid fconfig record in the flash:

```
RedBoot> fconfig -i
....
```

For more information about these commands, see the Section called *Flash Image System (FIS)* in Chapter 2 and the Section called *Persistent State Flash-based Configuration and Control* in Chapter 2.

## Install POST RedBoot in flash

Load a POST configuration RedBoot image into RAM then save it in flash:

```
RedBoot> load -m y -b %FREEMEMLO}
```

Use minicom's "send" function ^AS with ymodem to send your file eg. `redboot-POST.srec`

See load for details of the load command.

```
RedBoot> fis cre RedBoot[post] -b %FREEMEMLO} -r 0x9fc80000
```

```
An image named 'RedBoot[post]' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot[post]'
  at 0xbfc80000..0xbfcffff from 0x80100000 - continue (y/n)? y
```

## Install RedBoot in the boot block

Load a ROM configuration RedBoot image into RAM then save it in flash:

```
RedBoot> load -m y -b %{FREEMEMLO}
```

Use minicom's "send" function ^AS with ymodem to send your file eg. redboot-ROM.srec

See load for details of the load command.

```
RedBoot> fis cre RedBoot -b %{FREEMEMLO} -r 0x9fc00000
An image named 'RedBoot' exists - continue (y/n)? y
* CAUTION * about to program 'RedBoot'
  at 0xbfc00000..0xbfc3ffff from 0x80100000 - continue (y/n)? y
```

Reset RedBoot which should run the flash-based RedBoot:

```
RedBoot> reset
....
```

To check that all is well in the FIS table, you can use the **fis list** command. You should see something like this:

```
RedBoot> fis lis
Name                FLASH addr  Mem addr    Length      Entry point
RedBoot             0xBFC00000 0xBFC00000 0x00040000 0x9FC00000
RedBoot[post]      0xBFC80000 0xBFC80000 0x00040000 0x9FC80000
RedBoot config     0xBFFC0000 0xBFFC0000 0x00020000 0x00000000
FIS directory      0xBFFE0000 0xBFFE0000 0x00020000 0x00000000
RedBoot>
```

For more information about the fis, see the Section called *Flash Image System (FIS)* in Chapter 2.

**NOTE:** If you chose not to install the ROM configuration RedBoot, rather than **reset** above, type **go 0xbfc80000** to jump into the POST-configuration RedBoot.

## Flash management

### Updating the POST RedBoot image

To update the POST RedBoot image, follow the procedures detailed in the Section called *Update the primary RedBoot flash image* in Chapter 4, but use a POST RedBoot image and the FIS name "RedBoot[post].

### Starting RedBoot from ASCOM Boot image

If you chose not to install the ROM configuration RedBoot, you will need to select “Jump in Memory” and type in **bfc80000** (Bee Eff Cee Eight oh oh oh oh, not the default) then “yes” to confirm. RedBoot should start, all happy.

```
PLC Bootloader [Ver. 2.0] Jul 04 2001 - 14:51:39
```

```
Boot Menu
=====
```

```
Configuration
view memory
[JUMP IN MEMORY]
boot from sdram
start S3 download and execute
start S3 download
start gdb-stub
jump at 0xbfc20000 (start Green Hills monserv)
```

```
[use : n or N - next, p or P - previous, x, X or enter - valid]
```

You will need to do this every time the board is power cycled.

## Communication Channels

Serial, Ethernet.

The default serial setup is 38400 8N1.

The ethernet acquires its ESA from the Serial EEPROM that is automatically managed by the uPD985xx MicroWire subsystem.

## Special RedBoot Commands

None. But this board is unusual in that it might be fitted with an oversized Intel StrataFlash device. In this case the flash device driver takes special care to use the flash correctly, and reports as such during startup:

```
FLASH: Oversized device! End addr 0xc0400000 changed to 0xc0000000
FLASH: 0xbfc00000 - 0xc0000000, 32 blocks of 0x00020000 bytes each.
....
```

The CPU is unable to address the upper half of the flash device which would live in addresses 0xc0000000 - 0xc0400000 so it adjusts the description of the flash device to accommodate this limitation.

## Memory Maps

This is all dictated by the MIPS architecture of the VR4120 MIPS Core at the heart of the uPD985xx devices. Addresses 0x80000000 - 0x9fffffff are cachable access to physical address space, and addresses 0xa0000000 - 0xbfffffff are non-cachable access to physical address space. RedBoot and eCos uses only these two areas. Flash and I/O areas are accessed through the non-cachable area; RAM is accessed (mainly) through the cachable space.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=laki
export ARCH_DIR=mips
export PLATFORM_DIR=laki1
```

The names of configuration files are listed above with the description of the associated modes.

# MIPS/VR4375 NEC DDB-VRC4375

## Overview

RedBoot supports only serial port 1, which is connected to the upper of the stacked serial connectors on the board. The default serial port settings are 38400,8,N,1. FLASH management is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

A device programmer should be used to program a socketed FLASH part (AMD 29F040). The board as delivered is configured for a 512K EPROM. To install a FLASH ROM, Jumpers J30, J31 and J36 need to be changed as described in the board's User Manual.

## Special RedBoot Commands

None.

## Memory Maps

RedBoot sets up the memory map primarily as described in the board's User Manual. There are some minor differences, noted in the following table:

Physical Addresses	Virtual Addresses	Resource
-----------------------	----------------------	----------

00000000-01FFFFFF	80000000-81FFFFFF	Base SDRAM (cached)
00000000-01FFFFFF	A0000000-A1FFFFFF	Base SDRAM (uncached)
0C000000-0C0BFFFF	AC000000-AC0B0000	PCI IO space
0F000000-0F0001FF	AF000000-AF0001FF	VRC4375 Registers
1C000000-1C0FFFFFF	BC000000-BC0FFFFFF	VRC4372 Registers
1C100000-1DFFFFFF	BC100000-BDFFFFFF	PCI Memory space
1FC00000-1FC7FFFF	BFC00000-BFC7FFFF	FLASH ROM
80000000-8000000D	C0000000-C000000D	RTC
8000000E-80007FFF	C000000E-C0007FFF	NVRAM
81000000-81FFFFFF	C1000000-C1FFFFFF	Z85C30 DUART
82000000-82FFFFFF	C2000000-C2FFFFFF	Z8536 Timer
83000000-83FFFFFF	C3000000-C3FFFFFF	8255 Parallel port
87000000-87FFFFFF	C7000000-C7FFFFFF	Seven segment display

**NOTE:** By default the VRC4375 SIMM control registers are not programmed since the values used must depend on the SIMMs installed. If SIMMs are to be used, correct values must be placed in these registers before accessing the SIMM address range.

**NOTE:** The allocation of address ranges to devices in the PCI IO and memory spaces is handled by the eCos PCI support library. They do not correspond to those described in the board User Manual.

**NOTE:** The MMU has been set up to relocate the VRC4372 supported devices mapped at physical addresses 0x8xxxxxxx to virtual addresses 0xCxxxxxxx.

## Ethernet Driver

The ethernet driver is in two parts:

A generic ether driver for the Intel i21143 device is located in `devs/eth/intel/i21143`. Its package name is `CYGPKG_DEVS_ETH_INTEL_I21143`.

The platform-specific ether driver is `devs/eth/mips/vrc4375`. Its package is `CYGPKG_DEVS_ETH_MIPS_VRC4375`. This tells the generic driver the address in IO memory of the chip, for example, and other configuration details. The ESA (MAC address) is by default collected from on-board serial EEPROM, unless configured statically within this package.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=vrc4373
export ARCH_DIR=mips
export PLATFORM_DIR=vrc4373
```

The names of configuration files are listed above with the description of the associated modes.

# PowerPC/MPC860T Analogue & Micro PowerPC 860T

## Overview

RedBoot uses the SMC1 serial port. The default serial port settings are 38400,8,N,1. Ethernet is also supported using the RJ-45 connector. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROMRAM	[ROMRAM]	RedBoot running from RAM, but contained in the board's flash boot sector.	redboot_ROMRAM.ecm

## Initial Installation Method

RedBoot must be installed at the A & M factory.

## Special RedBoot Commands

None.

## Memory Maps

Memory Maps RedBoot sets up the following memory map on the MBX board.

```
Physical Address Range Description
-----
0x00000000 - 0x007ffffff DRAM
0xfe000000 - 0xfe0ffffff flash (AMD29LV8008B)
0xff000000 - 0xff0ffffff MPC registers
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=viper
export ARCH_DIR=powerpc
export PLATFORM_DIR=viper
```

The names of configuration files are listed above with the description of the associated modes.

# PowerPC/MPC8XX Motorola MBX

## Overview

RedBoot uses the SMC1/COM1 serial port. The default serial port settings are 38400,8,N,1. Ethernet is also supported using the 10-base T connector.

Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm

Configuration	Mode	Description	File
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

Device programmer is used to program the XU1 socketed flash part (AM29F040B) with the ROM mode image of RedBoot. Use the on-board EPPC-Bug monitor to update RedBoot.

This assumes that you have EPPC-Bug in the on-board flash. This can be determined by setting up the board according to the following instructions and powering up the board.

The EPPC-Bug prompt should appear on the SMC1 connector at 9600 baud, 8N1.

1. Set jumper 3 to 2-3 [allow XU1 flash to be programmed]
2. Set jumper 4 to 2-3 [boot EPPC-Bug]

If it is available, program the flash by following these steps:

1. Prepare EPPC-Bug for download:

```
EPPC-Bug>lo 0
```

At this point the monitor is ready for input. It will not return the prompt until the file has been downloaded.

2. Use the terminal emulator's ASCII download feature (or a simple clipboard copy/paste operation) to download the `redboot.ppcbug` file.

Note that on Linux, Minicom's ASCII download feature seems to be broken. A workaround is to load the file into emacs (or another editor) and copy the full contents to the clipboard. Then press the mouse paste-button (usually the middle one) over the Minicom window.

3. Program the flash with the downloaded data:

```
EPPC-Bug>pflash 40000 60000 fc000000
```

4. Switch off the power, and change jumper 4 to 1-2. Turn on the power again. The board should now boot using the newly programmed RedBoot.

## Special RedBoot Commands

None.

## Memory Maps

Memory Maps RedBoot sets up the following memory map on the MBX board.

```
Physical Address Range Description
-----
0x00000000 - 0x003ffffff DRAM
0xfa100000 - 0xfa100003 LEDs
0xfe000000 - 0xfe07ffff flash (AMD29F040B)
0xff000000 - 0xff0fffff MPC registers
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=mbx
export ARCH_DIR=powerpc
export PLATFORM_DIR=mbx
```

The names of configuration files are listed above with the description of the associated modes.

# SuperH/SH2(SH7615) Control SerHub1

## Overview

RedBoot uses both the COM1 (SCIF1, RS232/422/485) and COM2 (SCIF2, IrDA) serial ports. The default serial port settings are 38400,8,N,1 for COM1 and 9600,8,N,1 for COM2. Ethernet is also supported using the RJ45 connector.

Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

For bootstrapping RedBoot into the 29LV400 flash, it is necessary to set jumper J3 (SWAP), causing the mapping of the 29LV400 to appear at 0x00040000 while the two 37VF010 parts appear at 0x00000000. In order for the RedBoot flash code to handle the miss-aligned location of the 29LV400 part, the option CYGSEM\_DEVS\_FLASH\_SH\_SERHUB1\_HALF must be set. Such a configuration of RedBoot is called either RAM/half or ROM/half, depending on whether it is configured to run from RAM or flash (ROM).

To install RedBoot into the 29LV400 part (or write any other data to that part), run a "half"-configured version of RedBoot. This can be done in one of two ways:

- Program a ROM/half version of RedBoot into the 37VF010 parts.
- Program the Control monitor into the 37VF010 parts and use it to download a RAM/half version of RedBoot:

```
> dl
```

in a shell on the host computer, now copy the RAM/half version of RedBoot to the serial port:

```
$ cat redboot_RAM_half.srec > /dev/ttyS0
```

After downloading completes and the prompt returns, start RedBoot by issuing the command

```
> go 060213C0
```

(the address may change - it can be found at the last line of the `redboot_RAM_half.srec` file).

**NOTE:** The RAM/half configuration of RedBoot uses the same baud rate as the Control monitor (9600 baud) to avoid confusing the terminal emulator when RedBoot starts up.

Both "half"-configured RedBoot images should show this line when probing for the flash part:

```
FLASH: 0x00040000 - 0x000c0000, 8 blocks of 0x00010000 bytes each.
```

When the RedBoot prompt appears, download the ROM mode (non-half) configuration of RedBoot and program it into the flash:

```
RedBoot> lo -m y -b %{FREEMEMLO}
```

Now send the file `redboot_ROM.srec` using the terminal emulator's Y-modem upload function, and you should eventually see the prompt again:

```
Address offset = 0x06048000
Entry point: 0x000013c0, address range: 0x00000000-0x00017e30
xyzModem - CRC mode, 2201(SOH)/0(STX)/0(CAN) packets, 3 retries
RedBoot>
```

Now write the RedBoot image into the 29LV400 flash:

```
RedBoot> fi write -f 0x00040000 -b %{FREEMEMLO} -l 0x00020000
* CAUTION * about to program FLASH
          at 0x00040000..0x0005ffff from 0x06048000 - continue (y/n)? y
... Erase from 0x00040000-0x00060000: ..
... Program from 0x06048000-0x06068000 at 0x00040000: ..
RedBoot>
```

## Special RedBoot Commands

The **sm** command allows the serial transceiver mode of COM1 to be changed to one of RS232, RS422, or RS485. The board always starts up using the RS232 mode.

If a permanent change to one of the other modes is required, use the script feature to change the mode after a timeout:

```
RedBoot> fconfig
Run script at boot: true
Boot script:
Enter script, terminate with empty line
>> sm 422
>>
Boot script timeout (1000ms resolution): 1
Use BOOTP for network configuration: true
```

```
Console baud rate: 38400
DNS server IP address:
GDB connection port: 9000
Force console for special debug messages: false
Network debug at boot time: false
Update RedBoot non-volatile configuration - continue (y/n)? y
... Erase from 0x00060000-0x00061000: .
... Program from 0x0606e000-0x0606f000 at 0x00060000: .
RedBoot>
```

When resetting the board, it will print out the RedBoot banner using the RS232 mode and then change to the selected mode (here RS422) after a 1-second delay. This means it is always possible to recover the board from a wrong configuration by connecting it to a standard PC serial connection.

## Memory Maps

RedBoot sets up the following memory map on the board.

Physical Address	Range	Description
0x00000000	- 0x0007ffff	Flash (29LV400)
0x06000000	- 0x0607ffff	SRAM

## Ethernet Driver

The ethernet driver uses a hardwired ESA which can, at present, only be changed in CDL.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=serhub1
export ARCH_DIR=sh
export PLATFORM_DIR=serhub1
```

The names of configuration files are listed above with the description of the associated modes.

# SuperH/SH2(SH7044) Alpha Project AP-SH2F-2A

## Overview

RedBoot uses the SCI1 serial port. The default serial port settings are 38400,8,N,1.

Management of on-core flash is not supported. RedBoot is available only in ROM mode, which must be programmed into the flash using the Windows programming application.

## Initial Installation Method

For bootstrapping RedBoot into the on-core flash, turn off the board and set switch SS1 to OFF-OFF-OFF-OFF-OFF-OFF. Then turn back on the power and program the RedBoot srec image using the Windows programming application. Turn off the board again and set switch SS1 to OFF-OFF-OFF-OFF-OFF-OFF. Finally, turn on the power again. You should see the RedBoot banner written out on the serial port.

## Memory Maps

RedBoot sets up the following memory map on the board.

Physical Address	Range	Description
0x00000000	- 0x0003ffff	On-core flash
0x00400000	- 0x0043ffff	SRAM

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=apsh2f2a
export ARCH_DIR=sh
export PLATFORM_DIR=apsh2f2a
```

The names of configuration files are listed above with the description of the associated modes.

## SuperH/SH3(SH7708) Hitachi EDK7708

### Overview

RedBoot uses the serial port. The default serial port settings are 38400,8,N,1.

Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation Method

Program the ROM RedBoot image into flash using an eprom programmer.

### Memory Maps

RedBoot sets up the following memory map on the EDK7708 board.

```
Physical Address Range  Description
-----
0x80000000 - 0x8001ffff  Flash (AT29LV1024)
0x88000000 - 0x881fffff  DRAM
0xa4000000 - 0xa40000ff  LED ON
0xb8000000 - 0xb80000ff  LED ON
```

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=edk7708
export ARCH_DIR=sh
export PLATFORM_DIR=edk7708
```

The names of configuration files are listed above with the description of the associated modes.

# SuperH/SH3(SH7709) Hitachi Solution Engine 7709

## Overview

This description covers the MS7709SE01 variant. See the Section called *SuperH/SH3(SH77X9) Hitachi Solution Engine 77X9* for instructions for the MS7729SE01 and MS7709SSE0101 variants.

RedBoot uses the COM1 and COM2 serial ports. The default serial port settings are 38400,8,N,1. Ethernet is also supported using the 10-base T connector.

Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

The Solution Engine ships with the Hitachi boot monitor in EPROM which allows for initial

programming of RedBoot:

1. Set switch SW4-1 to ON [boot from EPROM]
2. Connect a serial cable to CN1 (SCI) and power up the board.
3. After the boot monitor banner, invoke the flash download/program command:

```
Ready >fl
```

4. The monitor should now ask for input:

```
Flash ROM data copy to RAM  
Please Send A S-format Record
```

At this point copy the RedBoot ROM SREC file to the serial port:

```
$ cat redboot_SE7709RP_ROM.eprom.srec > /dev/ttyS0
```

Eventually you should see something like

```
Start Addr = A1000000  
End Addr = A1xxxxxx  
Transfer complete
```

from the monitor.

5. Set switch SW4-1 to OFF [boot from flash] and reboot the board. You should now see the RedBoot banner.

## Special RedBoot Commands

The **exec** command which allows the loading and execution of Linux kernels is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the SE77x9 are:

**-b** <addr>

Parameter block address. This is normally the first page of the kernel image and defaults to 0x8c101000

**-i** <addr>

Start address of initrd image

**-j** <size>

Size of initrd image

**-c** "args"

Kernel arguments string

`-m <flags>`

Mount ronly flags. If set to a non-zero value the root partition will be mounted read-only.

`-f <flags>`

RAM disk flags. Should normally be 0x4000

`-r <device number>`

Root device specification. /dev/ram is 0x0101

`-l <type>`

Loader type

Finally the kernel entry address can be specified as an optional argument. The default is 0x8c102000

For the the SE77x9, Linux by default expects to be loaded at 0x8c001000 which conflicts with the data space used by RedBoot. To work around this, either change the CONFIG\_MEMORY\_START kernel option to a higher address, or use the compressed kernel image and load it at a higher address. For example, setting CONFIG\_MEMORY\_START to 0x8c100000, the kernel expects to be loaded at address 0x8c101000 with the entry point at 0x8c102000.

## Memory Maps

RedBoot sets up the following memory map on the SE77x9 board.

Physical Address	Range	Description
0x80000000	- 0x803ffffff	Flash (MBM29LV160)
0x81000000	- 0x813ffffff	EPROM (M27C800)
0x8c000000	- 0x8dffffff	DRAM
0xb0000000	- 0xb03ffffff	Ethernet (DP83902A)
0xb0800000	- 0xb08ffffff	16C552A
0xb1000000	- 0xb100ffff	Switches
0xb1800000	- 0xb18ffffff	LEDs
0xb8000000	- 0xbbffffff	PCMCIA (MaruBun)

## Ethernet Driver

The ethernet driver uses a hardwired ESA which can, at present, only be changed in CDL.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=se77x9
export ARCH_DIR=sh
export PLATFORM_DIR=se77x9
```

The names of configuration files are listed above with the description of the associated modes.

## SuperH/SH3(SH7729) Hitachi HS7729PCI

### Overview

RedBoot uses the COM1 and COM2 serial ports (and the debug port on the motherboard). The default serial port settings are 38400,8,N,1. Ethernet is also supported using a D-Link DFE-530TX PCI plugin card. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation Method

A ROM mode RedBoot image must be programmed into the two EPROMs. Two files with a split version of the ROM mode image is provided: it is also possible to recreate these from the `redboot.bin` file, but requires the `split_word.c` program in `hal/sh/hs7729pci/VERSION/misc` to be built and executed with the `redboot.bin` filename as sole argument.

After doing this it is advised that another ROM mode image of RedBoot is programmed into the on-board flash, and that copy be used for booting the board. This allows for software programmed updates of RedBoot instead of having to reprogram the EPROMs.

1. Program the EPROMs with RedBoot. The `.lo` image should go in socket M1 and the `.hi` image in socket M2.
2. Set switch SW1-6 to ON [boot from EPROM]
3. Follow the instructions under Flash management for updating the flash copy of RedBoot, but force the flash destination address with
 

```
-f 0x80400000
```

 due to setting of the SW1-6 switch.
4. Set switch SW1-6 to OFF [boot from flash] and reboot the board. You should now see the RedBoot banner. At this time you may want to issue the command `fis init` to initialize the flash table with the correct addresses.

## Special RedBoot Commands

The `exec` command which allows the loading and execution of Linux kernels is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The `exec` parameters used for the HS7729PCI are:

`-b <addr>`

Parameter block address. This is normally the first page of the kernel image and defaults to 0x8c101000

`-i <addr>`

Start address of initrd image

`-j <size>`

Size of initrd image

`-c "args"`

Kernel arguments string

`-m <flags>`

Mount ronly flags. If set to a non-zero value the root partition will be mounted read-only.

`-f <flags>`

RAM disk flags. Should normally be 0x4000

`-r <device number>`

Root device specification. /dev/ram is 0x0101

`-l <type>`

Loader type

Finally the kernel entry address can be specified as an optional argument. The default is 0x8c102000

On the HS7729PCI, Linux expects to be loaded at address 0x8c101000 with the entry point at 0x8c102000. This is configurable in the kernel using the CONFIG\_MEMORY\_START option.

## Memory Maps

RedBoot sets up the following memory map on the HS7729PCI board.

Physical Address	Range	Description
0x80000000	- 0x803ffffff	Flash (MBM29LV160)
0x80400000	- 0x807ffffff	EPROM (M27C800)
0x82000000	- 0x82ffffff	SRAM
0x89000000	- 0x89ffffff	SRAM
0x8c000000	- 0x8fffffff	SDRAM
0xa8000000	- 0xa800ffff	SuperIO (FDC37C935A)
0xa8400000	- 0xa87ffffff	USB function (ML60851C)
0xa8800000	- 0xa8bffffff	USB host (SL11HT)
0xa8c00000	- 0xa8c3ffff	Switches
0xa8c40000	- 0xa8c7ffff	LEDs
0xa8c80000	- 0xa8cffffff	Interrupt controller
0xb0000000	- 0xb3ffffff	PCI (SD0001)
0xb8000000	- 0xbbffffff	PCMCIA (MaruBun)

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=hs7729pci
export ARCH_DIR=sh
export PLATFORM_DIR=hs7729pci
```

The names of configuration files are listed above with the description of the associated modes.

## SuperH/SH3(SH77X9) Hitachi Solution Engine 77X9

### Overview

This description covers the MS7729SE01 and MS7709SSE0101 variants. See the Section called *SuperH/SH3(SH7709) Hitachi Solution Engine 7709* for instructions for the MS7709SE01 variant.

RedBoot uses the COM1 and COM2 serial ports. The default serial port settings are 38400,8,N,1. Ethernet is also supported using the 10-base T connector. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

### Initial Installation Method

The Solution Engine ships with the Hitachi boot monitor in EPROM which allows for initial programming of RedBoot:

1. Set switches SW4-3 and SW4-4 to ON [boot from EPROM]
2. Connect a serial cable to COM2 and power up the board.
3. After the boot monitor banner, invoke the flash download/program command:

```
Ready >f1
```

4. The monitor should now ask for input:

```
Flash ROM data copy to RAM
```

Please Send A S-format Record

At this point copy the RedBoot ROM SREC file to the serial port:

```
$ cat redboot_rom.eprom.srec > /dev/ttyS0
```

Eventually you should see something like

```
Start Addr = A1000000
```

```
End Addr = A1xxxxxx
```

```
Transfer complete
```

from the monitor.

5. Set switch SW4-3 to OFF [boot from flash] and reboot the board. You should now see the RedBoot banner.

## Special RedBoot Commands

The **exec** command which allows the loading and execution of Linux kernels is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the SE77x9 are:

**-b** <addr>

Parameter block address. This is normally the first page of the kernel image and defaults to 0x8c101000

**-i** <addr>

Start address of initrd image

**-j** <size>

Size of initrd image

**-c** "args"

Kernel arguments string

**-m** <flags>

Mount rdnly flags. If set to a non-zero value the root partition will be mounted read-only.

**-f** <flags>

RAM disk flags. Should normally be 0x4000

**-r** <device number>

Root device specification. /dev/ram is 0x0101

-l <type>

Loader type

Finally the kernel entry address can be specified as an optional argument. The default is 0x8c102000

On the SE77x9, Linux expects to be loaded at address 0x8c101000 with the entry point at 0x8c102000. This is configurable in the kernel using the CONFIG\_MEMORY\_START option.

## Memory Maps

RedBoot sets up the following memory map on the SE77x9 board.

Physical Address	Range	Description
0x80000000	- 0x803ffffff	Flash (MBM29LV160)
0x81000000	- 0x813ffffff	EPROM (M27C800)
0x8c000000	- 0x8dffffff	SDRAM
0xb0000000	- 0xb03ffffff	Ethernet (DP83902A)
0xb0400000	- 0xb07ffffff	SuperIO (FDC37C935A)
0xb0800000	- 0xb0bffffff	Switches
0xb0c00000	- 0xb0ffffff	LEDs
0xb1800000	- 0xb1bffffff	PCMCIA (MaruBun)

## Ethernet Driver

The ethernet driver uses a hardwired ESA which can, at present, only be changed in CDL.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=se77x9
export ARCH_DIR=sh
export PLATFORM_DIR=se77x9
```

The names of configuration files are listed above with the description of the associated modes.

# SuperH/SH4(SH7751) Hitachi Solution Engine 7751

## Overview

RedBoot uses the COM1 serial port. The default serial port settings are 38400,8,N,1. Ethernet is also supported using the 10-base T connector. Management of onboard flash is also supported.

The following RedBoot configurations are supported:

Configuration	Mode	Description	File
ROM	[ROM]	RedBoot running from the board's flash boot sector.	redboot_ROM.ecm
RAM	[RAM]	RedBoot running from RAM with RedBoot in the flash boot sector.	redboot_RAM.ecm

## Initial Installation Method

The Solution Engine ships with the Hitachi boot monitor in EPROM which allows for initial programming of RedBoot:

1. Set switches SW5-3 and SW5-4 to ON [boot from EPROM]
2. Connect a serial cable to COM1 and power up the board.
3. After the boot monitor banner, invoke the flash download/program command:

```
Ready >f1
```

4. The monitor should now ask for input:

```
Flash ROM data copy to RAM  
Please Send A S-format Record
```

At this point copy the RedBoot ROM SREC file to the serial port:

```
$ cat redboot_ROM.eprom.srec > /dev/ttyS0
```

Eventually you should see something like

```
Start Addr = A1000000  
End Addr = A1xxxxxx  
Transfer complete
```

from the monitor.

5. Set switch SW5-3 to OFF [boot from flash] and reboot the board. You should now see the RedBoot banner.

## Special RedBoot Commands

The **exec** command which allows the loading and execution of Linux kernels is supported for this board (see the Section called *Executing Programs from RedBoot* in Chapter 2). The **exec** parameters used for the SE7751 are:

**-b** *<addr>*

Parameter block address. This is normally the first page of the kernel image and defaults to 0x8c101000

**-i** *<addr>*

Start address of initrd image

**-j** *<size>*

Size of initrd image

**-c** *"args"*

Kernel arguments string

**-m** *<flags>*

Mount ronly flags. If set to a non-zero value the root partition will be mounted read-only.

**-f** *<flags>*

RAM disk flags. Should normally be 0x4000

**-r** *<device number>*

Root device specification. /dev/ram is 0x0101

**-l** *<type>*

Loader type

Finally the kernel entry address can be specified as an optional argument. The default is 0x8c102000

On the SE7751, Linux expects to be loaded at address 0x8c101000 with the entry point at 0x8c102000. This is configurable in the kernel using the CONFIG\_MEMORY\_START option.

## Memory Maps

RedBoot sets up the following memory map on the SE7751 board.

Physical Address	Range	Description
0x80000000	- 0x803ffffff	Flash (MBM29LV160)
0x81000000	- 0x813ffffff	EPROM (M27C800)
0x8c000000	- 0x8fffffff	SDRAM
0xb8000000	- 0xb8fffffff	PCMCIA (MaruBun)
0xb9000000	- 0xb9fffffff	Switches
0xba000000	- 0xbaffffff	LEDs
0xbd000000	- 0xbdfffffff	PCI MEM space
0xbe200000	- 0xbe23ffff	PCI Ctrl space
0xbe240000	- 0xbe27ffff	PCI IO space

## Ethernet Driver

The ethernet driver uses a hardwired ESA which can, at present, only be changed in CDL.

## Rebuilding RedBoot

These shell variables provide the platform-specific information needed for building RedBoot according to the procedure described in Chapter 3:

```
export TARGET=se7751
export ARCH_DIR=sh
export PLATFORM_DIR=se7751
```

The names of configuration files are listed above with the description of the associated modes.