



Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040

Tested Hardware and Operating System List (THOL)

Revision 1.0

February, 2012

Enterprise Platforms and Services Division

Revision History

Date	Revision Number	Modifications
February 2012	1.0	Initial release
		-

Disclaimers

THE INFORMATION IN THIS DOCUMENT IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications.

Intel retains the right to make changes to its test specifications at any time, without notice.

The hardware vendor remains solely responsible for the design, sale and functionality of its product, including any liability arising from product infringement or product warranty.

Copyright © Intel Corporation 2009-2012. All rights reserved.

Intel and the Intel logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Table of Contents

1. Introduction	1
1.1 Test Overview	1
1.1.1 Basic Compatibility Testing	1
1.1.2 Adapter / Peripheral Compatibility and Stress Testing	2
1.2 Pass/Fail Test Criteria.....	3
2. Firmware Configurations	4
3. Operating Systems	5
3.1 Operating System Certifications	6
4. Supported Server Boards	7
4.1 Intel® Server Boards.....	7
4.2 3 rd Party Server Boards.....	7
5. Enclosures, PCI Adapters, and Peripherals	8
5.1 External Storage	8
5.2 Internal Storage	8
5.3 Tape and Optical Drives.....	8
6. Hard Disk Drives and Solid State Drives	9
6.1 Hard Disk Drives and Solid State Drives (SSD).....	9

<This page intentionally left blank.>

1. Introduction

This document provides users of the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 with a guide to the operating systems, server boards, chassis, disk drives, and other peripherals that Intel tested for use with these integrated RAID modules.

This document will be updated as additional testing is performed, or until these Intel® integrated RAID Modules are no longer in production. Each new release of the document will include the information from previous releases.

Intel will only provide support for the RAID module when it is installed in a system configured with the specified server boards, and when the server board is configured with the tested RAID firmware, system BIOS / firmware, and operating system versions.

These RAID Modules were thoroughly tested with Intel® server boards, Intel® drive enclosures, and the third-party devices listed in this document. However, it is not practical to test these RAID Modules in every possible combination of server board, drive enclosure, hard drive, and peripheral device. Sample combinations have been tested to gain confidence in their compatibility, and the devices listed were tested in one or more configurations.

1.1 Test Overview

Testing performed on the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 is classified under two categories:

- Compatibility Testing
- Stress Testing

1.1.1 Basic Compatibility Testing

Compatibility testing is performed with each supported operating system. Basic installation testing validates that Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 can be used to install the operating system and that the base hardware feature set is functional. A small set of peripherals are used for installation purposes only. Additional add-in cards are not tested.

Note: *The latest version of an operating system signifies the latest supported version at the time of testing. New releases of this document may include a newly supported release of an operating system. Previous releases of a supported operating system may not be tested beyond the basic compatibility test process.*

1.1.1.1 Support Commitment for Basic Installation Testing

Intel commits to the following level of customer support for operating systems that receive only basic installation testing:

- Intel will provide tested operating system drivers for each of the integrated controllers on the server board, provided the controller vendor has a driver available. Intel does not

require vendors to develop drivers for operating systems that they do not already support. This may limit the functionality of certain server board integrated controllers.

- Intel will provide support to customers who experience issues with the integrated controllers due to the installation or functionality of an operating system only if a driver is available.
- Intel does not provide support for issues related to the use of add-in adapters or peripherals installed in the server system with an operating system that received only basic installation testing.
- Support is defined as assistance provided to a customer in root causing an issue and determining an acceptable resolution to the operating system problem. The resolution may include, but is not limited to, on-board controller driver updates, engaging the vendor, BIOS changes, firmware changes, or determining an acceptable workaround for the issue with the customer.

1.1.2 Adapter / Peripheral Compatibility and Stress Testing

Adapter / Peripheral Compatibility and Stress testing is performed only on the most current release of a supported operating system available at the time of testing. The Adapter / Peripheral Compatibility and Stress testing process consists of three areas:

- **Base Platform:** Each base platform will successfully install a given operating system, successfully run a disk stress test, and successfully run a network stress test.
- **Adapter Compatibility:** Adapter compatibility validation (CV) testing uses test suites to gain an accurate view of how the server performs with a wide variety of adapters under the primary supported operating systems. These tests are designed to show hardware compatibility between the cards and the server platform and include functional testing only. CV testing does not include heavy stressing of the systems or the cards.
- **Stress Testing:** This test sequence uses configurations with add-in adapters installed in all available slots (depending on the chassis used), and runs for a minimum of 72 hours (three days) without injecting errors. Each configuration passes an installation test, a network/disk stress test, and tape backup test. Any fatal errors require a restart of the test.

1.1.2.1 Support Commitment for Adapter / Peripheral Compatibility and Stress Testing

Intel will provide the following level of customer support for operating systems that receive Adapter / Peripheral Compatibility and Stress testing:

- Intel will provide support to customers who experience issues with tested operating systems involving the installation or functionality of the server board with or without the adapters and peripherals listed in this document as having been tested under the operating system.
- Support is defined as assistance provided to a customer in root causing an issue and determining an acceptable resolution to the problem. The resolution may include, but is not limited to, on-board controller driver updates, engaging the vendor, BIOS changes, firmware changes, or determining a workaround for the issue.
- Intel provides and tests operating system drivers for each on-board video, network, and storage controller.

- Intel enables vendors to provide driver support for add-in adapters using these operating systems.
- Intel will go through some of the steps to achieve certification to ensure its customers do not encounter problems. The actual certification is the responsibility of the customer.

Note: *Intel does not provide a support commitment for operating systems, adapter cards, and peripherals not listed in this document. Intel will consider requests for support on a case-by-case basis.*

1.2 Pass/Fail Test Criteria

For each operating system, adapter, and peripheral configuration, a test passes if specific criteria are met. Specific configurations with particular characteristics are addressed on a case-by-case basis. In general, a configuration passes testing if the following conditions are met:

- The operating system installed without error.
 - Manufacturer's installation instructions or Intel's best-known methods were used for the operating system installation.
 - No extraordinary workarounds were required during the operating system installation.
 - The server system behaved as expected during and after the operating system installation.
 - Application software installed and executed normally.
- Hardware compatibility tests ran to completion without error.
- Test software suites executed successfully:
 - Test and data files were created in the correct directories without error.
 - Files copied from the client to the server and back match the original without error.
 - Clients remain connected to the server system.
 - Industry-standard test suites run to completion without error.

2. Firmware Configurations

The following table lists the tested controller and firmware configurations. This document will be updated with additional configurations as new revisions of the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 or firmware versions for that controller are released. Each configuration is assigned an identifier number which is referenced in the tables throughout this document.

Note: Intel only provides support for adapters and peripherals in the configuration with which they were tested.

Base System Identifier #	Product Code	Part Number	Firmware Revision
1	RMS25KB080	917089	Initial release
	RMS25KB040	917090	
	RMS25JB080	917087	
	RMS25JB040	917088	

3. Operating Systems

The following table provides a list of supported operating systems for the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040. Each operating system was tested for compatibility with Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 configuration listed in Chapter 2. Operating systems are only supported in the specified base system configuration(s) with which they were tested.

The following table also indicates whether each operating system received Basic Installation testing, or Adapter / Peripheral Compatibility and Stress testing. For information on the support commitments for Basic Installation Testing and Adapter / Peripheral Compatibility and Stress Testing, see Chapter 1.

Any variations to the standard operating system installation process are documented in the Installation Guidelines section of this document. If the installation guidelines are not noted in the following table, then the operating system installed as expected using the manufacturer's installation instructions or Intel's best-known methods.

Note: *The operating systems listed in the following table have been tested for compatibility with the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040, but the operating system and its associated driver may not have been tested for compatibility with the server board you have selected. Refer to the supported operating system list for your server board to verify operating system compatibility with the server board. This document lists testing performed on Intel® Server Boards only.*

Ident#	Operating System (with latest Service Package or Update Package)	Base System Configuration Tested – Type of Testing
1	Microsoft Windows 2008*	Configuration 1 – Compatibility and Stress
2	Microsoft Windows 2008*, x64	Configuration 1 – Compatibility and Stress
3	Microsoft Windows 2008 R2*, x64	Configuration 1 – Compatibility and Stress
4	Red Hat* Enterprise Linux ES 6.0	Configuration 1 – Compatibility and Stress
5	Red Hat* Enterprise Linux ES 6.0, x86_64	Configuration 1 – Compatibility and Stress
6	SuSE* Linux Enterprise Server 11.0	Configuration 1 – Compatibility and Stress
7	SuSE* Linux Enterprise Server 11.0 x86_64	Configuration 1 – Compatibility and Stress
8	Microsoft Windows 7*	Configuration 1 – Basic Installation
9	Microsoft Windows 7*, x64	Configuration 1 – Basic Installation
10	Microsoft Windows Vista*	Configuration 1 – Basic Installation
11	Microsoft Windows Vista*, x64	Configuration 1 – Basic Installation
12	Microsoft Windows 2003*	Configuration 1 – Basic Installation
13	Microsoft Windows 2003*, x64	Configuration 1 – Basic Installation
14	Red Hat* Enterprise Linux ES 5.0	Configuration 1 – Basic Installation
15	Red Hat* Enterprise Linux ES 5.0, x86_64	Configuration 1 – Basic Installation
16	SuSE* Linux Enterprise Server 10.0	Configuration 1 – Basic Installation
17	SuSE* Linux Enterprise Server 10.0, x86_64	Configuration 1 – Basic Installation

Ident#	Operating System (with latest Service Package or Update Package)	Base System Configuration Tested – Type of Testing
18	VMware* ESX 4.1	Configuration 1 – Basic Installation
19	VMware* ESXi 4.1	Configuration 1 – Basic Installation
20	VMWare* ESXi 5.0	Configuration 1 – Basic Installation

3.1 Operating System Certifications

The following table lists the operating systems that Intel will certify with the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040. Each customer is responsible for their own certification from the individual operating system vendors. In many cases, customers may leverage their operating system certifications from the testing completed by Intel. See the “Comments” column next to each operating system in the following table for additional information. Intel’s certifications, pre-certification, and operating system testing may help reduce some of the risk in achieving customer certifications with the operating system vendors.

Operating System	Certification Listing	Comments
Microsoft Windows 2008 Enterprise Server*	Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 , RMS25JB040	OEM must request certification by Microsoft for their specific product. http://www.microsoft.com/whdc/hcl/default.aspx

4. Supported Server and Workstation Boards

4.1 Intel® Server and Workstation Boards

Below list includes the Intel® Server and Workstation Boards software versions that the server and workstation boards were configured with at the time of testing.

Intel® Server and Workstation Boards	BIOS	BMC	FRU/SDR	Comment
S2600GZ/GL	Initial release	Initial release	Initial release	
S2600CP	Initial release	Initial release	Initial release	Not supported by RMS25JB080 and RMS25JB040
S2600IP	Initial release	Initial release	Initial release	
S2600CO	Initial release	Initial release	Initial release	Not supported by RMS25JB080 and RMS25JB040
W2600CR	Initial release	Initial release	Initial release	

Note: To select the proper Intel® Integrated RAID module for Intel® Server System, please use the Server Configurator tool available at <http://serverconfigurator.intel.com/default.aspx>.

4.2 3rd Party Server Boards

The Intel® Integrated RAID module RMS25KB080, RMS25KB040, RMS25JB080, and RMS25JB040 do not support 3rd party server boards.

5. Enclosures, PCI Adapters, and Peripherals

The testing of enclosures, add-in cards, and peripherals was performed on the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 by Intel labs, independent test labs, or the vendor. Compatibility and stress testing was performed with the latest version of an operating system available at the time of testing.

Although a large sample of configurations were tested, not all devices were tested under all operating systems, and not all possible combinations or configurations of third-party devices were tested for inter-compatibility due to the large number of possible configurations. To verify compatibility, use the Server Configurator Tool available at:

<http://serverconfigurator.intel.com/default.aspx>.

Add-in adapter card and peripheral compatibility and stress testing is performed with the latest version of an operating system available at the time of testing. The adapters are divided into categories based on their functionality. All integrated on-board devices are tested by default and are, therefore, not included in the following tables.

Note: *All adapter cards and peripherals were not tested under all operating systems.*

Any variations to the standard adapter installation process or to expected adapter functionality are documented in the 'Installation Guidelines' section of this document. If there are installation guidelines affecting a particular adapter and operating system combination, they are referenced in the following table. If the installation guidelines are not noted in the following table, then the adapter installed and functioned as expected, using the manufacturer's installation instructions or Intel's best-known methods.

Note: *Adapter cards are normally tested with unused add-in adapters and on-board controller expansion ROMs disabled in the BIOS Setup. Intel recommends that customers disable the option ROM for add-in controllers and/or the on-board controllers when not booting from the controller or needing to use its built-in utilities.*

5.1 External Storage

None.

5.2 Internal Storage

Please refer to Section 4.1 for details.

5.3 Tape and Optical Drives

None.

6. Hard Disk Drives and Solid State Drives

The testing of hard disk drives and solid state drives was performed with the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 by Intel labs, independent test labs, or vendors. The compatibility and stress testing is performed with the latest version of an operating system available at the time of testing. Although a large sample of configurations was tested, not all devices were tested under all operating systems, and not all possible combinations or configurations of third-party devices were tested for inter-compatibility due to the large number of possible configurations. To verify that the device is included for the server board as well as for the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040, use the Server Configurator tool available at:

<http://serverconfigurator.intel.com/default.aspx>.

Note: All hard disk drives and solid state drives were not tested under all operating systems.

Any variations to the standard adapter installation process or to the expected adapter functionality are documented in the 'Installation Guidelines' section of this document. If there are installation guidelines affecting a particular adapter and operating system combination, these are referenced in the following table. If the installation guidelines are not noted in the following table, then the adapter installed and functioned as expected, using the manufacturer's installation instructions or Intel's best-known methods.

6.1 Hard Disk Drives and Solid State Drives (SSD)

Note: The hard disk drives and solid state drives are listed in the following table only if they were attached to the Intel® Integrated RAID Module RMS25KB080, RMS25KB040, RMS25JB080 and RMS25JB040 during testing.

Note: To select hard drives for Intel® Server Chassis and Intel® Server System, please use the Server Configurator tool available at

<http://serverconfigurator.intel.com/default.aspx>.

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Toshiba*	SAS	6Gb/s	MBF2600RC	0107	600GB	2.5"	10K
Fujitsu*	SAS	6Gb/s	MBE2073RC	0103	73GB	2.5"	15K
Fujitsu*	SAS	6Gb/s	MBD2300RC	D807	300GB	2.5"	10K
Fujitsu*	SAS	6Gb/s	MBE2147RC	0103	147GB	2.5"	15K
Fujitsu*	SAS	6Gb/s	MBD2147RC	0102	147GB	2.5"	10K
Fujitsu*	SAS	3Gb/s	MBB2073RC	0105	73GB	2.5"	10K
Fujitsu*	SAS	3Gb/s	MAV2036RC	0108	36GB	2.5"	10K
Fujitsu*	SAS	3Gb/s	MBC2073RC	0104	73GB	2.5"	15K
Fujitsu*	SAS	3Gb/s	MBB2147RC	0105	140GB	2.5"	10K
Fujitsu*	SAS	3Gb/s	MAU3147RC	0104	147GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MBA3300RC	0103	300GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MBA3147RC	0103	147GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MBA3073RC	0103	73GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MAX3036RC	0104	36GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MAX3073RC	0104	73GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MAX3036RC	D207	36GB	3.5"	15K
Fujitsu*	SAS	3Gb/s	MAX3147RC	5202	146GB	3.5"	15K
Fujitsu*	SATA	3Gb/s	MHZ2320B	0009	320GB	2.5"	5400

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Fujitsu*	SATA	3Gb/s	MHZ2320B	001E	320GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MJA2320B	0018	320GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MHZ2160B	011E	160GB	2.5"	7200
Fujitsu*	SATA	3Gb/s	MHZ2160B	0009	160GB	2.5"	7200
Fujitsu*	SATA	3Gb/s	MHZ2250B	0009	250GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MHZ2250B	001E	250GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MJA2400B	0018	400GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MHZ2080B	001E	80GB	2.5"	5400
Fujitsu*	SATA	3Gb/s	MHZ2120B	0109	120GB	2.5"	5400
Hitachi*	SAS	6Gb/s	HUC106060CSS600	A840	600GB	2.5"	10K
Hitachi*	SAS	6Gb/s	HUC106060CSS601	B852	600GB	2.5"	FDE
Hitachi*	SAS	6Gb/s	HUC106060CSS600	A150	600GB	2.5"	10K
Hitachi*	SAS	6Gb/s	HUS156030VLS600	A538	300GB	3.5"	15K
Hitachi*	SAS	6Gb/s	HUS156060VLS601	B530	600GB	3.5"	SED
Hitachi*	SAS	6Gb/s	HUS156060VLS600	A392	600GB	3.5"	15K
Hitachi*	SAS	6Gb/s	HUC151473CSS600	A330	73GB	2.5"	15K
Hitachi*	SAS	6Gb/s	HUC151414CSS600	A370	147GB	2.5"	15K
Hitachi*	SAS	6Gb/s	HUC151414CSS600	A330	147GB	2.5"	15K
Hitachi*	SAS	6Gb/s	HUC103014CSS600	A529	147G	2.5"	10K
Hitachi*	SAS	6Gb/s	HUC103030CSS600	A120	300GB	2.5"	10K
Hitachi*	SAS	6Gb/s	HUC151414CSS600	A330	147GB	2.5"	15K
Hitachi*	SAS	6Gb/s	HUC151473CSS600	A330	73GB	2.5"	15K
Hitachi*	SAS	6Gb/s	HUC103014CSS600	A120	147GB	2.5"	10K
Hitachi*	SAS	6Gb/s	HUS156045VLS600	a53E	450GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A130	36GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A230	36GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS153073VLS300	A110	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A120	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151414VLS300	A110	146GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151414VLS300	A420	147GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A230	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A211	73GB	3.5"	15K
Hitachi*	SATA	3Gb/s	HDS725050KLA360	ABOA	500GB	3.5"	7200
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A211	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS156030VLS600	A310	300GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A110	36GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A420	36GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A230	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A350	36GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS154530VLS300	A4B0	300GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS154545VLS300	A4B0	450GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A340	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS153030VLS300	A120	300GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151473VLS300	A130	73GB	3.5"	15K
Hitachi*	SAS	3Gb/s	HUS151436VLS300	A48B	36GB	3.5"	15K
Hitachi*	SATA	3Gb/s	HDS722020ALA330	A20N	2TB	3.5"	7200
Hitachi*	SATA	3Gb/s	H7220AA30SUN20T	A2DZ	2TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HUA72202ALA330	A00U	2TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDT721010SLA360	A3AA	1TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDE721050SLA330	GM40	500GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDE721010SLA330	A31B	1TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS728080PLA380	A69A	82GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS722512VLSA80	A63A	120GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS72161	AB1A	160GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDT72502	A72A	250GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDP72503	A52A	320GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDT722525DLA380	A80A	250GB	3.5"	7200
Hitachi*	SATA	3Gb/s	S728080PLA380	PF2O	80GB	3.5"	7200

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Hitachi*	SATA	3Gb/s	HDT722525DLA380	A60A	250GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS722580VLSA80	A63A	80GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS728080PLA380	A60A	82GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS728080PLA380	A6BA	82GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDT722516DLA380	A80A	160GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS72161	ABEA	160GB	3.5"	7200
Hitachi*	SATA	3Gb/s	HUA72101	A70M	1TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HUA72201	A25C	1TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HUA722010CLA330	25C	1TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HUA72201	A39C	1TB	3.5"	7200
Hitachi*	SATA	6Gb/s	HDS723030ALA640	A380	3TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDS72202ALA330	A20N	2TB	3.5"	7200
Hitachi*	SATA	3Gb/s	HDT72010SLA360	A3AA	1TB	3.5"	7200
IBM*	SAS	6Gb/s	ESXST9146852SS	B623	146GB	2.5"	15K
IBM*	SAS	3Gb/s	ESXSST973452SS	B6233	72GB	2.5"	15K
IBM*	SAS	3Gb/s	ESXSMA3073RC	T904	80GB	3.5"	15K
IBM*	SAS	3Gb/s	ESXSBBA036C3ESTT0Z	BH0D	36GB	3.5"	10K
IBM*	SAS	3Gb/s	MAX3073RC	T904	73GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA073C3-ETS10N	A540	73GB	3.5"	15K
IBM*	SAS	3Gb/s	MAX3147RC	T904	146GB	3.5"	15K
IBM*	SAS	3Gb/s	ST3300555SS	BA33	300GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA146C3-ETS10	A49A	146GB	3.5"	15K
IBM*	SAS	3Gb/s	ST3146855SS	BA23	146GB	3.5"	15K
IBM*	SAS	3Gb/s	ST3300555SS	BA33	300GB	3.5"	15K
IBM*	SAS	3Gb/s	GNA300C3ESTT0ZN	BH0D	300GB	3.5"	15K
IBM*	SAS	3Gb/s	MBC2073RC	SC03	73GB	2.5"	15K
IBM*	SAS	3Gb/s	ST973452SS	B623	73GB	2.5"	15K
IBM*	SAS	3Gb/s	BBA036C3ESTT0ZN	BH0D	36GB	3.5"	15K
IBM*	SAS	3Gb/s	ST336754SS	BA17	36GB	3.5"	15K
IBM*	SAS	3Gb/s	MAX3036RC	T904	36GB	3.5"	15K
IBM*	SAS	3Gb/s	ESXSVPA073C3	NA49	73GB	3.5"	15K
IBM*	SAS	3Gb/s	ST373454SS	BA1A	73GB	3.5"	15K
IBM*	SAS	3Gb/s	ST373455SS	BA23	73GB	3.5"	15K
IBM*	SAS	3Gb/s	MAX3073RC	T904	73GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA073C3-ETS10N	A540	73GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA073C3-ETS10N	A49A	73GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA073C3-ETS10N	A49B	73GB	3.5"	15K
IBM*	SAS	3Gb/s	GNA073C3ESTT0Z N	BH0G	73GB	3.5"	15K
IBM*	SAS	3Gb/s	GNA073C3ESTT0Z N	BH0D	73GB	3.5"	15K
IBM*	SAS	3Gb/s	ST3146855SS	BA23	146GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA146C3-ETS10	A49A	146GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA146C3-ETS10	A49B	146GB	3.5"	15K
IBM*	SAS	3Gb/s	VPA146C3-ETS10	A540	146GB	3.5"	15K
IBM*	SAS	3Gb/s	GNA300C3ESTT0Z N	BH0D	300GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS10K5_073SAS	BP05	73GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS15K2_73SAS	BG34	73GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS10K5_147SAS	BK05	146GB	3.5"	10K
Maxtor*	SAS	3Gb/s	8K147S0	MS05	146GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS10K5_300SAS	BP05	300GB	3.5"	10K
Maxtor*	SAS	3Gb/s	8K036S0	MS05	36GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS15K2_36SAS	BK00	36GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS15K2_36SAS	BP05	36GB	3.5"	15K
Maxtor*	SAS	3Gb/s	ATLAS10K5_073SAS	BG34	73GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_073SAS	BP00	73GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_147SAS	103	146GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_147SAS	BP05	146GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_300SAS	BP00	300GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_147SAS	BP00	146GB	3.5"	10K

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Maxtor*	SAS	3Gb/s	ATLAS10K5_73SAS	BG3H	73GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS15K2_36SAS	BG3R	36GB	3.5"	15K
Maxtor*	SATA	3Gb/s	6B300S0	1980	300GB	3.5"	7200
Maxtor*	SAS	3Gb/s	8J300S0	MS05	300GB	3.5"	10K
Maxtor*	SAS	3Gb/s	ATLAS10K5_73SAS	BG3R	73GB	3.5"	10K
Samsung*	SATA	3Gb/s	SP2504C	0-33	250GB	3.5"	7200
Samsung*	SATA	3Gb/s	HE103UJ	1111	1TB	3.5"	7200
Samsung*	SATA	3Gb/s	HE103UJ	1113	1TB	3.5"	7200
Seagate*	SAS	6Gb/s	ST973352SS	0002	73GB	2.5"	SED
Seagate*	SAS	6Gb/s	ST9450404SS	0004	450GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST31000424SS	0004	1TB	3.5"	7200
Seagate*	SAS	6Gb/s	ST3500414SS	0004	500GB	3.5"	7200
Seagate*	SAS	6Gb/s	ST9500431SS	DSF0	500GB	2.5"	7200
Seagate*	SAS	6Gb/s	ST973452SS	B623	73GB	2.5"	15K
Seagate*	SAS	6Gb/s	ST9146852SS	B623	146GB	2.5"	15K
Seagate*	SAS	6Gb/s	ST3300657SS	0006	300GB	3.5"	15K
Seagate*	SAS	6Gb/s	ST3450857SS	0005	450GB	3.5"	15K
Seagate*	SAS	6Gb/s	ST9146803SS	0002	146GB	2.5"	15K
Seagate*	SAS	6Gb/s	ST9146803SS	B235	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9146703SS	FT00	136GB	2.5"	SED
Seagate*	SAS	6Gb/s	ST9146803SS	0004	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9146802SS	MSB0	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9300603SS	B248	300GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9500430SS	0001	500GB	2.5"	7200
Seagate*	SAS	6Gb/s	ST9146703SS	MSB3	147GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9146802SS	MSB03	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9146802SS	0207	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9146803SS	ER60	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST32000444SS	0004	2TB	3.5"	7200
Seagate*	SAS	3Gb/s	ST973402SS	MSB0	73GB	2.5"	
Seagate*	SAS	3Gb/s	ST373455SS	00013LQ03M3L	73GB	3.5"	
Seagate*	SAS	3Gb/s	ST973401SS	S108	73GB	2.5"	10K
Seagate*	SAS	3Gb/s	ST336754SS	0003	36GB	3.5"	
Seagate*	SAS	3Gb/s	ST373454SS	0002	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	1503	146GB	3.5"	
Seagate*	SAS	3Gb/s	ST336754SS	S412	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3300555SS	MSB0	300GB	3.5"	
Seagate*	SAS	3Gb/s	ST3300655SS	0001	300GB	3.5"	
Seagate*	SAS	3Gb/s	ST936701SS	0023	36GB	2.5"	10K
Seagate*	SAS	3Gb/s	ST336754SS	S4123KQ0ST37	36GB	2.5"	15K
Seagate*	SAS	3Gb/s	ST973401SS	0002	73GB	2.5"	10K
Seagate*	SAS	3Gb/s	ST973402SS	0207	73GB	2.5"	10K
Seagate*	SAS	3Gb/s	ST973402SS	MS003	73GB	2.5"	10K
Seagate*	SAS	3Gb/s	ST3146756SS	D3C7	146GB	3.5"	SED
Seagate*	SAS	3Gb/s	ST3450056SS	D3C7	450GB	3.5"	SED
Seagate*	SAS	3Gb/s	ST336754SS	0023	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	S410	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	S4103KQ1SEDX	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	S4123KQ1TLFW	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	1501	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	1502	36GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	0023	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	S412	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	S410	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	0003	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	MS02	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373454SS	0002	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	S4123KN01YAD	146GB	3.5"	15K

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Seagate*	SAS	3Gb/s	ST3146854SS	S410	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	0003	146GB	3.5"	
Seagate*	SAS	3Gb/s	ST3146854SS	0002	146GB	3.5"	
Seagate*	SAS	3Gb/s	ST3146854SS	1503	146GB	3.5"	
Seagate*	SAS	3Gb/s	ST373454SS	1503	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	0033	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	0023	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST3146854SS	S412	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373455SS	S527	73GB	3.5"	
Seagate*	SAS	3Gb/s	ST3146854SS	MS04	146GB	3.5"	
Seagate*	SAS	6Gb/s	ST3600002SS	ER60	600GB	3.5"	10K
Seagate*	SAS	6Gb/s	ST336754SS	0004	146GB	2.5"	10K
Seagate*	SAS	6Gb/s	ST9300503SS	FT00	300GB	2.5"	SED
Seagate*	SAS	3Gb/s	ST3146855SS	S527	146GB	3.5"	
Seagate*	SAS	3Gb/s	ST3300056SS	081C	300G	3.5"	
Seagate*	SAS	3Gb/s	ST973401LSUN72G	0556	72GB	3.5"	
Seagate*	SAS	3Gb/s	ST3146356SS	0004	147GB	3.5"	
Seagate*	SAS	3Gb/s	ST373455SS	0002	73GB	3.5"	
Seagate*	SAS	3Gb/s	ST3146854SS	S412	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST373455SS	0002	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	0002	36GB	3.5"	
Seagate*	SAS	6Gb/s	ST3450802SS	0004	450GB	3.5"	10K
Seagate*	SAS	3Gb/s	ST31000640SS	E319	1TB	3.5"	
Seagate*	SAS	3Gb/s	ST936701SS	0002	36GB	2.5"	
Seagate*	SATA	6Gb/s	ST33000650NS	ZZA6	3TB	3.5"	7200
Seagate*	SATA	6Gb/s	ST32000641AS	CC13	2TB	3.5"	7200
Seagate*	SATA	6Gb/s	ST3500410AS	ZZATZZZZ	500GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3250824AS	H	250GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3500641NS	S	500GB	3.5"	
Seagate*	SATA	3Gb/s	ST3750640NS	D	750GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3750640NS	3QD1	750GB	3.5"	
Seagate*	SATA	3Gb/s	ST3750840NS	E	750GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3160827AS	0003	160GB	3.5"	
Seagate*	SATA	3Gb/s	ST3250620NS	3.AEE	250GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST31000340NS	SN03/SN06	1TB	3.5"	
Seagate*	SATA	3Gb/s	ST3160815AS	3.AAD	160GB	3.5"	
Seagate*	SATA	3Gb/s	ST3250824AS	3.AAH	250GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3808110AS	3AAH	80GB	3.5"	
Seagate*	SATA	3Gb/s	ST3160815AS	D	160GB	3.5"	
Seagate*	SATA	3Gb/s	ST3200540AS	CC83	2TB	3.5"	4K Media 7200
Seagate*	SATA	3Gb/s	ST31000333AS	CC1F	1TB	3.5"	
Seagate*	SATA	3Gb/s	ST3750840AS	3.AAD	750GB	3.5"	
Seagate*	SATA	3Gb/s	ST9500530NS	SN02	500GB	2.5"	
Seagate*	SATA	3Gb/s	ST980825AS	0003	80GB	2.5"	
Seagate*	SATA	3Gb/s	ST3250620NS	20.06C07	250GB	3.5"	
Seagate*	SATA	3Gb/s	ST3250620NS	3.AEJ	250GB	3.5"	
Seagate*	SATA	3Gb/s	ST3250620NS	E	250GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST3750640NS	.AEP	750GB	3.5"	
Seagate*	SATA	3Gb/s	ST3500630NS	W	500GB	3.5"	
Seagate*	SATA	3Gb/s	ST3500641AS	E	500GB	3.5"	
Seagate*	SATA	3Gb/s	ST3500320NS	SN05	500GB	3.5"	
Seagate*	SATA	3Gb/s	ST3160827AS	0003	160GB	3.5"	
Seagate*	SATA	3Gb/s	ST3500641AS	A002	500GB	3.5"	7200
Seagate*	SATA	3Gb/s	ST380815AS	C002	808GB	3.5"	
Seagate*	SATA	3Gb/s	ST31000340NS	SU09/SU0D	1TB	3.5"	
Seagate*	SATA	3Gb/s	ST31000340NS	SN06	1TB	3.5"	
Seagate*	SATA	3Gb/s	ST32000644NS	SN11	2TB	3.5"	

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Seagate*	SAS	3Gb/s	ST973402SS	MS00	73GB	2.5"	10K
Seagate*	SATA	3Gb/s	ST380013AS	0003	80GB	3.5"	
Seagate*	SAS	3Gb/s	ST373455SS	S513	73GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST336754SS	S400	36GB	3.5"	
Seagate*	SAS	3Gb/s	ST314854SS	0004	146GB	3.5"	15K
Seagate*	SAS	3Gb/s	ST936751SS	F401	36GB	2.5"	
Seagate*	SATA	3Gb/s	ST31000524NS		1TB	3.5"	7200
Seagate*	SAS	6Gb/s	ST33000650SS	F901	3TB	3.5"	
Western Digital*	SAS	6Gb/s	WD1460BKFG-02P2V0	RG00	146GB	2.5"	10K
Western Digital*	SAS	6Gb/s	WD3000BKFG-02P2V0	RG00	300GB	2.5"	10K
Western Digital*	SAS	6Gb/s	WD6000BKHG-02A29V0	VG01	600GB	2.5"	10K
Western Digital*	SATA	6Gb/s	WD6000BLHX-01V7BV0	5G04	600GB	2.5"	10K
Western Digital*	SATA	6Gb/s	WD5003ABYX-01WERA0	1S01	500GB	3.5"	7200
Western Digital*	SATA	6Gb/s	WD1003FBYX-01Y7B0	1V01	1TB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2002FYPS-02W3B0	1G01	2TB	3.5"	5400
Western Digital*	SATA	3Gb/s	WD2003FYYS-0	0D01	2TB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2002FYPS0	5G04	2TB	3.5"	5400
Western Digital*	SATA	3Gb/s	WD10EADS11M	0A80	1TB	3.5"	4K Media
Western Digital*	SATA	3Gb/s	WD5000ABPS-01ZZB0	1B01	500GB	3.5"	5400
Western Digital*	SATA	3Gb/s	WD1600YS	6C04	160GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2000		200GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2500YS-18S	6C07	250GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2500YS-23S	6C04	250GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD500YS	2/E07	500GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2500YS	WCAN	250GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1000FYPS-01ZKB0	1B01	1TB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5001ABYS-01TNA0	1B01	500GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5000YS-01M	20000000	500GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5002ABYS-01B1B0	3B03	500GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD3000HLFS-0	4V01	300GB	3.5"	10K
Western Digital*	SATA	3Gb/s	WD1002FBYS-0	0C05	1TB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD3202ABYS	3B03	320GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5000ABYS-0	1C01	500GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1600AABS	6H05	600GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD800JD	0010	80GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1200JS	1C03	120GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD740GD-00FL	8F33	740GB	3.5"	10K
Western Digital*	SATA	3Gb/s	WD1600JS-00M	1C03	160GB	3.5"	
Western Digital*	SATA	3Gb/s	WD4000YR	6A01	400GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD2500JS	1C03	250GB	3.5"	
Western Digital*	SATA	3Gb/s	WD4000YD-00K	6G11	400GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD4000YD-00K	6A01	400GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5000KS	2000000	500GB	3.5"	
Western Digital*	SATA	3Gb/s	WD7500AY	4G30	750GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD7500AAKS-0	4G30	750GB	3.5"	
Western Digital*	SATA	3Gb/s	WD1003FBYX	1TB	1S01	3.5"	7200
Western Digital*	SATA	3Gb/s	WD5003ABYX	500GB	1V01	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1600AAJS	6H05	160GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1600JS-75NCB3	20000	160GB	3.5"	7200
Western Digital*	SATA	3Gb/s	WD1600JS	6C04	160GB	3.5"	7200
ADATA*	SATA	3Gb/s	AS599S-128GM-C	3.1.0	128GB	2.5"	
ADATA*	SATA	3Gb/s	AS599S-256GM-C	3.1.0	256GB	2.5"	
CORSAIR*	SATA	3Gb/s	CMFSSD-64D1	0000	64GB	2.5"	
Intel*	SATA	3Gb/s	X25-E,SSDSA2SH032G1	8790	32GB	2.5"	
Intel*	SATA	3Gb/s	X25-E,SSDSA2SH064G1	8790	64GB	2.5"	
Intel*	SATA	3Gb/s	X25-E,SSDSA2SH064G1GN	8850	64GB	2.5"	
Intel*	SATA	3Gb/s	X25-M,SSDSA2MH080G1	8626	80GB	2.5"	

Manufacture	Type	Speed	Model	FW version	Capacity	Size	RPM
Intel*	SATA	3Gb/s	X25-M,SSDSA2MH160G1	8626	160GB	2.5"	
Intel*	SATA	3Gb/s	X25-M,SSDSA2MH160G1	8820	160GB	2.5"	
Intel*	SATA	3Gb/s	X25-M,SSDSA2M080G2GC	02HD	80GB	2.5"	
Intel*	SATA	3Gb/s	X25-M,SSDSA2MH160G2GC	02HD	160GB	2.5"	
Micron*	SATA	6Gb/s	P300-MTFDDAC100SAL	B901	100GB	2.5"	
OCZ Technology*	SATA	3Gb/s	ITDCSTE025M2002	1.5E	240GB	2.5"	
Patriot Memory*	SATA	3Gb/s	PatriotTorqx12	1881	120GB	2.5"	
Pliant*	SAS	3Gb/s	LS300S	T101	300GB	3.5"	
Samsung*	SATA	3Gb/s	MCBQE25G		25GB	2.5"	
Samsung*	SATA	3Gb/s	2.5"50GBSSDSATA	803Q	50GB	2.5"	
Samsung*	SATA	3Gb/s	2.5"100GBSSDSATA	803Q	100GB	2.5"	
STEC*	SATA	1.5Gb/s	MACH8 IO	2084	22GB	2.5"	
STEC*	SATA	1.5Gb/s	M8ISB2-25UC	2119	25GB	2.5"	
STEC*	SATA	1.5Gb/s	M8ISB2-50UC	2119	50GB	2.5"	
UNIGEN*	SATA	3Gb/s	UGB88PGB100HB1-ES	RC Rev1	100GB	2.5"	
Super Talent*	SATA	3Gb/s	UGB88APT128HS3	1916	128GB	2.5"	
Super Talent*	SATA	3Gb/s	FTM12CT25H	STTMP2	120GB	2.5"	
ANOBIT*	SATA	3Gb/s	Genesis-1	2.21	200GB	3.5"	
PLIANT*	SAS	3Gb/s	LB150M	P103	150GB	2.5"	
PLIANT*	SAS	3Gb/s	LB150S	P103	150GB	2.5"	
PLIANT*	SAS	3Gb/s	LB200M	P200	200GB	2.5"	
PLIANT*	SAS	3Gb/s	LB400M	P200	400GB	2.5"	
PLIANT*	SAS	3Gb/s	LS150S	P104	150GB	3.5"	
Micron*	SATA	6Gb/s	MTFDDAC050SAL-1N1AA	0001	50GB	2.5"	
Micron*	SATA	6Gb/s	MTFDDAC200SAL-1N1AA	0001	200GB	2.5"	
Micron*	SATA	6Gb/s	MTFDDAK064MAG-1G1	0002	64GB	2.5"	
Micron*	SATA	6Gb/s	MTFDDAK128MAG-1G1	0002	128GB	2.5"	
Micron*	SATA	6Gb/s	MTFDDAK256MAG-1G1	0002	256GB	2.5"	
KINGSTON*	SATA	3Gb/s	SNVP325-S2/256GB	0201	256GB	2.5"	
KINGSTON*	SATA	3Gb/s	SNVP325-S2/512GB	0202	512GB	2.5"	
Intel*	SATA	3Gb/s	SSDSA2BW160G3	0266	160GB	2.5"	
Intel*	SATA	6Gb/s	SSDSC2MH120A2C	PPXM	120G	2.5"	