Ci Design
RS2600

http://www.cidesign.com

Chassis Configuration (as tested with Intel's Server Board SCB2)

Model tested: RS2600
Fans (qty x size): 3 x (80mmx80mm)
Hard drives: 6
Processor: 2x1 GHz Pentium III (FC-PGA2)
Memory: 128 MB X 6
Power Supply: SeaSonic (SS-350FK)
RAID: N/A
Additional Information:

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

Product Information

Model#: RS2600

Size (LxWxH inches): 24"x17"x3.5"

Size (LxWxH millimeters): 609.6 x 431.8 x 88.9

5.25" Bays: 1 x Half Height

3.50" Bays: 1 x 1.6" Height for FDD or DAT/DSS Tape

Fans: 3 x (80mm x 80mm)

Power Supply: Ci Design/SS-350FK/350W

Other Information: Up to 3 standard and 3 Low Profile PCI Card support, Optional FDD and Slim CD-ROM Combo Tray for the 5.25" Bay

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

List of Intel
Real Server Boxed Boards

Mechanically Compatible with:

SCB2

Thermally Compatible with:

SCB2