



2U Rack RS 2100i

www.cidesign.com



Product Information

Model#: RS 2100i

Size: (LxWxH in): 24 x 19 x 3.468

Size: (LxWxH mm): 609.6 x 482.6 x 88.1

5.25" Bays: 1

3.50" Bays: 1 standard and 4 x SCA/IDE

Fans: 4 system fans (80mm x80mm)

Power Supply: 460W

Other Information: Optional Slimline CD-Rom/FDD kit

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: Rack Server Series

Options: Fixed IDE, Removable IDE, hot swap SCSI

Chassis Configuration As tested with Intel® Server Board SE7501BR2. Posting on Server Board SE7501HG2 Reference Chassis list based On Mechanical and Thermal similarity

Model tested: RS 2100i

Fans (qty x size): 4 x 80mm 2 Sanyo Denki 109R0612G4031 Processor fans.

Hard drives: 3 x Seagate* SCSI ST318406LC

Processor: 2 x Intel© 2.8 GHz Xeon™

Memory: 4 x Samsung* 128M DDR266 DIMM M386L1713BTI-CA0

Power Supply: EMACS* 460W R2W-6460P

Additional Information:

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

SE7501BR2 & SE7501HG2

Thermally Compatible with:

SE7501BR2 & SE7501HG2

* Third party names and brands are the property of their respective owners.